




**GEOENVIRONMENTAL ASSESSMENT  
GROVE HOUSE  
SELLINDGE, KENT  
GLADMAN  
GEA-22653H-25-59  
MARCH 2025**

**IDOM**



GEOENVIRONMENTAL ASSESSMENT  
GROVE HOUSE  
SELLINDGE, KENT  
GLADMAN  
GEA-22653H-25-59  
MARCH 2025

### Document Issue Record

Status	Final	Date of Issue	18/03/25
Prepared by		Approved by	
Ben Alexander		Nathan Dellow	
			
Callum Moller		MCIWEM, MEnvSc, CEnv	
		BSc (Hons), FGS	

Rev	Prepared	Approved	Date of Issue	Reason(s) for Revision
1	CMM	SAH	18/03/2025	Updated preliminary foundation zoning

## TABLE OF CONTENTS

EXECUTIVE SUMMARY .....	I
SECTION 1 INTRODUCTION .....	2
SECTION 2 TIER 1 (NON-INTRUSIVE INVESTIGATION) .....	3
2.1 INTRODUCTION .....	3
2.2 SITE LOCATION AND SETTING .....	3
2.3 SITE HISTORY .....	4
2.4 GEOLOGY .....	4
2.5 HYDROGEOLOGY .....	5
2.6 HYDROLOGY .....	5
2.7 FLOODING .....	5
2.8 CURRENT SITE ISSUES .....	6
2.9 INDICATIVE GROUND STABILITY HAZARDS .....	6
2.10 MINING, GROUND WORKINGS AND NATURAL CAVITIES .....	6
2.11 RADON GAS .....	6
2.12 UXO .....	8
SECTION 3 PRELIMINARY CONCEPTUAL SITE MODEL AND PRELIMINARY RISK ASSESSMENT 9	
SECTION 4 SITE INVESTIGATION RATIONALE .....	9
4.1 INTRODUCTION .....	9
4.2 SITE INVESTIGATION METHODS .....	9
SECTION 5 GROUND CONDITIONS .....	11
5.1 SUMMARY .....	11
5.2 TOPSOIL .....	11
5.3 HEAD DEPOSITS .....	11
5.4 SANDGATE FORMATION .....	12
SECTION 6 PRELIMINARY GEOTECHNICAL RECOMMENDATIONS .....	13
6.1 GEOTECHNICAL LABORATORY TESTING .....	13
6.2 FOUNDATIONS .....	13
6.3 EXCAVATIONS AND GROUNDWATER .....	14
6.4 FLOOR SLABS .....	15
6.5 BURIED CONCRETE .....	15
6.6 ROADS AND PAVED AREAS .....	15
6.7 EARTHWORKS .....	15
6.8 SOAKAWAYS .....	16
SECTION 7 ENVIRONMENTAL ASSESSMENT – SOIL QUALITY .....	16
7.1 RESULTS .....	16
7.2 SUMMARY .....	18
SECTION 8 ENVIRONMENTAL ASSESSMENT – GROUNDWATER QUALITY .....	18
8.1 RESULTS .....	18
8.2 DISCUSSION .....	19
SECTION 9 ENVIRONMENTAL ASSESSMENT - HAZARDOUS GAS .....	19
9.1 RESULTS .....	19
SECTION 10 ENVIRONMENTAL ASSESSMENT - VAPOUR .....	22
10.1 RESULTS .....	22
SECTION 11 WASTE CLASSIFICATION, OFF-SITE DISPOSAL OR RE-USE .....	22
11.1 WASTE CLASSIFICATION .....	22

	11.2	RE-USE CONSIDERATIONS .....	23
SECTION 12		GENERIC QUANTITATIVE RISK ASSESSMENT (TIER 2) .....	24
	12.1	INTRODUCTION .....	24
	12.2	SOIL CONTAMINATION (HEAVY METALS, HYDROCARBONS, PESTICIDES AND HERBICIDES) .....	25
	12.3	SOIL CONTAMINATION (ASBESTOS) .....	27
	12.4	CONTROLLED WATERS (GROUNDWATER) .....	27
	12.5	HAZARDOUS GAS .....	28
	12.6	VAPOUR .....	31
	12.7	RADON .....	32
SECTION 13		UPDATED COMBINED CONCEPTUAL SITE MODEL AND RISK ASSESSMENT ....	33
SECTION 14		DETAILED QUANTITATIVE RISK ASSESSMENT (TIER 3) .....	35
SECTION 15		PRELIMINARY REMEDIATION STRATEGY AND RECOMMENDATIONS .....	35
	15.1	INTRODUCTION .....	35
	15.2	GAS / VAPOUR PROTECTION .....	35
	15.3	PROTECTION OF CONSTRUCTION WORKERS .....	35
	15.4	WATER SUPPLY PIPES .....	36
	15.5	WASTE .....	36
	15.6	OTHER RECOMMENDATIONS .....	36
SECTION 16		CONCLUSIONS .....	36

#### APPENDIX 1

- Site Location Plan CSA-3256-114
- Topographic Survey 2019-070\_Topo\_01-04\_2d\_RevD
- Development Framework Plan CSA-5622-115

#### APPENDIX 2

- Radon Potential Dataset Mapping

#### APPENDIX 3

- Risk Assessment Methodology

#### APPENDIX 4

- Site Investigation Location Plan

#### APPENDIX 5

- Exploratory Hole Logs

#### APPENDIX 6

- Soil Chemistry
- Summary Spreadsheet
- Laboratory Analysis Certificates

#### APPENDIX 7

- Geotechnical Laboratory Certificates

APPENDIX 8

- Groundwater Chemistry
- Laboratory Analysis Certificates

APPENDIX 9

- Field Monitoring Records
- Groundwater Level Data
- Hazardous Soil Gas Data

APPENDIX 10

- Gas Risk Assessment

EXECUTIVE SUMMARY

A Geoenvironmental Assessment was requested by Gladman. The purpose of the assessment was to identify any contaminative or geotechnical issues associated with former land use at *Grove House, Sellindge, Kent* which might impact on the sites redevelopment.

SITE DETAILS							
Approximate Area (ha)	Centred on OSGB Eastings, Northings	Previous Use(s)		Current Use		Proposed Use	
2.95	609960, 138210	Open fields		Open fields for livestock grazing		Residential	

PHASE 1 NON-INTRUSIVE INVESTIGATION							
Geology			Groundwater Aquifer		Surface Water	Radon	
Made Ground	Superficial	Solid	Superficial	Solid			
None present	Head	Sandgate & Hythe Formations	No SPZ	No SPZ – 1900m W for nearest abstraction	Ponds to south of site, no major surface water within 250m of site	Basic radon protection required – Majority of site in RnC4.	

PHASE 2 INTRUSIVE INVESTIGATION					
Geology			Contamination		Waste Classification
Made Ground	Superficial	Solid	Source ► Pathway ► Receptor		Risk Rating
None encountered	Head	Sandgate Formation	No contamination was encountered above residential screening levels.		VERY LOW

Geotechnical					
Foundations		Buried Concrete	Roads and Pavement	Earthworks	Soakaway
Traditional strip footings at depths between 1.0 and 2.0 m bgl are suitable for allowable bearing pressures of 100 kN/m². Two zones remain low strength at 2.0 m where ground improvement or piles are recommended. Additional deepening is required within the zone of influence of trees.		DS-1, AC-1	CBR values range between 2.3 and 4.2 %	Not considered at this stage	Unlikely to be suitable.

RECOMMENDATIONS			
Remediation	Waste / Re-use	Geotechnical	Other
Basic radon protection required.	WAC tests for wastes destined for landfill	Ground improvement of soft soils. Additional investigation may be required to inform piled foundation design in the zone of influence of trees and untreated soft soils.	UXO supervision and non-intrusive magnetometer surveys required for intrusive works. Intrusive magnetometer surveys required for piling locations.

## SECTION 1 INTRODUCTION

- 1.1 Gladman proposes to develop an area of land located at Grove House, Ashford Road, Sellindge, Kent TN25 6JX for residential development purposes. No proposed development plans were available at the time of writing. A Development Framework Plan is included in Appendix 1, along with a site location plan and topographic survey.
- 1.2 IDOM Merebrook Limited (IDOM) has been commissioned by Gladman to undertake preliminary site investigation works and to advise on the geo-environmental implications of the redevelopment of the site for the proposed end use.
- 1.3 The objectives of the investigation are to:
  - i.* Assess surface and sub-surface ground conditions present at the site;
  - ii.* Identify hazards associated with ground contamination which may place constraints on the site and the proposed development;
  - iii.* Evaluate the risks associated with any identified hazards;
  - iv.* Provide preliminary recommendations for the mitigation of any significant risks identified; and
  - v.* Provide preliminary geotechnical recommendations.
- 1.4 A Tier 1 Preliminary Risk Assessment (Non-intrusive Investigation) and a Tier 2 Generic Quantitative Risk Assessment (Preliminary Exploratory Investigation) have been undertaken for the subject site.
- 1.5 This report presents the findings of the investigation and provides an interpretation of the geo-environmental conditions that exist at the site. The contaminative status of the site and the implications with respect to development have been interpreted in accordance with the current government guidance on source-pathway-receptor risk assessment. This report follows LCRM (Land Contamination Risk Management) guidance to appraise land contamination hazards associated with the site.
- 1.6 This report has been prepared for Gladman for the sole purpose described above and no extended duty of care to any third party is implied or offered. Third parties making reference to the report should consult Gladman and IDOM as to the extent to which the findings may be appropriate for their use.

## **SECTION 2 TIER 1 (NON-INTRUSIVE INVESTIGATION)**

### **2.1 INTRODUCTION**

2.1.1 A non-intrusive investigation has been conducted by RSK in report 52109 R01(01) – Land to the south of Ashford Road, Sellindge (August 2019). The report has been summarised within the following sections and been used to inform the decisions of the IDOM site investigation and subsequent risk assessment. Section 2.2 was written based on the site as seen during the IDOM site investigation in January 2025.

2.1.2 The above report used authoritative sources, and it is believed that they are reasonably reliable. However, independent verification of the information supplied has not necessarily been carried out and IDOM cannot be held liable for inaccuracies or deficiencies in the information.

### **2.2 SITE LOCATION AND SETTING**

2.2.1 The site is located to the south of Ashford Road, Sellindge, Kent TN25 6JX with the proposed development occupying open fields surrounding a residential property known as Grove House. The site is currently used for livestock grazing.

2.2.2 The site occupies an area of approximately 2.95 hectares located at National Grid Reference 609960, 138210 and indicated on drawing CSA-3256-114, presented in Appendix 1 of this report.

2.2.3 The site is bounded by Ashford Road to the north with residential properties, open fields and a public house beyond. To the west and south the site is bounded by the open fields of Potten Farm and to the east the site is bounded by Bulls Lane with residential properties beyond. Grove house and associated parking and landscaped areas are situated within the centre of the site but are not part of the proposed development area. The outer site boundaries consist of wire fences, with wooden panel fencing and brick walls bounding Grove House.

2.2.4 The site surface is grass covered. The site topography slopes gently from south to north with the slope becoming steeper for a short distance around the centre of the site, creating a terraced effect. The bank between the upper southern terrace and lower northern terrace runs from the centre of the western boundary with Potten Farm to the western boundary of Grove House. A pond is located a few metres to the south of the southeastern corner of site, within the grounds of Grove House. A ditch runs from Grove House and curves round to the southern boundary to the west, before running east along the southern boundary. Water was present within the ditch around the Grove House boundary.

2.2.5 No visual contamination was evident on site. Sparsely populated mature and semi mature trees line the boundaries of site and occur within the site.

## 2.3 SITE HISTORY

- 2.3.1 The site has remained as open fields with localised trees since 1873, with a tennis court in the east of the site between 1971 and 1989 which partially overlaps the subject site. Farmland and residential properties have surrounded the site since the 1800s.




Figure 1: Extract from 1971 mapping (from RSK Desk Study). Note: Grove House and surrounds are excluded from the study area

## 2.4 GEOLOGY

### 2.4.1

2.4.2 Table 1 summarises British Geological Survey (BGS) mapping for the site:

Table 1: Summary of published geology

Geological Unit	Type	Description
Superficial	Head	Clay and silt,
Bedrock	Sandgate Formation	Fine sands, silts and silty clays, commonly glauconitic; some sands limonitic or calcareous; some soft sandstones.
Bedrock	Hythe Formation	Alternating sandy limestones ("Ragstone") and glauconitic sandy mudstones.

## 2.5 HYDROGEOLOGY

- 2.5.1 The aquifer status of groundwater held within the geological units, the presence Source Protection Zones and related potable abstractions are summarised in Table 2 below:

Table 2: Summary of published hydrogeology

Geological Unit	Aquifer Designation	Source Protection Zone	Location of Potable Abstraction
Head	Unproductive	No SPZ	1900 m W
Sandgate Formation	Secondary A aquifer		
Hythe Formation	Principal Aquifer		

## 2.6 HYDROLOGY

- 2.6.1 The nearest identified surface water features to the site are the ponds located within the grounds of Grove House. There are multiple land drains located to the NE, NW, and SW within 500m of the site including a medium sized lake with weirs located 300m N. The East Stour River is located 500m south – flowing NW to SE.
- 2.6.2 There are 3no. current licensed surface water abstractions within a 2 km radius of the site located 1700m and 1940m NE and used for general agriculture and spray irrigation.

## 2.7 FLOODING

- 2.7.1 The site has limited potential for groundwater flooding to occur in the SE and N of the site and predominantly low risk of flooding from surface water with a small area deemed high risk in the north of the site. A flood risk assessment (FRA) was outside the scope of the report.

## 2.8 CURRENT SITE ISSUES

- 2.8.1 Potentially significant environmental issues have been investigated within relevant distances of the site, based on the database of records supplied by Landmark as summarised in Table 3 below.

Table 3: Potentially significant environmental issues

Environmental Category	Description
Water discharge or pollution incidents within 250 m	Oil in ditch 200m E, 26th November 1997. Category 3 –Minor incident. This is unlikely to impact the site
Waste management sites within 250 m	None within 250m of the site.
Statutory authorisations within 50 m	None within 250m of the site.
Trades of possible contaminative use within 50 m	None within 250m of the site.
Special protection or conservation areas within 50 m	None within 250m of the site.

## 2.9 INDICATIVE GROUND STABILITY HAZARDS

- 2.9.1 Geotechnical hazards identified that could be present and affect the site include:

- i.* Sudden lateral changes in ground conditions;
- ii.* Shrinkable clay soils; and
- iii.* Silt rich soils susceptible to rapid loss of strength in wet conditions.

## 2.10 MINING, GROUND WORKINGS AND NATURAL CAVITIES

- 2.10.1 None within a radius that will affect the site.

## 2.11 RADON GAS

- 2.11.1 The licensed Radon Potential Dataset for the site has been consulted. The Radon Potential is shown in six discrete Radon Classes (RnC1 to RnC6) as set out in

- 2.11.2 Table 4. The Radon Class is defined as a percentage probability range of dwellings exceeding the Radon Action Level.

Table 4: Radon classes, risk and mitigation

Radon Class (probability range)	General Risk	Affected Area ?	Building Control Regulations (England and Wales)
1 (0 to <1%)	low	No	No *
2 (1 to <3%)	medium	Yes	No *
3 (3 to <5%)		Yes	Yes - Basic
4 (5 to <10%)		Yes	Yes - Basic
5 (10 to <30%)	high	Yes	Yes - Full
6 (30 to 100%)		Yes	Yes - Full

\* Fitting radon protection in new buildings might be considered if there is a high risk location such as a routinely occupied basement

2.11.3 The licensed Radon Potential Dataset has been obtained from Groundsure which illustrates the 25 m tiled mapping and is provided in Appendix 2. The Radon Potential Dataset has changed since they were obtained by RSK in 2019. The Groundsure Radon Check provides the latest version as of February 2025. This data is the highest resolution radon dataset available for the UK, produced to a 50 m accuracy. This data has been pre-buffered to account for the relative accuracy and other uncertainties, so no additional buffering on site is required. Figure 1 below shows an insert of the Groundsure radon maps.

2.11.4 The site-specific Radon Potential Dataset and Guidance issued by the Buildings Research Establishment (BRE-211) indicates that:

- i. The majority of the site lies within an area designated RnC4 and basic protection measures are required under the Building Control Regulations.
- ii. Small areas in the north and west of the site lie within RnC2 where radon protection measures are not required.

2.11.5 Basic radon protection consists of a well-installed damp-proof membrane, modified and extended to form a gas-tight radon-proof barrier between the ground and the building. Subject to agreement with the Council and NHBC, there is a possibility the proposed development could be zoned with basic radon protection measures in structures within RnC4 only.




Figure 2: Groundsure radon maps.

- 2.11.6 Temporary site buildings can also be affected by radon. The Ionising Radiations Regulations 2017 apply where "any work (other than a practice) is carried out in an atmosphere containing radon 222 gas at an annual average activity concentration in air exceeding  $300 \text{ Bq.m}^{-3}$ ." In accordance with HSE guidance, a site specific radon risk assessment for the workplace should be carried out where buildings are located in an area affected by radon (RnC2 and above).

## 2.12 UXO

- 2.12.1 A detailed UXO risk assessment was carried out by Brimstone (DRA-24-1799-IDOM121R-LandtotheSouthofAshfordRoad,Sellindge,Kent) which assessed the site as a moderate risk. UXO safety awareness briefings and EOD engineer supervision on all intrusive works, intrusive magnetometer probe surveys on piling positions and non-intrusive magnetometer surveys on open excavations were recommended.

### **SECTION 3 PRELIMINARY CONCEPTUAL SITE MODEL AND PRELIMINARY RISK ASSESSMENT**

- 3.1 A preliminary conceptual site model (CSM) and Preliminary Risk Assessment have been developed by RSK from the findings of the desk study and site reconnaissance.
- 3.2 The desk study and site reconnaissance has identified the following potentially significant sources of contamination:
- i.* Potential localised made ground deposits associated with surrounding development and historic tennis courts which partially overlap the subject site;
  - ii.* Hazardous ground gases from made ground; and
  - iii.* Asbestos, herbicides and pesticides from farming activities.
- 3.3 The potential pollutant linkages with a risk of low/moderate or above that may drive site investigation works include:
- i.* Direct contact with potentially impacted soils by future site occupants;
  - ii.* Chemical attack of potential hydrocarbon contamination on future potable water supply lines;
  - iii.* Vertical and lateral migration of potential hydrocarbon contamination within underlying Controlled Waters; and,
  - iv.* Inhalation of potentially hazardous soil vapours by future site users and adjacent site users.

### **SECTION 4 SITE INVESTIGATION RATIONALE**

#### **4.1 INTRODUCTION**

- 4.1.1 A site investigation rationale has been devised in accordance with the findings of the Tier 1 Assessment and the resultant preliminary conceptual site model and risk assessment. Priority contaminants were identified as metals, PAHs, asbestos, herbicides, pesticides and ground gases.
- 4.1.2 Intrusive sampling locations were chosen on the basis of providing broad spatial coverage of the site.

#### **4.2 SITE INVESTIGATION METHODS**

- 4.2.1 An intrusive investigation was carried out by IDOM between 21 January and 28 January 2025 and comprised the following scope of work:
- i.* One rotary core borehole (MBH101) to 19.3m metres below ground level (m bgl);

- ii. Eight shallow windowless sample probe holes (MWS101 to MWS108) to a depth of 3 to 4 m bgl;
  - iii. Six machine-dug trial holes (MTP101 to MTP106) to a depth of 2.2 to 3.5 m bgl; and
  - iv. Six CBRs (MCBR1 to MCBR6) on the surface of the natural soils below the topsoil.
- 4.2.2 Exploratory hole locations are indicated on drawing 22653-303-001 in Appendix 4. Logging of exploratory holes was undertaken by an IDOM Officer. Exploratory hole logs are contained in Appendix 5.
- 4.2.3 Rotary coring equipment was used to advance borehole MBH101. Standard Penetration Tests (SPTs) were performed at approximate 1 metre intervals. The tests involved driving a steel cone tipped series of rods into the ground over a distance of 450 mm using the repeated blows of a 63.5 kg weight allowed to free fall over a distance of 760 mm. The total number of blows required for the final 300 mm penetration (the 'N' value) is recorded on the window sample logs.
- 4.2.4 A tracked windowless sampling rig was used to advance MWS101 to MWS108. This comprised a rig-mounted drop hammer to drive a hollow steel barrel into the ground. The barrel is recovered along with a removable plastic sleeve, which lines the barrel and holds a core of soil which is retracted for logging and sampling. SPTs were performed at approximate 1 m intervals in all windowless sample holes.
- 4.2.5 Details of monitoring installations in boreholes are summarised in Table 5.

Table 5: Summary of gas and groundwater monitoring installations

Location Ref	Depth To Top of Response Zone (m bgl)	Depth To Base Of Response Zone (m bgl)	Strata
MWS101	1.0	3.0	Head Deposits / Sandgate Formation
MWS104	1.0	3.0	Sandgate Formation
MWS106	1.0	3.0	Head Deposits / Sandgate Formation

- 4.2.6 Representative soil samples were taken from various depths and strata to assess the contaminative status of the site. Soil samples were submitted to an MCERTS/UKAS accredited laboratory for chemical analysis of a broad suite of potential contaminants. The results are provided in Appendix 6.
- 4.2.7 A programme of geotechnical laboratory testing was performed on selected soil samples obtained from the boreholes, comprising classification and strength tests. Chemical testing was also undertaken to assess the aggressiveness of the ground with respect to buried concrete. The results are provided in Appendix 7.

## SECTION 5 GROUND CONDITIONS

### 5.1 SUMMARY

- 5.1.1 No surface treatment was present on site and the site surface consisted of grass covered topsoil.
- 5.1.2 The strata encountered were consistent with the published geology.
- 5.1.3 A summary of the ground conditions encountered is presented in Table 6, whilst a more detailed assessment of the strata is contained in the following sections of the report.

Table 6: Summary of sub-surface ground conditions

Strata	Depth to Top of Range (m bgl)	Thickness Range (m)
Topsoil	0.0	0.2 – 0.5
Head deposits	0.2 – 0.5	0.7 – 1.6
Sandgate Formation	0.2 – 2.2	Base not proven – rock head at 11.50m

### 5.2 TOPSOIL

- 5.2.1 Generally consisted of a dark brown slightly sandy slightly gravelly clay with gravels of flint and occasional brick.
- 5.2.2 No visual or olfactory evidence of contamination was encountered.

### 5.3 HEAD DEPOSITS

- 5.3.1 The Head deposits were encountered in all exploratory holes underlying the topsoil. The only exception is within MBH101, MTP104 and MTP105 where the Head deposits were not encountered. This stratum was typically encountered to a depth of between 1.0 and 1.5 m below ground level (bgl) although was notably deeper in MTP103 and MWS101 where this stratum was encountered to a depth of 2.2 and 1.90 m bgl, respectively.
- 5.3.2 The Head deposits generally consist of a soft to firm slightly sandy clay. The boundary between the Head deposits and Sandgate Formation was difficult to distinguish but generally was marked by a change from brown to grey colours and a noticeable increase in sand content.
- 5.3.3 No visual or olfactory evidence of contamination was encountered in the head deposits.
- 5.3.4 Groundwater was not generally encountered; however, a slight seepage was observed in MTP103 at a depth of 2.2 m bgl .

5.3.5 Hand shear vanes were carried out within the Head deposits at depths ranging between 1.60 and 2.0 m. Undrained shear strengths ranged between 30 and 60 kPa with a mean value of 41 kPa.

5.3.6 Due to its limited thickness, SPTs were only carried out at a depth of 1.0 m in windowless sample borehole numbers MWS101, MWS106 and MWS107 with corresponding N-values ranging between 7 and 13 indicative of soils of low to medium strength.

#### 5.4 SANDGATE FORMATION

5.4.1 The Sandgate Formation generally consisted of sandy clays, sands and clayey sands interbedded to a depth of 11.50 m bgl. Rock head was encountered at 11.50 m bgl in MBH101 and consisted of a moderately weak greenish grey fine-grained sandstone with shell fragments. Fractures were very closely to closely spaced and undulating (Min = 5cm, Max = 63cm, Average 26cm) at 80 to 90 degrees. The strength of the rock increased with depth to strong or greater from 13.20 m and became grey in colour.

5.4.2 No visual or olfactory evidence of contamination was encountered in the Sandgate Formation.

5.4.3 Groundwater was encountered at 1.17 to 3.50 m bgl in MWS101 to MWS104 during drilling. Within Trial pits MTP101 and MTP102, fast ground water ingress was encountered at 2.90 m bgl and within MTP106 slight groundwater seepage was encountered at 1.0 m bgl.

5.4.4 No hand shear vanes were carried out in the Sandgate Formation due to its generally granular nature. SPT N-values generally increase with depth and are summarised in Table 7 below.

Table 7 – Summary of SPT N-values in the Sandgate Formation.

Depth	No. Tests	N-value range (mean)	Notes
1.0	5	2 – 10 (7)	Cohesive soils are empirically low to medium strength.
2.0	8	8 – 17 (13)	Clays are generally medium strength although locally high strength. One SPT in sand is medium dense.
3.0	8	7 – 38 (23)	Clays are medium to high strength (MWS104 remains low strength). Sands are medium dense.
4.0	6	14 – 50 (36)	Clays are high to very high strength (MWS104 remains medium strength). Sands are very dense. Refusal (N=50) achieved in three boreholes.
5.5m, 7m and 8.5	3 SPTs in MBH101 only	35, 47 and 49, respectively	Clays are high strength.
10 – 17.5 m	6 SPTs in MBH01 only	50 (refusal)	Sandstone recorded penetration between 75 and 225 mm.

## **SECTION 6 PRELIMINARY GEOTECHNICAL RECOMMENDATIONS**

### **6.1 GEOTECHNICAL LABORATORY TESTING**

- 6.1.1 Geotechnical classification and strength testing has been carried out on a number of samples. The results are contained in Appendix 7 and discussed below. The results of sulphate testing are summarised later in this report.
- 6.1.2 Atterberg limit classification was undertaken on nineteen samples from depths ranging between 0.50 and 9.0 m bgl. The modified plasticity index ranges between 12 and 34 % for all the samples indicating soils comprise low to medium plasticity clays. The volume change potential of these samples in accordance with NHBC standards is characterised for the site as medium-volume change potential.
- 6.1.3 In addition to the Atterberg limits classification, no sample was found to be significantly desiccated in line with Driscoll (1983)<sup>1</sup> when considering the natural moisture content in relation to 0.4x the liquid limit. The site appears to have historically been used for agriculture therefore the testing suggests no long-term risk associated with soil moisture deficit in relation to the historic agricultural usage. However, this does not preclude the risk of cyclic shrink/swelling from existing trees and foundations must still consider the effect existing trees may have on long-term differential settlements/heave.
- 6.1.4 Particle size distribution analysis was undertaken on two samples of the Sandgate Formation at depths ranging between 2.0 and 2.90 m bgl. These soils were described as sand in the exploratory hole logs although noted to be clayey are classified as Class 2A/B – general cohesive fill. In addition, one of the samples scheduled for Atterberg limits classification was also described as sand within the exploratory hole logs but were found to be of low plasticity clay.
- 6.1.5 Three samples of rock quality material were tested for point load strength index from MBH101 at depths ranging between 14.0 and 18.20 m bgl. Is(50) strength ranges between 2.86 and 6.06 MPa. Using a conversion factor of 24, these point load strengths indicate the rock stratum is of strong to very strong unconfined compressive strength.

### **6.2 FOUNDATIONS**

- 6.2.1 The proposed development includes a new residential development, predominantly within the western half of the site. It appears from the development framework that the eastern half of the site will remain undeveloped. A children's play area is proposed along the centre of the southern boundary.
- 6.2.2 The ground investigation proved a general thickness of Head deposits across the majority of the site to depths ranging between 1.0 and 1.50 m bgl, only absent from

---

<sup>1</sup> Driscoll, R. (1983) *The influence of vegetation on the swelling and shrinking of clay soils in Britain*. Geotechnique 33(2) pp 93-105

three of the exploratory holes. The Sandgate Formation underlies the superficial deposits and topsoil comprising variable cohesive and granular soils.

- 6.2.3 The underling soils are typically of medium-volume change potential therefore a minimum foundation depth of 0.90 m bgl will apply to new footings outside the zone of influence of existing trees and 1.25 m applies where accounting for restricted new planting.
- 6.2.4 The soils at minimum foundation depth are variable and a preliminary foundation zoning plan is provided in Appendix 1. The preliminary foundation zoning plan includes the zone of influence from existing trees based on the Arboricultural Impact Assessment Report (Ref: CSA/4059/14, dated June 2024). It also includes areas of reasonably consistent strata with allowable bearing pressure recommendations. Within the zone of influence of trees, the foundations should be deepened in accordance with NHBC guidance.
- 6.2.5 A zone is defined in the southwest corner (MTP104, MTP105, MWS106 and MWS107). In these exploratory holes, undrained shear strengths range between 60 and 80 kPa at 1.0 m depth therefore considered suitable for traditional strip/trench footings with an allowable bearing pressure of 100 kN/m<sup>2</sup>. Anticipated total settlements in this area is less than 25 mm for traditional footings up to 1.0 m wide.
- 6.2.6 Three yellow zones are highlighted on the plan in the north and around the southern and eastern site boundaries. In these areas the shallow soils are of very low to low strength; however, at 2.0 m depth the soils are reasonably consistent with undrained shear strengths of at least 55 kPa. Traditional strip/trench footings deepened to a depth of 2.0 m in these areas are calculated to have an allowable bearing pressure of 100 kN/m<sup>2</sup> with anticipated total settlements less than 25 mm for footings up to 1.0 m wide.
- 6.2.7 Two red zones are defined in the east and west where low strength soils persist at a depth of 2.0 m bgl. In these areas, 100 kN/m<sup>2</sup> will not be achievable at 2.0 m depth and it is recommended that an alternative foundation solution be adopted such as ground improvement or pile foundations.
- 6.2.8 It is considered that 100 kN/m<sup>2</sup> will be achievable at 1.0 m depth in ground improvement areas; however, the exploratory hole logs should be provided to a specialist contractor to confirm this. Additional deepening will still be required within the zone of influence of existing trees. Where additional deepening due to trees is anticipated to exceed 2.0 m then a piled foundation solution may be necessary.
- 6.2.9 Given the high variability of the soils, an allowance should be made for including mesh reinforcement in all traditional foundations.

### 6.3 EXCAVATIONS AND GROUNDWATER

- 6.3.1 Limited groundwater was encountered during the investigation, however fast groundwater ingress was noted in MTP101 and MTP102. At this stage it is

considered that only simple dewatering techniques such as sump pumping will be required.

- 6.3.2 Excavations generally remained stable in the short-term with the exception of MTP101 and MTP102 where collapses were noted at depths of 2.80 and 2.90 m bgl, respectively associated with the groundwater ingress. In the medium to long-term, excavations are likely to become unstable. In any case, construction workers must not enter excavations unless they are battered to a safe angle or shored, especially where groundwater is encountered.

#### 6.4 FLOOR SLABS

- 6.4.1 The underlying soils are characterised as medium-volume change potential. Ground bearing floor slabs are unlikely to be feasible. At this stage an allowance should be made for cast-in-situ suspended slabs or precast suspended floors with void dimensions in accordance with NHBC standards.

#### 6.5 BURIED CONCRETE

- 6.5.1 Recommendations given in BRE Special Digest 1:2005 "*Concrete in aggressive ground*" have been followed in order to give recommendations with respect to buried concrete.
- 6.5.2 Water soluble sulphate analysis was carried out on 10 soil samples obtained from depths of between 0.50 and 18.50 m bgl with soil pH determination also carried out on these samples. Water soluble sulphate contents ranged between 4 and 227 mg.l<sup>-1</sup>. In accordance with BRE guidelines the characteristic value is calculated by determining the mean of the highest 20 % of results. In this case the characteristic value is 193.5 mg.l<sup>-1</sup>. On this basis the Design Sulphate Class is DS-1.
- 6.5.3 The pH values in the soil samples varied between 5.4 and 8.5. The mean of the lowest 20 % of values is 5.75 which represents the characteristic value. Mobile groundwater conditions have been assumed and, on this basis, the Aggressive Chemical Environment for Concrete (ACEC) class for the site is AC-1.

#### 6.6 ROADS AND PAVED AREAS

- 6.6.1 CBR testing was carried out at six locations using a CBR plunger. CBR values range between 2.3 and 4.2 %. The results of CBR testing should be provided to the designer for roadway and footway design.

#### 6.7 EARTHWORKS

- 6.7.1 Proposed level changes have not been provided for the site. Limited testing of natural soils indicate they will be Class 2A/B – general cohesive fill and therefore geotechnically suitable for use. Once finished levels are known, cut/fill drawings, volume calculations and any necessary earthworks specification and material management plans can be produced by IDOM.

## 6.8 SOAKAWAYS

- 6.8.1 Soakaway testing was carried out in three trial excavations (MTP103 – MTP105). The testing did not record any change in water level in two of the tests (MTP104 and MTP105) and rose by 0.01 m in MTP103. On this basis, the soils are considered to be practically impervious and a soakaway drainage system will be unsuitable for the site.

## SECTION 7 ENVIRONMENTAL ASSESSMENT – SOIL QUALITY

### 7.1 RESULTS

- 7.1.1 A total of seven soil samples were submitted to the laboratory for chemical analysis, including 1 sample from natural ground and six samples from topsoil. The laboratory chemical analysis certificates are contained in Appendix 6. The results of the analysis are summarised in Table 8.
- 7.1.2 An initial screening exercise has been undertaken whereby contaminant concentrations recorded in soils have been assessed against *Suitable for Use Levels* (S4ULs) published in 2015 by LQM/CIEH<sup>2</sup>. These precautionary screening levels are designed to be representative of minimal risk to human health in a number of land use scenarios. In this report S4ULs have been selected for a residential land use where the possibility of consumption of homegrown produce exists and assuming a soil organic matter of 2.5 % (as soil SOM data ranged from 0.8 to 4.7%). For lead the DEFRA Category 4 Screening Level<sup>3</sup> has been used as this is based on updated toxicological data and a low risk to human health.
- 7.1.3 An additional set of phytotoxin screening levels have been adopted from 'The Code of Agricultural Practice for the Protection of Soil' Ministry of Agriculture, Fisheries and Food (MAFF), 1993, which are protective of healthy plant growth.

Table 8: Summary of soils chemical analysis results

CONTAMINANT	No of Tests	MAX (mg.kg <sup>-1</sup> )	MEAN (mg.kg <sup>-1</sup> )	SCREENING LEVEL (SL) (mg.kg <sup>-1</sup> )	No > SL*
<b>HUMAN HEALTH RISK ASSESSMENT</b>					
Asbestos in soil	6	nd	nd	Detected	0
pH	7	9.0	6.5	5 – 9	0
Arsenic	7	9.3	8.0	37	0
Barium	7	55.0	40.6	1300	0
Cadmium	7	0.2	0.2	11	0
Chromium (III)	7	25.0	20.3	910	0

<sup>2</sup> Nathanail, C. P., McCaffrey, C., Gillett, A. G., Ogden, R. C. and Nathanail, J. F. 2015. *The LQM/CIEH S4ULs for Human Health Risk Assessment*. Land Quality Press, Nottingham. Copyright Land Quality Management Limited reproduced with permission; Publication Number S4UL3100. All rights reserved. Including August 2015 nickel update.

<sup>3</sup> SP1010 *Development of Category 4 Screening Levels Main Report* (Dec 2013) and SP1010 *Policy Companion Document* (Mar 2014).

CONTAMINANT	No of Tests	MAX (mg.kg <sup>-1</sup> )	MEAN (mg.kg <sup>-1</sup> )	SCREENING LEVEL (SL) (mg.kg <sup>-1</sup> )	No > SL*
Hexavalent Chromium	7	1.8	1.8	6	0
Lead	7	50.0	27.5	200	0
Mercury	7	0.3	0.3	40	0
Nickel	7	13.0	9.2	130	0
Selenium	7	1.0	1.0	250	0
Vanadium	7	32.0	28.1	410	0
TPH Aliphatic >EC <sub>5</sub> - EC <sub>6</sub>	7	0.010	0.010	78	0
TPH Aliphatic >EC <sub>6</sub> - EC <sub>8</sub>	7	0.010	0.010	230	0
TPH Aliphatic >EC <sub>8</sub> - EC <sub>10</sub>	7	0.010	0.010	65	0
TPH Aliphatic >EC <sub>10</sub> - EC <sub>12</sub>	7	1.00	1.00	330	0
TPH Aliphatic >EC <sub>12</sub> - EC <sub>16</sub>	7	2.00	2.00	2400	0
TPH Aliphatic >EC <sub>16</sub> - EC <sub>21</sub>	7	8.00	8.00	92000	0
TPH Aliphatic >EC <sub>21</sub> - EC <sub>35</sub>	7	8.00	8.00	92000	0
TPH Aromatic >EC <sub>5</sub> - EC <sub>7</sub>	7	0.010	0.010	140	0
TPH Aromatic >EC <sub>7</sub> - EC <sub>8</sub>	7	0.010	0.010	290	0
TPH Aromatic >EC <sub>8</sub> - EC <sub>10</sub>	7	0.020	0.020	83	0
TPH Aromatic >EC <sub>10</sub> - EC <sub>12</sub>	7	1.00	1.00	180	0
TPH Aromatic >EC <sub>12</sub> - EC <sub>16</sub>	7	2.00	2.00	330	0
TPH Aromatic >EC <sub>16</sub> - EC <sub>21</sub>	7	10.00	10.00	540	0
TPH Aromatic >EC <sub>21</sub> - EC <sub>35</sub>	7	10.00	10.00	1500	0
Benzene	7	0.005	0.005	0.17	0
Toluene	7	0.005	0.005	290	0
Ethylbenzene	7	0.005	0.005	110	0
Xylene	7	0.013	0.013	130	0
Naphthalene	7	0.05	0.05	5.6	0
Acenaphthylene	7	0.05	0.05	420	0
Acenaphthene	7	0.05	0.05	510	0
Fluorene	7	0.05	0.05	400	0
Phenanthrene	7	0.17	0.09	220	0
Anthracene	7	0.05	0.05	5400	0
Fluoranthene	7	0.50	0.21	560	0
Pyrene	7	0.45	0.18	1200	0
Benzo(a)anthracene	7	0.24	0.11	11	0
Chrysene	7	0.40	0.15	22	0
Benzo(b)fluoranthene	7	0.45	0.17	3.3	0
Benzo(k)fluoranthene	7	0.24	0.10	93	0
Benzo(a)pyrene	7	0.34	0.13	2.7	0
Indeno(1,2,3-c,d)pyrene	7	0.22	0.10	36	0

CONTAMINANT	No of Tests	MAX (mg.kg <sup>-1</sup> )	MEAN (mg.kg <sup>-1</sup> )	SCREENING LEVEL (SL) (mg.kg <sup>-1</sup> )	No > SL*
Dibenzo(a,h)anthracene	7	0.05	0.05	0.28	0
Benzo(g,h,i)perylene	7	0.26	0.11	340	0
Phenol	7	1.0	1.0	200	0
Herbicides	2	nd	nd	-	0
Pesticides	2	nd	nd	-	0
<b>PHYTOTOXICITY RISK ASSESSMENT</b>					
Copper	7	13.0	9.3	200	0
Nickel	7	13.0	9.2	110	0
Zinc	7	55.0	41.3	300	0

Notes: \* Number of samples exceeding screening level

nd = not detected

## 7.2 SUMMARY

7.2.1.1 There was no contamination encountered above residential screening levels for any of the tested contaminants.

## SECTION 8 ENVIRONMENTAL ASSESSMENT – GROUNDWATER QUALITY

### 8.1 RESULTS

8.1.1 Groundwater level monitoring and sampling was undertaken on one occasion. Resting waters levels were recorded at 0.84 – 2.17m bgl.

8.1.2 Groundwater flow is likely to follow the site topography to the north.

8.1.3 Samples were submitted to the laboratory for analysis of a typical contamination suite. Screening levels for groundwater have been derived from the maximum concentrations set out in the Water Supply (Water Quality) Regulations 2018 (England) where prescribed, or for those determinands not included, the 1989 regulations. The laboratory chemical analysis certificate is contained in Appendix 8 and groundwater level data is contained in Appendix 9. A summary of groundwater contaminant concentrations is contained in Table 9.

8.1.4 Table 9: Summary of groundwater chemical analysis results

Contaminant	Units	Max	Mean	No. Tests	Screen Level (SL)	No. > SL
pH	-	7.1	7.1	3	6.5**	0
Arsenic	µg.l <sup>-1</sup>	0.48	0.4	3	10	0
Cadmium	µg.l <sup>-1</sup>	0.02	0.02	3	5	0
Chromium (total)	µg.l <sup>-1</sup>	1.6	0.8	3	50	0

Contaminant	Units	Max	Mean	No. Tests	Screen Level (SL)	No. > SL
Copper	µg.l <sup>-1</sup>	2.6	2.0	3	2000	0
Lead	µg.l <sup>-1</sup>	0.7	0.4	3	10	0
Mercury	µg.l <sup>-1</sup>	0.05	0.05	3	1	0
Nickel	µg.l <sup>-1</sup>	2.6	4.4	3	20	0
Selenium	µg.l <sup>-1</sup>	2.3	1.4	3	10	0
Zinc	µg.l <sup>-1</sup>	14	6.7	3	5000	0
Cyanide	µg.l <sup>-1</sup>	10	10	3	50	0
Sulphate	mg.l <sup>-1</sup>	47.5	19.8	3	250	0
TPH	µg.l <sup>-1</sup>	<10	<10	3	10	0
BTEX	µg.l <sup>-1</sup>	<3.0	<3.0	3	-	0
PAH (total)	µg.l <sup>-1</sup>	0.16	0.16	3	-	0
PAH****	µg.l <sup>-1</sup>	<0.01	<0.01	3	0.1	0
Benzo(a)pyrene	µg.l <sup>-1</sup>	<0.01	<0.01	3	0.01	0
Naphthalene	µg.l <sup>-1</sup>	<0.01	<0.01	3	-	0
Phenols	µg.l <sup>-1</sup>	<10	<10	3	0.5	0

Notes: \* Samples exceeding screen level

\*\* Minimum value applies (i.e. most acid)

\*\*\* Not detected above screening level

\*\*\*\* sum of benzo(b)fluoranthene, benzo(k)fluoranthene, benzo(ghi)perylene & indeno(1,2,3-cd)pyrene

## 8.2 DISCUSSION

- 8.2.1 No contaminants tested within waters were above the relevant screening levels. For phenols the laboratory limit of detection was above the screening level, however with no sources identified for these contaminants they are unlikely to be present at concentrations above screening levels.

## SECTION 9 ENVIRONMENTAL ASSESSMENT - HAZARDOUS GAS

### 9.1 RESULTS

- 9.1.1 Gas monitoring has been undertaken on three occasions (with three rounds remaining) – 3<sup>rd</sup> February to 25<sup>th</sup> February 2025. The maximum and steady state levels of methane, carbon dioxide, oxygen, carbon monoxide and hydrogen sulphide were recorded in each standpipe, together with associated parameters including borehole flow and ambient air pressure. The time taken to reach steady state was also recorded. Data has been excluded from the assessment where the resting water level was above the top of the slotted pipe response zone in the well.
- 9.1.2 The full results are presented in Appendix 9 and a summary of key readings for each strata monitored are presented in **Error! Reference source not found.** Table 10**Error! Reference source not found.**



Table 10: Summary of hazardous Gas Monitoring data with response zone within natural stratum

Monitoring Well Reference				MWS101		
Top of Response Zone (m bgl)				1.00		
Bottom of Response Zone (m bgl)				3.00		
Response Zone Stratum				-		
Round	AP (mb)	Flow Max (l.hr <sup>-1</sup> )	Flow Steady (l.hr <sup>-1</sup> )	Methane Max (% v/v)	Carbon Dioxide Max (% v/v)	Dip to water (m bgl)
1	-	-	-	-	-	0.84
2	-	-	-	-	-	0.85
3	1006	0.0	0.0	0.0	1.3	1.68
4	-	-	-	-	-	-
5	-	-	-	-	-	-
6	-	-	-	-	-	-

Monitoring Well Reference				MWS104		
Top of Response Zone (m bgl)				1.00		
Bottom of Response Zone (m bgl)				3.00		
Response Zone Stratum				-		
Round	AP (mb)	Flow Max (l.hr <sup>-1</sup> )	Flow Steady (l.hr <sup>-1</sup> )	Methane Max (% v/v)	Carbon Dioxide Max (% v/v)	Dip to water (m bgl)
1	1018	0.0	0.0	0.0	0.5	1.42
2	-	-	-	-	-	0.92
3	1005	0.0	0.0	0.0	0.7	1.77
4	-	-	-	-	-	-
5	-	-	-	-	-	-
6	-	-	-	-	-	-

Monitoring Well Reference				MWS106		
Top of Response Zone (m bgl)				1.00		
Bottom of Response Zone (m bgl)				3.00		
Response Zone Stratum				-		
Round	AP (mb)	Flow Max (l.hr <sup>-1</sup> )	Flow Steady (l.hr <sup>-1</sup> )	Methane Max (% v/v)	Carbon Dioxide Max (% v/v)	Dip to water (m bgl)
1	1017	0.0	0.0	0.0	0.8	1.30
2	1014	0.0	0.0	0.0	1.6	1.20
3	1004	0.0	0.0	0.0	1.1	2.17
4	-	-	-	-	-	-
5	-	-	-	-	-	-
6	-	-	-	-	-	-

9.1.3 The response zone was flooded in MWS101 for Round 1 and 2 and MWS104 for round 2 so these have been discounted from the risk assessment.

9.1.4 The monitoring rounds were undertaken at barometric pressures ranging from 1004 to 1018 mb. No positive flow was recorded. Over the three monitoring rounds methane (CH<sub>4</sub>) was not detected, carbon dioxide (CO<sub>2</sub>) was detected to a maximum of 1.6 % v/v with a corresponding depleted oxygen concentration of 17.5 % v/v.

## SECTION 10 ENVIRONMENTAL ASSESSMENT - VAPOUR

### 10.1 RESULTS

10.1.1 Vapour monitoring has been undertaken on three occasions (3 rounds remaining) – 3rd February to 25th February 2025. The maximum and steady state levels of VOCs were recorded using a PID (photo-ionization device) in each standpipe. The time taken to reach steady state was also recorded. A maximum concentration of 0.0ppm was recorded within boreholes which were not discounted due to response zone flooding.

## SECTION 11 WASTE CLASSIFICATION, OFF-SITE DISPOSAL OR RE-USE

### 11.1 WASTE CLASSIFICATION

11.1.1 Waste soils are classified into two main categories: Hazardous and Non-hazardous, based on Technical Guidance WM3: *Guidance on the classification and assessment of waste* (1st Edition v1.2.GB) published by Natural Resources Wales, Scottish Environment Protection Agency and the Environment Agency.

11.1.2 The soil chemical analysis results show that the soils are likely to be non-hazardous.

11.1.3 Whilst no asbestos has been identified by the investigations to date, it is the case that any soil that contains identifiable pieces of asbestos containing material (i.e. any

particle of a size that can be identified as potentially being asbestos by a competent person if examined by the naked eye), then the soil is regarded as hazardous waste. Soil with an asbestos content in excess of 0.1% by weight is classified as hazardous waste.

- 11.1.4 WAC tests are a supplementary set of tests that determine the acceptability of waste soils into the determined category of landfill based on the waste classification. For non-hazardous waste, WAC testing can determine whether soils could be accepted at inert landfill. For hazardous waste, WAC testing provides information whether soils can be disposed of a hazardous landfill or as Stable Non-reactive hazardous waste (SNRHW). Where hazardous soils fail these criteria, pre-treatment may be necessary.
- 11.1.5 Preliminary Waste Acceptance Criteria (WAC) testing suggests soils are suitable for disposal in an inert landfill. The results of the WAC testing are presented in Appendix 6.
- 11.1.6 Natural as-dug arisings (excluding topsoil) could be classed as inert waste without the requirement for WAC testing.
- 11.1.7 Materials, including waste soils which are not to be retained on site, should be removed and disposed of in accordance with all relevant statutes.
- 11.1.8 It is a requirement that waste sent to landfill should have been subject to measures to reduce the amount of waste, reduce harmful or hazardous properties and facilitate recycling. These requirements may be satisfied by measures such as segregation and screening of wastes to recover suitable fill and material for crushing, segregation of inert materials and putrescible wastes.
- 11.2 **RE-USE CONSIDERATIONS**
  - 11.2.1 As a sustainable alternative to off-site disposal, it may be possible to re-use site-won soils provided the following criteria are met:
    - i. Use of the material will not create an unacceptable risk of pollution to the environment or harm to human health;
    - ii. The material must be chemically and geotechnically suitable without further treatment;
    - iii. There must be certainty of use within the scheme;
    - iv. Material should only be used in the quantity necessary for that use.
  - 11.2.2 Provided these criteria are met, the re-use of site-won materials is unlikely to be deemed a waste activity. Production of a *Materials Management Plan* under the industry *CL:AIRE Code of Practice on the Definition of Waste* represents a robust method of demonstrating that the proposed re-use of material meets the criteria and is not liable for landfill tax.

- 11.2.3 During excavation and re-use of “*uncontaminated soil and other naturally occurring material*”, an exclusion to waste legislation can apply under the Waste Framework Directive. To qualify for the exclusion, soils must be:

- i.* Uncontaminated;
- ii.* Excavated during the construction activities; and
- iii.* Certain to be used in its natural state for construction purposes on the same site.

- 11.2.4 Under this exclusion, the definition of uncontaminated soil and other naturally occurring material is as follows:

*virgin soil or soil that is equivalent to virgin soil. Other naturally occurring material means soil, stones, gravel, rock, etc.*

## SECTION 12 GENERIC QUANTITATIVE RISK ASSESSMENT (TIER 2)

### 12.1 INTRODUCTION

- 12.1.1 The site investigation has not identified any significant sources of contamination and ground gas concentrations are low.

- 12.1.2 The site investigation has shown the following contaminant sources identified in the Tier 1 Assessment are either not present or unlikely to be significant:

- i.* Made ground
- ii.* Herbicides and pesticides from agricultural land uses.

- 12.1.3 The potential impacts of contamination sources have been considered with respect to the following receptors:

- i.* Present site users;
- ii.* Future residents;
- iii.* Construction workers;
- iv.* Plants used in landscaping;
- v.* Potable water supply pipework;
- vi.* The general public and adjacent site users;
- vii.* Controlled waters;

- 12.1.4 The potential sources of contamination at the site and the implications with respect to development have been interpreted in accordance with the current government guidance on source-pathway-receptor risk assessment.

- 12.1.5 In each case the existence of a pollutant linkage requires a pathway by which the receptor could be exposed to the source. A qualitative assessment of risk is thus considered in the first instance with respect to the site in its current condition and is summarised in the sections below.
- 12.1.6 The level of risk considers the likelihood of the risk occurring and the severity of the potential consequence of that risk using the approach outlined in Appendix 5. As illustrated in Table 11, this Tier 2 risk assessment combines the likelihood and severity of the risk using a Risk Assessment Matrix approach as recommended by CIRIA C552, 2001 and updated in *Guidance for the Safe Development of Housing on Land Affected by Contamination R&D66* published by NHBC, EA and CIEH (2008).

Table 11: Risk assessment matrix (after CIRIA C552 and R&D66)

		MAGNITUDE OF POTENTIAL CONSEQUENCE (SEVERITY) OF RISK			
		SEVERE	MEDIUM	MILD	MINOR
LIKELIHOOD OF RISK	HIGH LIKELIHOOD	Very High Risk	High Risk	Moderate Risk	Low Risk
	LIKELY	High Risk	Moderate Risk	Moderate / Low Risk	Low Risk
	LOW LIKELIHOOD	Moderate Risk	Moderate / Low Risk	Low Risk	Very Low Risk
	UNLIKELY	Moderate / Low Risk	Low Risk	Very Low Risk	Very Low Risk

- 12.2 **SOIL CONTAMINATION (HEAVY METALS, HYDROCARBONS, PESTICIDES AND HERBICIDES)**
- 12.2.1 No soil contamination above residential screening levels was encountered and therefore the risk to receptors is considered to be very low to low.
- 12.2.2

- 12.2.3 Table 12 below summarises the level of risk assigned to each receptor from soil contamination:

Table 12: Risks from soil contamination (heavy metals, hydrocarbons pesticides and herbicides)

Receptor		Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
The general public and present site users		dust inhalation	unlikely	minor	VERY LOW
		direct ingestion	unlikely	minor	VERY LOW
		dermal exposure	unlikely	minor	VERY LOW
		ingestion of fruit / vegetables	unlikely	minor	VERY LOW
Residents of future development		dust inhalation	unlikely	mild	VERY LOW
		direct ingestion	unlikely	mild	VERY LOW
		dermal exposure	unlikely	mild	VERY LOW
		ingestion of fruit / vegetables	unlikely	mild	VERY LOW
Construction workers		dust inhalation	unlikely	minor	VERY LOW
		direct ingestion	unlikely	minor	VERY LOW
		dermal exposure	unlikely	minor	VERY LOW
Future planting		direct uptake of phytotoxic metals	unlikely	minor	VERY LOW
Water supply pipes		direct contact leading to corrosion / permeation	unlikely	minor	VERY LOW
Adjacent site users		fugitive dust inhalation	unlikely	minor	VERY LOW
Controlled waters	Aquifer	infiltration / leaching	unlikely	minor	VERY LOW
	Surface water	run-off from site	unlikely	minor	VERY LOW
Protected habitat		dust deposition (demolition / construction phase)	unlikely	minor	VERY LOW
		direct ingestion (fauna feeding / drinking)	unlikely	minor	VERY LOW
		dermal exposure (fauna)	unlikely	minor	VERY LOW

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
	direct contact (flora)	unlikely	minor	VERY LOW
	groundwater flow to hydrologically connected habitat	unlikely	minor	VERY LOW
	surface water / sediment run-off	unlikely	minor	VERY LOW

### 12.3 SOIL CONTAMINATION (ASBESTOS)

12.3.1 No asbestos was encountered.

12.3.2 Table 13 below summarises the level of risk assigned to each receptor from asbestos contamination:

Table 13: Risks from soil contamination (asbestos)

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
The general public and present site users	inhalation of airborne fibres generated from dry soils	unlikely	minor	VERY LOW
Residents of future development		unlikely	mild	VERY LOW
Construction workers		unlikely	minor	VERY LOW
Adjacent site users		unlikely	minor	VERY LOW

### 12.4 CONTROLLED WATERS (GROUNDWATER)

12.4.1 No contamination was encountered within groundwater therefore the risk to end users is considered very low.

12.4.2 Table 14 below summarises the level of risk to surface water receptors:

Table 14: Risks from groundwater contamination

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
Surface water	Aquifer forms basal flow of surface water	unlikely	minor	VERY LOW

## 12.5 HAZARDOUS GAS

- 12.5.1 The presence of potentially significant concentrations of carbon dioxide and methane have not been identified at the site.
- 12.5.2 It is proposed to develop the site for residential use. The primary cause of soil gas entering a building is the pressure difference that exists between inside and outside the building: this tends to draw soil gas into the building from the ground below. Typically, soil gases can enter buildings through:
- i.* gaps around service pipes;
  - ii.* cracks in walls below ground and floor slabs;
  - iii.* construction joints; and
  - iv.* wall cavities.
- 12.5.3 The only potential source of ground gas identified by desk study was made ground which may contain putrescible materials. No significant made ground was encountered and as such, there is not considered to be a credible source of ground gas at the site. Nevertheless, confirmatory ground gas monitoring has been carried out with the results assessed in accordance with BS 8485:2015+A1:2019.
- 12.5.4 Borehole hazardous gas flow rates ( $Q_{hg}$ ) for carbon dioxide and methane were calculated using the maximum concentration recorded during each monitoring event together with steady state values of gas flow.
- 12.5.5 Where no gas borehole flow was detected, the detection limit of the instrumentation was used for the purposes of calculating the  $Q_{hg}$ .
- 12.5.6 Gas Screening Values (GSV) for methane and carbon dioxide have been derived from:
- i.* The maximum  $Q_{hg}$  calculated for methane and carbon dioxide for all monitoring events.
- 12.5.7 The  $Q_{hg}$  values for methane and carbon dioxide across all monitoring events are presented in Table 15 and the implied Characteristic Situation for the maximum  $Q_{hg}$  values are presented in Table 16.
- 12.5.8 A worst-case check has been carried out using the maximum peak gas flow and maximum peak gas concentrations for carbon dioxide and methane. The data is presented in Table 17.
- 12.5.9 Given the current limited dataset, on the basis of the presented measurements, the site GSV is taken to be  $0.0019 \text{ L.h}^{-1}$ , which is the worst case for methane and carbon dioxide. As presented in Appendix 14, a GSV of  $0.0019 \text{ L.h}^{-1}$  lies within the range of GSV values for CS1. Therefore, CS1 is taken as the design gas regime for the site.

12.5.10 The following information is presented in Appendix 14:

- i.* Wilson and Card Classifications;
- ii.* gas protection scores required for each Building Types and Characteristic Situation to achieve the appropriate level of protection; and
- iii.* gas protection elements that can be incorporated into building design with their associated assigned score.

12.5.11 No gas protection measures are considered necessary for the site in respect to carbon dioxide and methane.

Table 15: Borehole hazardous gas flow rates for all monitoring events

Monitoring Standpipe Reference	Gas	Borehole Hazardous Gas Flow Rate Calculated Using Peak Concentration and Steady State Flow					
		Round 1 $Q_{hg}$	Round 2 $Q_{hg}$	Round 3 $Q_{hg}$	Round 4 $Q_{hg}$	Round 5 $Q_{hg}$	Round 6 $Q_{hg}$
MWS101	methane	-	-	0.0001	-	-	-
	carbon dioxide	-	-	0.0013	-	-	-
MWS104	methane	0.0001	-	0.0001	-	-	-
	carbon dioxide	0.0005	-	0.0007	-	-	-
MWS106	methane	0.0001	0.0001	0.0001	-	-	-
	carbon dioxide	0.0008	0.0016	0.0011	-	-	-

Table 16: Maximum  $Q_{hg}$  for all individual events

Gas	Max $Q_{hg}$ across individual events	Implied CS
methane	0.0001	1
carbon dioxide	0.0019	1

Table 17: Worst case check maximum  $Q_{hg}$  using maximum flow and maximum peak gas concentration

Gas	Max $Q_{hg}$ events combined	Implied CS
methane	0.0001	1
carbon dioxide	0.0019	1

- 12.5.12 Table 18 below presents the Modified Wilson and Card Classifications and their corresponding hazard potentials as defined in BS 8485. The Modified Wilson and Card classification as presented in CIRIA C665 *Assessing risks posed by hazardous ground gases to buildings* instead defines this as the risk classification. The higher the classification the greater the risk posed by the presence of gas.

Table 18: Characteristic Situation and Risk

Characteristic Situation	Modified Wilson and Card Risk Classification
CS1	Very Low
CS2	Low
CS3	Moderate
CS4	Moderate to High
CS5	High
CS6	Very High

- 12.5.13 The risk classification for the site has been used to develop overall risk ratings for each identified receptor.

- 12.5.14 Table 19 below summarises the level of risk to each receptor from hazardous gas generation:

Table 19: Risks from hazardous gas

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
The general public and present site users	decomposition of putrescible made ground generating hazardous gas that can migrate by diffusion or advection via cracks in foundations / utility trenches / service penetrations. Outdoor inhalation in confined excavations.	unlikely	minor	VERY LOW
Residents of future development		unlikely	mild	VERY LOW
Construction workers		unlikely	minor	VERY LOW
Adjacent site users		unlikely	minor	VERY LOW

## 12.6 VAPOUR

- 12.6.1 The presence of potentially significant concentrations of Volatile Organic Compounds (VOCs) have not been identified at the site.

12.6.2 Table 20 and Table 21 below summarises the level of risk to each receptor from vapour generation:

Table 20: Risks from soil vapour

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
The general public and present site users	Volatilisation of VOCs from contaminated soil generating vapours that can migrate by diffusion or advection via cracks in foundations / utility trenches / service penetrations. Outdoor inhalation in confined excavations / localised spills.	unlikely	minor	VERY LOW
Residents of future development		unlikely	minor	VERY LOW
Construction workers		unlikely	minor	VERY LOW
Adjacent site users / general public		unlikely	minor	VERY LOW

Table 21: Risks from groundwater vapour

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
The general public and present site users	Volatilisation of VOCs from contaminated groundwater generating vapours that can migrate by diffusion or advection via cracks in foundations / utility trenches / service penetrations. Outdoor inhalation in confined excavations / localised spills.	unlikely	minor	VERY LOW
Residents of future development		unlikely	minor	VERY LOW
Construction workers		unlikely	minor	VERY LOW
Adjacent site users / general public		unlikely	minor	VERY LOW

## 12.7 RADON

12.7.1 Radon maps indicate a medium risk to receptors from radon gas.

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
The general public and present site users	Radon gas generated by decaying uranium	unlikely	minor	VERY LOW

Receptor	Pathway / Exposure	Likelihood of Risk	Severity of Risk	Overall Risk Rating
Residents of future development	within the underlying geology that can migrate by diffusion or advection via cracks in foundations / utility trenches / service penetrations into structures.	low likelihood	medium	MODERATE / LOW
Construction workers		unlikely	minor	VERY LOW

## SECTION 13 UPDATED COMBINED CONCEPTUAL SITE MODEL AND RISK ASSESSMENT

- 13.1 Following completion of the Tier 2 generic quantitative risk assessment, the preliminary combined conceptual site model and risk assessment has been updated and is presented in Table 22.

Table 22: Combined Conceptual Site Model and Tier 2 Risk Assessment

POTENTIAL CONTAMINANT SOURCE	RELEASE MECHANISM	PATHWAY	EXPOSURE ROUTE	RECEPTOR								
				Present Site Users / General Public	Future Residents / Site Users	Construction Workers	On-Site Planting	Water Supply Pipes	Adjacent Site Users / General Public	Controlled Waters		Protected Habitat
										Surface Water	Aquifer	
SOIL (HEAVY METALS, HYDROCARBONS PESTICIDES, HERBICIDES)	DUST	AIR	INHALATION	VERY LOW	VERY LOW	VERY LOW			VERY LOW			
	DIRECT	DIRECT	INGESTION	VERY LOW	VERY LOW	VERY LOW						
	DIRECT	DIRECT	DERMAL EXPOSURE	VERY LOW	VERY LOW	VERY LOW						
	DIRECT	DIRECT	DIRECT CONTACT / UPTAKE				VERY LOW	VERY LOW				
	PLANT UPTAKE	GARDEN FRUIT AND VEGETABLES	INGESTION	VERY LOW	VERY LOW							
	INFILTRATION / LEACHING	GROUNDWATER FLOW	DIRECT								VERY LOW	
		▲▼										
	RUNOFF	SURFACE WATER FLOW	DIRECT							VERY LOW		
MADE GROUND (ASBESTOS)	FIBRE RELEASE	AIR	INHALATION	VERY LOW	VERY LOW	VERY LOW			VERY LOW			
SOIL	GAS FROM DECOMPOSITION	AIR	INHALATION	VERY LOW	VERY LOW	VERY LOW			VERY LOW			
SOIL	VAPOUR FROM VOLATILISATION /	AIR	INHALATION	VERY LOW	VERY LOW	VERY LOW			VERY LOW			
GROUNDWATER (VOC)	VAPOUR FROM VOLATILISATION	AIR	INHALATION	VERY LOW	VERY LOW	VERY LOW			VERY LOW			
GROUNDWATER (DISSOLVED CONTAMINANTS)	DIRECT	BASEFLOW TO SURFACE WATER	DIRECT							VERY LOW		
URANIUM IN UNDERLYING STRATA	RADON FROM RADIOACTIVE DECAY	AIR	INHALATION	VERY LOW	MODERATE / LOW	VERY LOW						

X SOURCE►PATHWAY►RECEPTOR NOT COMPLETE AND NO FURTHER ACTION REQUIRED

## **SECTION 14 DETAILED QUANTITATIVE RISK ASSESSMENT (TIER 3)**

- 14.1 No contaminant linkages requiring further supplementary site investigation and detailed quantitative risk assessment have been identified and no preliminary remediation strategy is required.

## **SECTION 15 PRELIMINARY REMEDIATION STRATEGY AND RECOMMENDATIONS**

### **15.1 INTRODUCTION**

- 15.1.1 The site is in an area where basic radon protection is required.
- 15.1.2 No other unacceptable risks have been identified and (other than radon protection) remedial action is unlikely to be required. However, the ground gas monitoring programme is in progress and risks from bulk ground gases will be subject to updated assessment upon completion of the monitoring programme.
- 15.1.3 Following guidance given on Land Contamination Risk Management (LCRM) available on [www.gov.uk](http://www.gov.uk) and last updated in July 2023 the following three procedures should be followed:
- i.* Identify feasible remediation options;
  - ii.* Undertake a detailed evaluation of the options; and
  - iii.* Select the final remediation option.
- 15.1.4 This report provides an initial high-level overview and recommends a remedial option considered to be appropriate for each relevant contamination linkage. A detailed remediation method statement, compliant with LCRM guidance will be required.

### **15.2 GAS / VAPOUR PROTECTION**

- 15.2.1 Basic radon protection is required for the development. This consists of a well-installed damp-proof membrane, modified and extended to form a gas-tight radon-proof barrier between the ground and the building. Subject to agreement with the Council and NHBC, there is a possibility the proposed development could be zoned with basic radon protection measures in structures within RnC4 only.
- 15.2.2 On the basis of the initial rounds of monitoring, further gas and vapour protection measures are not considered necessary. This potentially could change on completion of the monitoring programme and updated risk assessment, however, the requirement for gas protection is considered unlikely given the lack of evidence for a source of ground gas. A revision to the report will be issued on completion of the monitoring.

### **15.3 PROTECTION OF CONSTRUCTION WORKERS**

- 15.3.1 No potential risks to construction workers have been identified however the adoption of appropriate Health and Safety procedures will ensure that risks to operatives from

unidentified hazardous materials at the site are minimised. Operatives should not be allowed to eat, drink or smoke on site except in designated areas and should be required to wash all exposed skin at the end of each shift. Operatives should be informed of the potential hazards at the site and should be required to report any observations of suspect material.

**15.4 WATER SUPPLY PIPES**

- 15.4.1 No contamination with the potential to permeate polymeric services has been identified by this investigation, however it is recommended that the utility provider is consulted with respect to their requirements for water supply pipes. Utility companies apply strict guideline levels on use of polymeric pipes.

**15.5 WASTE**

- 15.5.1 Materials, including waste soils which are not to be retained on site, should be removed and disposed of in accordance with all relevant statutes.

**15.6 OTHER RECOMMENDATIONS**


- 15.6.1 It is recommended that this report is submitted to the regulators (Local Authority EHO and Planners, Environment Agency Planning Liaison and NHBC) for approval prior to commencement of the works.
- 15.6.2 Any observations of ground conditions atypical of those already described should be reported to IDOM immediately so that an assessment of appropriate action can be made.



## **SECTION 16 CONCLUSIONS**

- 16.1 The ground conditions generally comprised superficial Head Deposits between 1.0 and 1.50 m bgl across the majority of the site. Underling the topsoil and superficial deposits are variable cohesive and granular deposits of the Sandgate Formation.
- 16.2 A foundation zone plan has been provided for the site. In summary the majority of the site will be suitable for traditional strip footings with an allowable bearing pressure of 100 kN/m<sup>2</sup> at depths ranging between 1.0 and 2.0 m bgl. Two zones are defined where an alternative solution such as ground improvement or piled foundations are recommended. Additional deepening is required due to the zone of influence from existing trees, where the anticipated depth exceeds 2.0 m then piled foundations are likely to be more cost-effective.
- 16.3 Basic radon protection measures are required for the development.
- 16.4 Soils are classed as non-hazardous and are likely to be suitable for an inert landfill.

**APPENDIX 1**

- Site Location Plan CSA-3256-114
- Topographic Survey 2019-070\_Topo\_01-04\_2d\_RevD
- Development Framework Plan CSA-5622-115





 Site Boundary: **2.95ha**

A	27.11.23	RC	Site boundary amended
Rev	Date	By	Description



Dixies Barns, High Street,  
Ashwell, Hertfordshire SG7 5NT

**t** 01462 743647  
**e** ashwell@csaenvironmental.co.uk  
**w** csaenvironmental.co.uk

Project

Land to the South of  
Ashford Road, Sellindge

Title

Site Location Plan

Client

Gladman Developments Ltd

Scale

1:1250 @ A3

Drawn

RC

Date

March 2020

Checked

RR

Drawing No.


CSA/3256/114

Rev

A







TREE SCHEDULE				TREE SCHEDULE			
No.	DMM	SPREAD Ø	HEIGHT	No.	DMM	SPREAD Ø	HEIGHT
TE1	2.50	18	8	TE101	0.70	18	18
TE2	1.10	18	19	TE102	0.80	18	18
TE3	0.70	18	25	TE103	0.70	18	18
TE4	0.80	24	20	TE104	0.55	18	18
TE5	0.40	8	10	TE105	0.55	18	18
TE6	0.80	15	15	TE106	0.70	12	14
TE7	0.70	4	7	TE107	0.70	6	10
TE8	0.50	14	14	TE108	0.70	6	10
TE9	0.50	14	14	TE109	0.70	6	10
TE10	0.50	14	14	TE110	1.30	18	20
TE11	0.50	14	14	TE111	1.30	18	20
TE12	0.50	14	14	TE112	1.10	18	18
TE13	0.50	14	14	TE113	1.10	18	18
TE14	0.50	14	14	TE114	0.50	10	10
TE15	0.50	14	14	TE115	0.50	10	18
TE16	0.50	14	12	TE116	0.70	10	18
TE17	0.50	14	14	TE117	0.50	10	18
TE18	0.50	6	4	TE118	1.30	20	24
TE19	0.50	6	4	TE119	0.80	18	34
TE20	0.50	4	4	TE120	0.80	22	24
TE21	0.50	4	4	TE121	0.50	10	12
TE22	0.50	4	4	TE122	0.80	22	18
TE23	0.50	4	4	TE123	0.50	10	12
TE24	0.50	4	4	TE124	0.50	10	12
TE25	0.50	18	18	TE125	0.80	22	18
TE26	0.50	18	18	TE126	0.80	22	18
TE27	1.10	12	16	TE127	1.30	20	11
TE28	0.40	10	6	TE128	1.30	20	11
TE29	0.50	8	8	TE129	0.80	12	10
TE30	0.50	8	8	TE130	0.80	12	10
TE31	0.50	8	8	TE131	0.75	18	16
TE32	0.50	8	8	TE132	0.50	20	14
TE33	1.00	16	14	TE133	0.50	20	14
TE34	0.50	8	8	TE134	0.30	10	10
TE35	0.50	8	8	TE135	0.30	10	10
TE36	0.50	8	8	TE136	0.30	10	10
TE37	0.50	8	8	TE137	2.00	20	18
TE38	0.50	12	12	TE138	1.30	18	12
TE39	0.50	12	12	TE139	1.30	18	12
TE40	0.50	12	12	TE140	0.30	12	5
TE41	1.80	18	18	TE141	1.00	14	7
TE42	1.30	20	18	TE142	0.80	18	14
TE43	0.50	8	8	TE143	0.30	12	12
TE44	0.50	8	8	TE144	0.40	14	12
TE45	0.50	8	8	TE145	0.40	14	12
TE46	0.50	10	10	TE146	0.40	8	8
TE47	0.70	14	10	TE147	0.30	10	10
TE48	0.50	12	12	TE148	0.40	18	18
TE49	0.50	12	12	TE149	0.40	18	18
TE50	0.40	10	12	TE150	0.40	18	18
TE51	0.40	10	12	TE151	0.80	18	18
TE52	0.40	10	12	TE152	0.80	18	18
TE53	0.40	10	12	TE153	0.20	6	6
TE54	0.40	10	12	TE154	0.20	6	6
TE55	0.40	10	12	TE155	0.20	6	6
TE56	0.40	10	12	TE156	0.20	6	6
TE57	0.40	10	12	TE157	0.20	6	6
TE58	0.40	10	12	TE158	0.20	6	6
TE59	0.40	10	12	TE159	0.20	6	6
TE60	0.40	10	12	TE160	0.20	6	6
TE61	0.40	10	12	TE161	0.40	12	18
TE62	0.40	10	12	TE162	0.40	12	18
TE63	0.40	10	12	TE163	0.40	12	18
TE64	0.40	10	12	TE164	0.40	12	18
TE65	0.40	10	12	TE165	0.40	12	18
TE66	0.40	10	12	TE166	0.40	12	18
TE67	1.20	18	18	TE167	0.40	8	8
TE68	0.40	10	12	TE168	0.40	8	8
TE69	0.40	10	12	TE169	0.40	8	8
TE70	0.40	10	12	TE170	0.15	6	6
TE71	0.40	10	12	TE171	0.30	18	18
TE72	1.00	10	22	TE172	0.55	20	18
TE73	0.80	24	22	TE173	0.40	8	8
TE74	0.40	10	12	TE174	0.80	18	18
TE75	0.80	10	18	TE175	0.80	18	18
TE76	0.80	10	18	TE176	0.80	18	18
TE77	0.80	10	18	TE177	0.40	18	18
TE78	0.70	14	18	TE178	0.20	8	18
TE79	0.70	14	18	TE179	0.20	8	18
TE80	0.40	10	10	TE180	0.30	12	18
TE81	0.40	10	10	TE181	0.30	12	18
TE82	1.80	24	18	TE182	0.30	12	18
TE83	0.50	12	18	TE183	0.30	12	18
TE84	0.50	12	18	TE184	0.20	12	18
TE85	0.50	18	16	TE185	0.40	14	18
TE86	0.10	8	8	TE186	0.50	16	18
TE87	0.40	18	18	TE187	0.50	16	18
TE88	0.40	18	18	TE188	0.50	16	18
TE89	0.40	18	18	TE189	0.75	18	18
TE90	0.70	18	18	TE190	0.45	18	18
TE91	0.40	10	10	TE191	0.30	18	18
TE92	1.20	10	10	TE192	0.20	6	6
TE93	1.20	20	20	TE193	0.30	6	6
TE94	0.80	20	20	TE194	0.20	6	6
TE95	0.80	20	20	TE195	0.20	6	6
TE96	0.80	18	18	TE196	0.20	6	6
TE97	0.70	18	18	TE197	0.20	6	6
TE98	0.70	18	18	TE198	0.20	6	6
TE99	0.50	18	18	TE199	0.20	6	6
TE00	0.50	18	18	TE200	0.20	6	6

TREE DIAMETER MEASURED APPROXIMATELY 1.5M ABOVE GROUND LEVEL. TREE  
SPREADS ARE SYMBOLIC ONLY AND ARE REPRESENTATIVE OF THE GENERALIZED  
CANOPY SIZE. THIS SOLE MAY NOT SIT CENTRALLY TO THE CANOPY. TREE HEIGHT  
ESTIMATED FROM GROUND LEVEL.



THIS SURVEY IS ORIENTATED TO ORDNANCE SURVEY GRID NORTH. THE SURVEY TO A PLANE GRID. HORIZONTAL MEASUREMENTS TAKEN FROM THIS SURVEY WILL BE GROUND DISTANCES.

ALL LEVELS RELATE TO ORDNANCE SURVEY DATUM GENERATED BY ACTIVE GP NETWORK.

NO ALLOWANCE HAS BEEN MADE FOR SUB SURFACE ACCESS TO MANHOLES OR CHAMBERS. ANY PIPE SIZES, DEPTHS OR BELOW GROUND DIMENSIONS ARE TAKEN FROM THE SURFACE AND THUS WILL ONLY BE APPROXIMATE. ANY FLOW TYPE (FOUL WATER, SURFACE WATER OR COMBINED) ARE ASSUMED AND THEREFORE REQUIRE VERIFICATION.

ROAD MARKINGS:

ROAD MARKINGS DISPLAYED ARE SYMBOLIC. LENGTH, SPACING AND THICKNESS ETC. ARE INDICATIVE ONLY.

### LEGEND

- |       |                                    |
|-------|------------------------------------|
| 30.25 | SPOT LEVEL                         |
|       | SURVEY STATION                     |
|       | SAPLING                            |
|       | BUSH/SHRUB                         |
|       | TREE (INDICATIVE ONLY)             |
|       | HEDGE/AREA OF UNDERGROWTH          |
|       | CONTOUR                            |
|       | GATE                               |
|       | OVERHEAD CABLE                     |
|       | FENCE                              |
|       | PHOTOGRAPH LOCATION AND NUMBER     |
|       | APPROXIMATE CULVERT/BRIDGE OPENING |

## ABBREVIATIONS

- [illegible]

## STATION CO-ORDINATES

STATION	EASTING	NORTHING	LEVEL	DESCRIPTION
STN2	006902.00	133309.51	66.88	Survey Nail
STN9	011064.05	133106.91	65.00	Survey Nail
STN10	011068.78	133119.48	67.03	Survey Nail
STN15	009651.87	133332.51	65.64	Survey Nail
STN51	011007.81	133270.07	66.92	Survey Nail
STN52	011013.82	133257.47	66.70	Survey Nail
STN53	011013.52	133253.17	65.67	Survey Nail
STN200	011013.85	133345.70	65.11	Survey Nail
STN101	011019.75	133350.50	63.62	Survey Nail
STN102	005792.52	133352.94	62.83	Survey Nail
STN300	006618.79	134112.96	64.48	Survey Nail
STN301	006625.44	134845.14	63.93	Survey Nail

## PLOT LOCATIONS



	*	*	*	
D	24.06.24	Pond and ditch measured.		J
C	24.05.23	Extend Ashford Rd to the west.		J
B	02.11.22	Moorstock Lane north to stream		J
A	16.06.21	Additional field surveyed.		J
Rev	Date	Revision notes		B

	Status
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	
59	
60	
61	
62	
63	
64	
65	
66	
67	
68	
69	
70	
71	
72	
73	
74	
75	
76	
77	
78	
79	
80	
81	
82	
83	
84	
85	
86	
87	
88	
89	
90	
91	
92	
93	
94	
95	
96	
97	
98	
99	
100	

## INFORMATION

Project

Ashford Road, Sellindge.

	<b>Title</b>

TOPOGRAPHICAL SURVEY  
AS OF 22.08.19  
SHEET 4 OF 4



Drawn By	Publish Date	Scale(s)	Sheet Size
JW/JH	03.09.19	1:500	A0
Project no.	Drawing no.	Revision	
2019-070	Topo_04_2D	D	



**LANDSCAPE FEATURES**  
Existing mature tree belts and hedgerows are to be retained and will inform the layout to ensure that the new homes sit within a strong landscape framework.

**PUBLIC RIGHTS OF WAY**  
Existing public footpath which crosses the Site will be retained along its current alignment.

**Water Recycling Centre**

**SUSTAINABLE DRAINAGE SYSTEMS (SuDS)**  
Proposed locations for drainage feature at the lower part of the Site to manage the flow of surface water during periods of heavy and persistent rainfall. The feature will form an integral part of the Site's green infrastructure framework and allow for habitat creation. In addition to the drainage features, 2 new wildlife ponds will be created, which will provide new habitats for wildlife and will form attractive new landscape and ecological features.

**INTEGRATION**  
Potential vehicular and pedestrian links are proposed to the other parts of Phase 2 (Policy CSD9) to ensure that Site A is brought forward in a holistic manner.

**MOBILITY HUB**  
A mobility hub, which will include bicycle and scooter parking facilities and electric car charging points, will be located close to the primary street and the central green.

**CHILDREN'S PLAY**  
Proposed children's play area located within area of open space central to the overall Phase 2 allocation.

Development under construction

  
0 20 40 60 80 100 metres

Site Boundary: 6.99ha

Proposed residential development: 3.47ha (Up to 105 dwellings @ 30.25 dph)

Proposed/potential vehicular access points

Proposed tree-lined primary street

Proposed mobility hub

Proposed secondary streets

Proposed private drives/lanes

Proposed shared/focal spaces

Proposed pedestrian links

Proposed recreational routes

Existing public rights of way

Potential vehicular links to other parts of Phase 2 allocation

Proposed public open space

Existing vegetation

Proposed tree, thicket and woodland planting

Proposed wildflower planting

Proposed location for children's play area

Proposed locations for seating areas

Water Recycling Centre: 0.09ha

Proposed location for drainage features (SuDS)

Proposed pump station

**CONTEXT**

Existing water features

Existing bus routes and bus stops

Listed Buildings

Policy CSD9 land outside the scope of the applicant's control

N	13.03.24	RC	DRAINAGE AMENDMENTS
M	08.11.23	RC	MINOR TEXT AMENDMENTS
Rev	Date	By	Description

  
Dixies Barns, High Street,  
Ashwell, Hertfordshire SG7 5NT  
t 01462 743647  
e ashwell@csaenvironmental.co.uk  
w csaenvironmental.co.uk

Project	Land at Potten Farm, Sellindge		
Title	Development Framework Plan		
Client	Gladman Developments Ltd		
Scale	1:2000 @ A2	Drawn	RC
Date	Nov 2022	Checked	RR
Drawing No.	CSA/5622/115	Rev	N



Legend

Minimum Foundation Depths due to Existing Tree Influence

Max ZOI	-----
1.0m	-----
1.5m	-----
2.0m	-----
2.5m	-----

Foundation Zones

100 kPa at 1.0 m bgl.	
100 kPa at 2.0 m bgl.	
Foundations >2.0 m bgl (pile).	

Notes  
Additional deepening will be required for new foundations within the zone of influence of existing trees.

Zone of Influence from trees based on the Arboricultural Impact Assessment Report (Ref: CSA/4509/14 dated June 2024. IDOM takes no responsibility for inaccuracies in this preliminary plan as a result of errors in third-party reports. Where tree heights are recorded to be 0 m, these have not been included as part of the tree influence assessment. Where the tree species is ambiguous i.e. "Chestnut-leaved oak" or "Zelkova" judgement has been made to base the tree species and water demand from the most likely worst-case species identified in Table 3 of NHBC Standards Chapter 4.2. Individual Trees and Tree Groups are based on the mature height or actual height of immature species in accordance with Table 3a of NHBC Standards Chapter 4.2; however, the mature tree height has been assumed for hedgerows because these the may have been cut.

Rev A: Tree influence and update to allowable bearing pressures	17/03/2025	-
First Issue	05/03/2025	-
Issue Details	Dwn	Chd

Client  
  
GLADMAN

Project  
  
Grove House

Dwg Title  
  
Preliminary Foundation Zone Plan

Drawing No.	22653h-311-001	Revision	A
Scale	1:1,000	Date	17/03/2025
Drawn	CMM	Checked	CMM



Cromford Mills, Mill Lane, Matlock, Derbyshire DE4 3RQ  
t: +44(0)1773 829 988 e: info.derbyshire@idom.com

**APPENDIX 2**    ▪    Radon Potential Dataset Mapping

Grove House, Ashford Road, Sellindge, Kent

## Professional opinion

## Site plan



© Crown copyright and database rights 2025. Ordnance Survey licence 100035207

## Search results

### In a radon affected area

The property is in a radon affected area. This could mean that inhabitants are at risk from the harmful effects of radon.

The percentage of homes estimated to be affected by radon in your local area is between 5% and 10%.

Please see [page 3](#) >

## Useful contacts

**UK Health Security Agency (UKHSA) / UKRadon**  
Radon Survey  
Chemical, Radiation and Environmental Hazards  
Chilton, Didcot  
Oxon  
OX11 0RQ  
<https://www.ukradon.org/> ↗

**UK Radon Association**  
<http://www.radonassociation.co.uk/> ↗

## Overview of findings and recommendations

### **Radon**


The property is in an area where elevated radon levels are expected to be found in 5-10% of properties.

#### Next steps for consideration:

- If the property was constructed after 2008 radon protection measures may have been installed during construction. We recommend checking with the Building Control department at the local authority to determine this;
- Enquire with the seller if they have completed a 3 month radon test and what the results were. If they have not had one completed, carry out a radon test at the property. The most accurate testing kits run for 3 months and can be obtained from UK Radon <https://www.ukradon.org/services/orderdomestic> ↗;
- Further information is available here <https://knowledge.groundsure.com/searches-radon> ↗.



## Radon



— Site Outline  
Search buffers in metres (m)

- Greater than 30%
- Between 10% and 30%
- Between 5% and 10%
- Between 3% and 5%
- Between 1% and 3%
- Less than 1%

The property is in a radon affected area, meaning there is an increased risk that properties will contain elevated levels of radon.

In order to determine if there is a problem at your property, a radon measurement in the building must be taken. Access to a testing service and further information on radon is available from UK Health Security Agency (UKHSA) or [www.ukradon.org](http://www.ukradon.org).

Radon is a colourless, odourless radioactive gas present in all areas of the United Kingdom, usually at levels that pose a negligible risk. However, the property is situated in an area where levels of radon can be much higher and pose a health risk. High levels of radon can cause lung cancer, particularly for smokers and ex-smokers. The higher the level and the longer the period of exposure, the greater the risk.

Please see [page 2](#) > for further advice.

This data is sourced from the British Geological Survey/UK Health Security Agency.



[Back to Summary](#)

Contact us with any questions at:  
[info@groundsure.com](mailto:info@groundsure.com)  
01273 257 755

Ref: HMD-155-6G9-7AT-4SB-6JH  
Your ref: 25-139-FO-22653h  
Grid ref: 609966 138211

## Methodologies and limitations

Groundsure's methodologies and limitations are available here: [knowledge.groundsure.com/methodologies-and-limitations](https://knowledge.groundsure.com/methodologies-and-limitations) ↗.

## Data providers

Groundsure works with respected data providers to bring you the most relevant and accurate information in your Radon Check report. To find out who they are and their areas of expertise see [www.groundsure.com/sources-reference](https://www.groundsure.com/sources-reference) ↗.

## Conveyancing Information Executive and our terms & conditions

### IMPORTANT CONSUMER PROTECTION INFORMATION

This search has been produced by Groundsure Ltd. Groundsure adheres to the Conveyancing Information Executive Standards.

In addition to The Property Ombudsman (TPO) redress scheme covering consumers, TPO will also provide redress to small businesses (including Charities and Trusts) and where the customer meets the following criteria:

- a small business (or group of companies) with an annual turnover of less than £3 million;
- a charity with an annual income of less than £3 million;
- a Trust with a net asset value of less than £3 million.

### Complaints Advice

If you have a query or complaint about your search, you should raise it directly with the search firm, and if appropriate ask for any complaint to be considered under their formal internal complaints procedure.

If you remain dissatisfied with the firm's final response, after your complaint has been formally considered, or if the firm has exceeded the response timescales, you may refer your complaint for consideration under The Property Ombudsman scheme (TPOs). The Ombudsman can award up to £5,000 to you if the Ombudsman finds that you have suffered actual financial loss and/or aggravation, distress or inconvenience as a result of your search provider failing to keep to the Standards.

Please note that all queries or complaints regarding your search should be directed to your search provider in the first instance, not to TPOs.

### COMPLAINTS PROCEDURE: If you want to make a complaint, we will:

- acknowledge it within 5 working days of receipt
- normally deal with it fully and provide a final response, in writing, within 20 working days of receipt
- liaise, at your request, with anyone acting formally on your behalf

Complaints should be sent to:

Operations Director, Groundsure Ltd, Nile House, Nile Street, Brighton, BN1 1HW. Tel: 01273 257 755. Email: [info@groundsure.com](mailto:info@groundsure.com)

↗ If you are not satisfied with our final response, or if we exceed the response timescales, you may refer the complaint to The Property Ombudsman scheme (TPOs): Tel: 01722 333306, E-mail: [admin@tpos.co.uk](mailto:admin@tpos.co.uk) ↗ We will co-operate fully with the Ombudsman during an investigation and comply with their final decision.

Groundsure's Terms and Conditions can be viewed here: [www.groundsure.com/terms-and-conditions-april-2023/](https://www.groundsure.com/terms-and-conditions-april-2023/) ↗

All of the advice and reports that Groundsure produces are covered by a comprehensive Remediation Contribution policy to ensure customers are protected, see [www.groundsure.com/remediation](https://www.groundsure.com/remediation) ↗ for full details.



**APPENDIX 3**    ▪    Risk Assessment Methodology

## RISK ASSESSMENT METHODOLOGY (FOLLOWING CIRIA C552, 2001)

The potential sources of contamination at the site and the implications with respect to development have been interpreted in accordance with the current government guidance on source-pathway-receptor risk assessment.

The existence of a pollutant linkage requires a pathway by which the receptor could be exposed to the source.

Where a complete pollutant linkage is deemed to be present, the level of *risk* is then determined taking into account the *likelihood* of significant impact and the *severity* of potential impact using the following classification tables which broadly follow the method set out in CIRIA C552.

Table A1: Classification of Severity (or Consequence)

CLASSIFICATION	DEFINITION
Severe	Short term (acute) risk to human health likely to result in “significant harm” as defined by the Environment Protection Act 1990, Part IIA. Short term risk of sensitive water resource. Catastrophic damage to buildings/property. A short term risk to a particular ecosystem or organism forming part of such ecosystem (note: the definitions of ecological systems within the Draft Circular on Contaminated Land, DETR, 2000).
Medium	Chronic damage to Human Health (“significant harm” as defined in DETR, 2000). Pollution of sensitive water resources, significant change in a particular ecosystem or organism forming part of such ecosystem.
Mild	Pollution of non sensitive water resources. Significant damage to crops, buildings, structures and services (“significant harm” as defined in the Draft Circular on Contaminated Land, DETR, 2000). Damage to sensitive buildings/structures/services or the environment.
Minor	Harm, although not necessarily significant harm, which may result in a financial loss or expenditure to resolve. Non permanent health effects to human health (easily prevented by means such as personal protective clothing, etc). Easily repairable effects of damage to buildings, structures and services.

Table A2: Classification of Likelihood (Probability)

CLASSIFICATION	DEFINITION
High Likelihood	There is a pollution linkage and an event that either appears very likely in the short term and almost inevitable over the long term or there is evidence at the receptor of harm or pollution.
Likely	There is a pollution linkage and all the elements are present and in the right place, which means that it is probable that an event will occur. Circumstances are such that an event is not inevitable, but possible in the short term and likely over the long term.
Low Likelihood	There is a pollution linkage and circumstances are possible under which an event could occur. However, it is by no means certain that even over a longer period such event would take place, and is less likely in the shorter term.
Unlikely	There is a pollution linkage but circumstances are such that it is improbable that an event would occur even in the very long term.

Table A3: Risk Estimation – Combination of Consequence and Probability(after CIRIA C552 and R&D66)

		MAGNITUDE OF POTENTIAL CONSEQUENCE (SEVERITY) OF RISK			
		SEVERE	MEDIUM	MILD	MINOR
LIKELIHOOD OF RISK	HIGH LIKELIHOOD	Very High Risk	High Risk	Moderate Risk	Low Risk
	LIKELY	High Risk	Moderate Risk	Moderate / Low Risk	Low Risk
	LOW LIKELIHOOD	Moderate Risk	Moderate / Low Risk	Low Risk	Very Low Risk
	UNLIKELY	Moderate / Low Risk	Low Risk	Very Low Risk	Very Low Risk





Table A4: Description of the Classified Risks and Likely Reaction Required

CLASSIFICATION	DEFINITION
Very High Risk	There is a high probability that severe harm could arise to a designated receptor from an identified hazard, OR, there is evidence that severe harm to a designated receptor is currently happening. This risk, if realised, is likely to result in a substantial liability. Urgent investigation (if not undertaken already) and remediation are likely to be required.
High Risk	Harm is likely to arise to a designated receptor from an identified hazard. Realisation of the risk is likely to present a substantial liability. Urgent investigation (if not undertaken already) is required and remedial works may be necessary in the short term and are likely over the long term.
Moderate Risk	It is possible that harm could arise to a designated receptor from an identified hazard. However, it is relatively unlikely that any such harm would be severe, or if any harm were to occur it is more likely that the harm would be relatively mild. Investigation (if not already undertaken) is normally required to clarify the risk and to determine the potential liability. Some remedial works may be required in the longer term.
Low Risk	It is possible that harm could arise to a designated receptor from an identified hazard but it is likely that this harm, if realised, would at worst normally be mild.
Very Low Risk	There is a low possibility that harm could arise to a receptor. In the event of such harm being realised, it is not likely to be severe.

**APPENDIX 4**    ▪    Site Investigation Location Plan



NOTES

-  MBHref Merebrook borehole with location reference
-  MTPref Merebrook trial pit with location reference
-  MWSref Merebrook window sample with location reference
-  CBRref Californian bearing ratio test with location reference

FIRST ISSUE	06/02/25	CW	AB	AB	-
DESCRIPTION	DATE	DWN	CHD	APP'D	REV

ISSUE PURPOSE	PRELIMINARY
---------------	-------------

CLIENT	GLADMAN
--------	---------

PROJECT	GROVE HOUSE
---------	-------------

DWG TITLE	EXPLORATORY HOLE LOCATION PLAN
-----------	--------------------------------








DWG NO.	22653h-303-001
---------	----------------



SCALE N.T.S	DATE FEBRUARY 2025	FRAME DIMS (mm) (A3) 420 x 297
DRAWN CW	CHECKED AB	APPROVED AB






















Registered Office: Cromford Mills, Mill Lane, Matlock, Derbyshire, DE4 3RQ  
Website: [www.merebrook.co.uk](http://www.merebrook.co.uk) t: +44(0)1773 829 988 e: [info.derbyshire@idom.com](mailto:info.derbyshire@idom.com)

**APPENDIX 5**    ▪    Exploratory Hole Logs







IDOM		Rotary Core Log																
Project Name: Grove House						Client: Gladman						Date: 24/01/2025 - 28/01/2025						
Location: Main Road, Sellindge, Kent						Contractor:						Co-ords: E610020.77 N138263.43						
Project No. : 22653H						Crew Name: Marshall Drilling						Drilling Equipment:						
Borehole Number MBH101			Hole Type CP+RC			Level			Logged By Ben Alexander			Scale 1:50			Page Number Sheet 1 of 2			
Well	Depth (m)	Type / Fl	Coring			Diameter Recovery (SPT)	Depth (m)	Level (m)	Legend	Stratum Description								
			TCR	SCR	RQD													
	0.50	D				(2)	0.20			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint. Soft brown mottled grey slightly sandy silty CLAY. Sand is fine [Sandgate Formation] Becomes grey mottled brown and orange brown from 0.4m.								1
	1.50	D	100	0	0													
	2.50	D	100	0	0	(36)	2.00			Greenish grey mottled orange brown clayey SAND with occasional sandy clay lenses. Sand is fine [Sandgate Formation]								2
			2.60															
	4.00	D	90	0	0	(50)	3.20			Stiff grey sandy CLAY [Sandgate Formation]								3
			4.90															
	5.00	D	73	0	0	(35)	4.90			Very dense, grey clayey fine SAND [Sandgate Formation]								4
			6.00	D	73			0										0
	8.00	D	47	0	0	(47)	8.00			Stiff grey silty slightly sandy CLAY with clayey and silty fine sand lenses. Sand is fine [Sandgate Formation]								5
			9.00	D	100			0										0
10.00	D				(49)	10.00			No recovery from 7.0 to 7.80m, likely washed out sand.								6	
Hole Diameter		Casing Diameter		Chiselling				Inclination and Orientation				Drilling Flush						
Depth Base	Diameter	Depth Base	Diameter	Depth Top	Depth Base	Duration	Tool	Depth Top	Depth Base	Inclination	Orientation	Depth Top	Depth Base	Type	Colour	Min (%)	Max (%)	
Remarks															IDOM			





IDOM		Rotary Core Log																				
Project Name: Grove House								Client: Gladman						Date: 24/01/2025 - 28/01/2025								
Location: Main Road, Sellindge, Kent								Contractor:						Co-ords: E610020.77 N138263.43								
Project No. : 22653H								Crew Name: Marshall Drilling						Drilling Equipment:								
Borehole Number MBH101				Hole Type CP+RC				Level				Logged By Ben Alexander				Scale 1:50		Page Number Sheet 2 of 2				
Well	Depth (m)	Type / FI	Coring			Diameter Recovery (SPT)	Depth (m)	Level (m)	Legend	Stratum Description												
			TCR	SCR	RQD																	
	11.50 - 12.30	B	60	0	0	11.50	11.50		Stiff grey silty slightly sandy CLAY with clayey and silty fine sand lenses. Sand is fine [Sandgate Formation]								11					
			75	58	58				Moderately weak greenish grey fine grained SANDSTONE with shell fragments. Very closely to closely spaced undulating fractures (Min = 5cm, Max = 63cm, Average 26cm) at 80 to 90 degrees [Sandgate Formation]								12					
	14.00 - 14.40	U	87	76	67				Strong grey shelly LIMESTONE from 12.90 to 13.0m. Becomes grey and strong or greater from 13.20m.								13					
			15.20 - 15.50	U	95				89	89	Infilled fracture with soft grey slightly sandy clay at 13.80 to 13.90m.								14			
	16.80 - 17.20	U			90				73	66	Infilled fracture with soft grey slightly sandy clay at 16.1 to 16.2m.								15			
			17.50 - 18.50	B	100				47	30	Fractured and non intact zone from 17.5 to 18.6m.								16			
	97	97			72				End of Borehole at 19.30m								17					
																			18			
																			19			
																			20			
Hole Diameter		Casing Diameter		Chiselling				Inclination and Orientation				Drilling Flush										
Depth Base	Diameter	Depth Base	Diameter	Depth Top	Depth Base	Duration	Tool	Depth Top	Depth Base	Inclination	Orientation	Depth Top	Depth Base	Type	Colour	Min (%)	Max (%)					
Remarks															IDOM							

IDOM		Trial Pit Log														
Project Name: Grove House					Client: Gladman					Date: 23/01/2025						
Location: Main Road, Sellindge, Kent					Contractor:					Co-ords: E609998.60 N138271.33						
Project No. : 22653H					Crew Name: Tara Plant Hire					Equipment: JCB						
Location Number MTP101			Location Type TP		Level		Logged By Ben Alexander			Scale 1:20		Page Number Sheet 1 of 1				
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description								
		Depth (m)	Type	Results												
		1.00 1.00	B HV	HVP=30 kPa	0.30			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.				0.5				
								Soft orange brown mottled grey slightly sandy CLAY. Sand is fine to medium [Head deposits]								
		2.00 2.00	B		1.50			Soft orange brown mottled grey sandy CLAY. Sand is fine to medium [Sandgate Formation]				1.5				
		2.90 2.90	B		1.80			Orange brown mottled grey clayey fine to medium SAND [Sandgate Formation]				2.0				
		2.90 2.90	B		3.00			<u>Becomes greyish brown and no longer clayey from 2.1m.</u>				2.5				
		2.90 2.90	B		3.00			End of Borehole at 3.00m				3.0				
		2.90 2.90	B		3.00							3.5				
		2.90 2.90	B		3.00							4.0				
Dimensions					Trench Support and Comment					Pumping Data						
Pit Length 1.40		Pit Width 0.45		Pit Stability Collapsing at 2.80m		Shoring Used		Remarks			Date		Rate		Remarks	
Remarks															IDOM	

IDOM		Trial Pit Log												
Project Name: Grove House					Client: Gladman					Date: 23/01/2025				
Location: Main Road, Sellindge, Kent					Contractor:					Co-ords: E609925.82 N138270.84				
Project No. : 22653H					Crew Name:					Equipment: JCB				
Location Number MTP102			Location Type TP		Level		Logged By Ben Alexander			Scale 1:20		Page Number Sheet 1 of 1		
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description						
		Depth (m)	Type	Results										
					0.20			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.						
								Soft orange brown slightly sandy CLAY [Head deposits]						
		0.60	HV	HVP=40 kPa										
		1.00	B											
		1.00	HV	HVP=60 kPa										
					1.40				Very soft greenish grey sandy CLAY with clayey sand horizons. Sand is fine to medium [Sandgate Formation]					
					2.10				Firm grey mottled orange brown sandy silty CLAY. Sand is fine to medium [Sandgate Formation]					
		2.20	B											
		2.30	HV	HVP=75 kPa					Greyish brown fine to medium SAND [Sandgate Formation]					
		2.80	B		3.00				End of Borehole at 3.00m					
Dimensions		Trench Support and Comment				Pumping Data								
Pit Length	Pit Width	Pit Stability	Shoring Used	Remarks			Date	Rate	Remarks					
1.50	0.45	Collasing at 2.9												
Remarks								IDOM						

IDOM		Trial Pit Log												
Project Name: Grove House					Client: Gladman					Date: 23/01/2025				
Location: Main Road, Sellindge, Kent					Contractor:					Co-ords: E609853.00 N138240.10				
Project No. : 22653H					Crew Name: Tara Plant Hire					Equipment: JCB				
Location Number MTP103			Location Type TP		Level		Logged By Ben Alexander			Scale 1:20		Page Number Sheet 1 of 1		
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description						
		Depth (m)	Type	Results										
		1.00	B HV	HVP=30 kPa	0.50			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.		0.5				
		1.00						Soft brown slightly sandy slightly gravelly CLAY. Sand is fine to medium. Gravel is fine to medium, sub angular of flint [Head deposits]		1.0				
		2.00	B HV	HVP=35 kPa	2.20					1.5				
		2.00								2.0				
	▼							End of Borehole at 2.20m		2.5				
										3.0				
										3.5				
										4.0				
Dimensions				Trench Support and Comment						Pumping Data				
Pit Length		Pit Width		Pit Stability	Shoring Used	Remarks			Date	Rate	Remarks			
1.50		0.45		Stable										
Remarks											IDOM			

IDOM		Trial Pit Log										
Project Name: Grove House				Client: Gladman				Date: 23/01/2025				
Location: Main Road, Sellindge, Kent				Contractor:				Co-ords: E609821.39 N138199.47				
Project No. : 22653H				Crew Name: Tara Plant Hire				Equipment: JCB				
Location Number MTP104		Location Type TP		Level		Logged By Ben Alexander		Scale 1:20		Page Number Sheet 1 of 1		
Well	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description					
	Depth (m)	Type	Results									
				0.40			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.		<div>0.5</div> <div>1.0</div> <div>1.5</div> <div>2.0</div> <div>2.5</div> <div>3.0</div> <div>3.5</div> <div>4.0</div>			
							Firm grey mottled orange brown slightly sandy CLAY with clayey sand and sandy clay horizons. Sand is fine to medium [Sandgate Formation]					
	0.80	HV	HVP=60 kPa									
	1.20 1.20	B HV	HVP=80 kPa									
	2.20 2.30	B HV	HVP=70 kPa	2.30								
							End of Borehole at 2.30m					
Dimensions				Trench Support and Comment				Pumping Data				
Pit Length 1.50		Pit Width 0.45		Pit Stability Stable		Shoring Used		Remarks		Date	Rate	Remarks
Remarks											IDOM	







IDOM		Trial Pit Log									
Project Name: Grove House			Client: Gladman			Date: 23/01/2025					
Location: Main Road, Sellindge, Kent			Contractor:			Co-ords: E609880.78 N138210.09					
Project No. : 22653H			Crew Name: Tara Plant Hire			Equipment: JCB					
Location Number MTP105		Location Type TP		Level		Logged By Ben Alexander		Scale 1:20		Page Number Sheet 1 of 1	
Well	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description				
	Depth (m)	Type	Results								
				0.40			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.				
	0.80	HV	HVP=70 kPa				Firm grey mottled orange brown slightly sandy silty CLAY. Sand is fine to medium [Sandgate Formation]	0.5			
								1.0			
	1.30	B						1.5			
								2.0			
	2.20 2.30	HV B	HVP=80 kPa					2.5			
			2.70			Stiff friable grey sandy CLAY with clayey sand horizons. Sand is fine to medium [Sandgate Formation]	3.0				
3.00	B		3.10			End of Borehole at 3.10m					
								3.5			
								4.0			
Dimensions			Trench Support and Comment				Pumping Data				
Pit Length	Pit Width	Pit Stability	Shoring Used	Remarks			Date	Rate	Remarks		
1.60	0.45	Stable									
Remarks								IDOM			









Project Name: Grove House			Client: Gladman			Date: 23/01/2025		
Location: Main Road, Sellindge, Kent			Contractor:			Co-ords: E609915.60 N138172.14		
Project No. : 22653H			Crew Name: Tara Plant Hire			Equipment: JCB		
Location Number MTP106		Location Type TP		Level		Logged By Ben Alexander		Page Number Sheet 1 of 1











Well	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description	
	Depth (m)	Type	Results					
				0.30			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.	
							Soft grey mottled orange brown slightly sandy CLAY. Sand is fine to medium [Head deposits]	0.5
	0.80	HV	HVP=35 kPa					1.0
	1.20	B						
	1.30	HV	HVP=60 kPa					
				1.40			Soft greenish grey sandy CLAY with clayey sand horizons. Sand is fine to medium [Sandgate Formation]	1.5
				1.60			Soft brown mottled orange brown sandy CLAY. Sand is fine to medium [Sandgate Formation]	
								2.0
	2.40	B						
	2.40	HV	HVP=50 kPa					2.5
				2.80			Orange brown mottled grey fine to medium clayey SAND.	3.0
	3.40	B					Becomes greeish grey from 3.3m.	
				3.50			End of Borehole at 3.50m	3.5
								4.0

Dimensions			Trench Support and Comment			Pumping Data		
Pit Length	Pit Width	Pit Stability	Shoring Used	Remarks		Date	Rate	Remarks
1.60	0.45	Stable						

Remarks






IDOM					Borehole Log					Borehole No. MWS101	
Project Name: Grove House					Client: Gladman					Date: 21/01/2025	
Location: Main Road, Sellindge, Kent					Contractor: 3D Drilling					Co-ords: E610104.98 N138236.91	
Project No: 22653H					Weather:					Drilling Equipment:	
Logged By Ben Alexander		Checked By CMM			Level		Hole Type WLS		Scale 1:30		Page Number Sheet 1 of 1
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description			
		Depth (m)	Type	Results							
		0.10	ES		0.30			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.			
		0.40	ES					Soft brown mottled orange brown slightly sandy CLAY. Sand is fine to medium. [Head deposits]			
		0.50	D								
		1.00	SPT	N=7 (1,1/2,1,2,2)	1.90						
		1.50	D								
		2.00	SPT	N=13 (2,3/4,3,3,3)							
		2.50	D		2.60			Medium dense, greyish brown and orange brown fine to medium SAND [Sandgate Formation] <i>Becomes clayey sand from 2.0m.</i>			
		3.00	SPT	N=17 (5,5/5,4,4,4)				Soft brown and greyish brown sandy CLAY. Sand is fine to medium [Sandgate Formation]			
		3.50	D								
		4.00	SPT	N=30 (15 for 75mm/7,7,8,8)	4.00			Firm brown sandy CLAY. Sand is fine to medium [Sandgate Formation].			
						End of Borehole at 4.00m					
Casing Details					Legend					Remarks	
Diameter	Top (m bgl)	Base (m bgl)			HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample					Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.	
Chiselling Details											
Top (m bgl)	Base (m bgl)	Duration (mins)									
										Groundwater Details	
					Depth Strike (m bgl)					Depth Rose (m bgl)	Time Elapsed (mins)






IDOM				Borehole Log				Borehole No. MWS102		
Project Name: Grove House				Client: Gladman				Date: 21/01/2025		
Location: Main Road, Sellindge, Kent				Contractor: 3D Drilling				Co-ords: E610038.32 N138254.71		
Project No: 22653H				Weather:				Drilling Equipment:		
Logged By Ben Alexander		Checked By CMM		Level		Hole Type WLS		Scale 1:30	Page Number Sheet 1 of 1	
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description		
		Depth (m)	Type	Results						
		0.10	ES		0.25		[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.	1		
		0.30	ES						Soft Brown mottled orange brown CLAY [Head deposits]	
		0.50	D							
		1.00	SPT	N=9 (2,1/1,3,2,3)	1.20		Soft to firm greenish grey and orange brown sandy CLAY [Sandgate Formation]	2		
		1.50	ES							
		2.00	SPT	N=14 (0,2/2,3,4,5)	2.00		Firm grey and orange brown slightly sandy CLAY. Sand is fine to medium [Sandgate Formation]	3		
		2.50	D							
		3.00	SPT	N=20 (3,4/5,4,5,6)	3.10		Grey and orange brown fine to medium SAND [Sandgate Formation]	4		
		3.50	D							
		3.70	SPT	N=50 (9,10/50 for 295mm)	3.70		Firm grey slightly sandy CLAY. Sand is fine to medium [Sandgate Formation]	5		
					Very dense brown clayey fine to medium SAND [Sandgate Formation]					
							End of Borehole at 3.70m	6		
Casing Details				Legend				Remarks		
Diameter	Top (m bgl)	Base (m bgl)		HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample				Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.		
Chiselling Details										
Top (m bgl)	Base (m bgl)	Duration (mins)		SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample				Groundwater Details		
								Depth Strike (m bgl)	Depth Rose (m bgl)	Time Elapsed (mins)

IDOM					Borehole Log					Borehole No. MWS103	
Project Name: Grove House					Client: Gladman				Date: 21/01/2025		
Location: Main Road, Sellindge, Kent					Contractor: 3D Drilling				Co-ords: E609939.69 N138200.88		
Project No: 22653H					Weather:				Drilling Equipment:		
Logged By Ben Alexander		Checked By CMM		Level		Hole Type WLS		Scale 1:30		Page Number Sheet 1 of 1	
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description			
		Depth (m)	Type	Results							
		0.10	ES		0.30			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.			
		0.40	ES					Soft orange brown and grey slightly sandy CLAY. Sand is fine to medium [Head deposits].			
		1.00	SPT	N=0 (0,0/0,0,0,0)	1.00			Soft greenish grey and orange brown sandy CLAY [Sandgate Formation]			
		1.50	D								
		2.00	SPT	N=12 (2,2/2,3,3,4)	2.80			Medium dense, grey and brown fine to medium clayey SAND			
		2.50	D								
		3.00	SPT	N=22 (3,4/5,5,7,5)	3.40			Firm grey and brown CLAY [Sandgate Formation]			
		3.50	D								
		3.70	SPT	N=50 (25 for 85mm/50 for 145mm)	3.70			End of Borehole at 3.70m			
Casing Details				Legend				Remarks			
Diameter	Top (m bgl)	Base (m bgl)		HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample				Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.			
Chiselling Details											
Top (m bgl)	Base (m bgl)	Duration (mins)									
				Groundwater Details							
				Depth Strike (m bgl)		Depth Rose (m bgl)		Time Elapsed (mins)			





IDOM				Borehole Log				Borehole No. MWS104	
Project Name: Grove House				Client: Gladman				Date: 21/01/2025	
Location: Main Road, Sellindge, Kent				Contractor: 3D Drilling				Co-ords: E609818.32 N138228.79	
Project No: 22653H				Weather:				Drilling Equipment:	
Logged By Ben Alexander		Checked By CMM		Level		Hole Type WLS		Scale 1:30	Page Number Sheet 1 of 1
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description	
		Depth (m)	Type	Results					
		0.10	ES		0.30			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.	
								Brown slightly sandy CLAY [Head deposits]	
		0.60	ES		1.00				1
		1.00	D						
		1.00	SPT	N=6 (0,0/2,1,2,1)				Soft to firm brown mottled orange brown slightly sandy CLAY. Sand is fine to medium [Sandgate Formation]	
		2.00	D		2.00				2
		2.00	SPT	N=12 (2,2/3,2,3,4)					
		3.00	D		3.00				3
		3.00	SPT	N=7 (2,1/2,2,1,2)					
		4.00	SPT	N=14 (4,4/4,3,3,4)	4.00			End of Borehole at 4.00m	4
								5	
								6	

Casing Details			Legend HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample	Remarks Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.	
Diameter	Top (m bgl)	Base (m bgl)			
Chiselling Details					
Top (m bgl)	Base (m bgl)	Duration (mins)			
			Groundwater Details		
			Depth Strike (m bgl)	Depth Rose (m bgl)	Time Elapsed (mins)

IDOM				Borehole Log				Borehole No. MWS105		
Project Name: Grove House				Client: Gladman				Date: 21/01/2025		
Location: Main Road, Sellindge, Kent				Contractor: 3D Drilling				Co-ords: E609864.25 N138185.19		
Project No: 22653H				Weather:				Drilling Equipment:		
Logged By Ben Alexander		Checked By CMM		Level		Hole Type WLS		Scale 1:30	Page Number Sheet 1 of 1	
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description		
		Depth (m)	Type	Results						
		0.10	ES		0.30			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.	1	
		0.50	D					Soft brown mottled orange brown slightly sandy slightly gravelly CLAY. Gravel is fine to medium of flint and sandstone [Head deposits]		
		1.00	SPT	N=10 (2,1/1,3,3,3)	1.20			Becomes gravelly from 0.9 to 1.2m. Becomes firm from 1.0m.		2
		1.50	D					Firm grey mottled orange brown sandy CLAY. Sand is fine to medium. [Sandgate Formation]		
		2.00	SPT	N=8 (1,2/1,2,2,3)			Becomes from to stiff from 2.0m.	3		
		2.50	D				Disturbed sample at 2.5m is clayey SAND.			
		3.00	SPT	N=24 (7,6/4,5,8,7)				4		
		3.50	D							
4.00	SPT	N=20 (3,4/4,5,5,6)	4.00			End of Borehole at 4.00m	4			
										5
										6
Casing Details				Legend				Remarks		
Diameter	Top (m bgl)	Base (m bgl)		HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample				Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.		
Chiselling Details								Groundwater Details		
Top (m bgl)	Base (m bgl)	Duration (mins)						Depth Strike (m bgl)	Depth Rose (m bgl)	Time Elapsed (mins)

IDOM				Borehole Log				Borehole No. MWS106	
Project Name: Grove House				Client: Gladman				Date: 21/01/2025	
Location: Main Road, Sellindge, Kent				Contractor: 3D Drilling				Co-ords: E610077.19 N138194.18	
Project No: 22653H				Weather:				Drilling Equipment:	
Logged By Ben Alexander		Checked By CMM		Level		Hole Type WLS		Scale 1:30	Page Number Sheet 1 of 1
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description	
		Depth (m)	Type	Results					
		0.10	ES		0.25		[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of brick and flint.	1	
		0.40 0.50	ES D				Soft grey mottled orange brown slightly sandy CLAY. Sand is fine to medium [Head deposits]		
		1.00	SPT	N=13 (1,1/2,3,4,4)	1.70		Grey and orange brown clayey fine to medium SAND [Sandgate Formation]	2	
		1.50	D						
		2.00	SPT	N=14 (1,3/3,3,4,4)	2.10		Firm to stiff grey mottled orange brown sandy CLAY with bands of fine to medium clayey sand. Sand is fine to medium [Sandgate Formation].	3	
		2.50	D						
		3.00	SPT	N=38 (2,6/10,10,10,8)	4.00		End of Borehole at 4.00m	4	
		3.50	D						
		4.00	SPT	N=50 (10,11/50 for 260mm)					5
Casing Details				Legend				Remarks	
Diameter	Top (m bgl)	Base (m bgl)	HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample				Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.		
Chiselling Details				Groundwater Details					
Top (m bgl)	Base (m bgl)	Duration (mins)	Depth Strike (m bgl)				Depth Rose (m bgl)	Time Elapsed (mins)	

IDOM				Borehole Log				Borehole No. MWS107		
Project Name: Grove House				Client: Gladman				Date: 21/01/2025		
Location: Main Road, Sellindge, Kent				Contractor: 3D Drilling				Co-ords: E610064.24 N138163.24		
Project No: 22653H				Weather:				Drilling Equipment:		
Logged By Ben Alexander		Checked By CMM		Level		Hole Type WLS		Scale 1:30	Page Number Sheet 1 of 1	
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description		
		Depth (m)	Type	Results						
		0.10	ES		0.30			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of brick and flint.		
		0.40 0.50	ES D					Soft to firm brown mottled orange brown slightly sandy CLAY. Sand is fine to medium [Head deposits]		
		1.00	SPT	N=13 (2,2/3,4,3,3)	1.40			Stiff grey mottled orange brown slightly sandy CLAY with occasional clayey sand lenses. Sand is fine to medium [Sandgate Formation]	1	
		1.50	D							
		2.00	SPT	N=17 (2,7/2,5,5,5)					2	
		2.50	D							
		3.00	SPT	N=25 (3,3/5,5,7,8)					3	
					4.00				End of Borehole at 4.00m	4
										5
								6		
Casing Details				Legend				Remarks		
Diameter	Top (m bgl)	Base (m bgl)		HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample				Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.		
Chiselling Details								Groundwater Details		
Top (m bgl)	Base (m bgl)	Duration (mins)						Depth Strike (m bgl)	Depth Rose (m bgl)	Time Elapsed (mins)

IDOM					Borehole Log					Borehole No. MWS108	
Project Name: Grove House					Client: Gladman					Date: 21/01/2025	
Location: Main Road, Sellindge, Kent					Contractor: 3D Drilling					Co-ords: E610071.21 N138239.44	
Project No: 22653H					Weather:					Drilling Equipment:	
Logged By Ben Alexander		Checked By CMM			Level		Hole Type WLS		Scale 1:30		Page Number Sheet 1 of 1
Well	Water Strikes	Sample and In Situ Testing			Depth (m)	Level (m)	Legend	Stratum Description			
		Depth (m)	Type	Results							
		0.10	ES		0.20			[Topsoil] Soft brown slightly sandy slightly gravelly CLAY. Gravel is fine to coarse, sub angular to sub rounded of flint.			
		0.50	D					Soft brown mottled orange brown slightly sandy CLAY. Sand is fine to medium [Head deposits]			
		1.00	SPT	N=8 (1,2/1,2,2,3)	1.00			Firm grey mottled orange brown slightly sandy CLAY. Sand is fine to medium [Sandgate Formation]	1		
		1.50	D								
		2.00	SPT	N=12 (2,1/2,3,4,3)					2		
		2.50	D								
		3.00	SPT	N=30 (2,5/6,7,9,8)	3.00				3		
							End of Borehole at 3.00m		4		
									5		
									6		
Casing Details				Legend					Remarks		
Diameter	Top (m bgl)	Base (m bgl)		HVP = Hand Vane Peak (kPa) PP = Pocket Penetrometer (kg cm2) PID = Photoionisation detector (ppm) D = Small Disturbed Sample (tub) J = Organic Sample (amber glass jar) V = Volatile Sample (amber glass vial) B = Bulk Bag Sample SPT(C) = Standard Penetration Test (cone) SPT(S) = Standard Penetration Test (split spoon) U = Undisturbed Sample					Coordinates and levels, where indicated, must not be used for design purposes. The user is responsible for verifying all site and setting out dimensions.		
Chiselling Details											
Top (m bgl)	Base (m bgl)	Duration (mins)									
				Groundwater Details							
				Depth Strike (m bgl)		Depth Rose (m bgl)		Time Elapsed (mins)			

**APPENDIX 6**

- Soil Chemistry
- Summary Spreadsheet
- Laboratory Analysis Certificates

Merebrook  
Cromford Mills  
Mill Lane  
Cromford  
Derbyshire  
DE4 3RQ

i2 Analytical Ltd.  
7 Woodshots Meadow,  
Croxley Green  
Business Park,  
Watford,  
Herts,  
WD18 8YS

e: balexander@idom.com  
coliveira@idom.com

t: 01923 225404  
f: 01923 237404  
e: reception@i2analytical.com

## **Analytical Report Number : 25-003326**

<b>Project / Site name:</b>	Grove	<b>Samples received on:</b>	23/01/2025
<b>Your job number:</b>	22653H	<b>Samples instructed on/ Analysis started on:</b>	27/01/2025
<b>Your order number:</b>	25-2-FDO-LABS	<b>Analysis completed by:</b>	03/02/2025
<b>Report Issue Number:</b>	1	<b>Report issued on:</b>	03/02/2025
<b>Samples Analysed:</b>	7 soil samples		

**Signed:** 

Joanna Wawrzeczko  
Senior Reporting Specialist  
**For & on behalf of i2 Analytical Ltd.**

Standard Geotechnical, Asbestos and Chemical Testing Laboratory located at: ul. Pionierów 39, 41-711 Ruda Śląska, Poland.

Accredited tests are defined within the report, opinions and interpretations expressed herein are outside the scope of accreditation.

Standard sample disposal times, unless otherwise agreed with the laboratory, are :	soils	- 4 weeks from reporting
	leachates	- 2 weeks from reporting
	waters	- 2 weeks from reporting
	asbestos	- 6 months from reporting
	air	- once the analysis is complete

Excel copies of reports are only valid when accompanied by this PDF certificate.

Retention period for records and reports is minimum 6 years from the date of issue of the final report.  
Some records may be kept for longer according to other legal/best practice requirements.

Any assessments of compliance with specifications are based on actual analytical results with no contribution from uncertainty of measurement.  
Application of uncertainty of measurement would provide a range within which the true result lies.  
An estimate of measurement uncertainty can be provided on request.

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433730	433731	433732	433733	433734
Sample Reference				MWS101	MWS103	MWS104	MWS105	MWS106
Sample Number				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Water Matrix				N/A	N/A	N/A	N/A	N/A
Depth (m)				0.10	0.10	0.60	0.10	0.10
Date Sampled				21/01/2025	21/01/2025	21/01/2025	21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Analytical Parameter (Soil Analysis)				Units	Test Limit of detection	Test Accreditation Status		

Stone Content	%	0.1	NONE	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Moisture Content	%	0.01	NONE	25	28	17	20	18
Total mass of sample received	kg	0.1	NONE	0.8	0.6	0.6	0.6	0.6

#### Asbestos

Asbestos in Soil Detected/Not Detected	Type	N/A	ISO 17025	Not-detected	Not-detected	Not-detected	Not-detected	Not-detected
Asbestos Analyst ID	N/A	N/A	N/A	SPU	SPU	SPU	SPU	SPU

#### General Inorganics

pH (L099)	pH Units	N/A	MCERTS	5.9	6.6	9	5.9	6
Water Soluble Sulphate as SO <sub>4</sub> 16hr extraction (2:1)	mg/kg	2.5	MCERTS	22	18	6.8	21	24
Water Soluble SO <sub>4</sub> 16hr extraction (2:1 Leachate Equivalent)	g/l	0.00125	MCERTS	0.0112	0.0088	0.00342	0.0105	0.0121
Water Soluble SO <sub>4</sub> 16hr extraction (2:1 Leachate Equivalent)	mg/l	1.25	MCERTS	11.2	8.8	3.42	10.5	12.1
Organic Matter (automated)	%	0.1	MCERTS	3.6	3.5	0.8	4.1	3.9
Total Organic Carbon (TOC) - Automated	%	0.1	MCERTS	2.1	2.1	0.5	2.4	2.3

#### Total Phenols

Total Phenols (monohydric)	mg/kg	1	MCERTS	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0
----------------------------	-------	---	--------	-------	-------	-------	-------	-------

#### Speciated PAHs

Naphthalene	mg/kg	0.05	MCERTS	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Acenaphthylene	mg/kg	0.05	MCERTS	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Acenaphthene	mg/kg	0.05	MCERTS	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Fluorene	mg/kg	0.05	MCERTS	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Phenanthrene	mg/kg	0.05	MCERTS	0.17	0.11	< 0.05	< 0.05	< 0.05
Anthracene	mg/kg	0.05	MCERTS	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Fluoranthene	mg/kg	0.05	MCERTS	0.5	0.48	< 0.05	0.08	0.05
Pyrene	mg/kg	0.05	MCERTS	0.45	0.43	< 0.05	0.06	< 0.05
Benzo(a)anthracene	mg/kg	0.05	MCERTS	0.24	0.23	< 0.05	< 0.05	< 0.05
Chrysene	mg/kg	0.05	MCERTS	0.34	0.4	< 0.05	< 0.05	< 0.05
Benzo(b)fluoranthene	mg/kg	0.05	ISO 17025	0.36	0.45	< 0.05	< 0.05	< 0.05
Benzo(k)fluoranthene	mg/kg	0.05	ISO 17025	0.21	0.24	< 0.05	< 0.05	< 0.05
Benzo(a)pyrene	mg/kg	0.05	MCERTS	0.32	0.34	< 0.05	< 0.05	< 0.05
Indeno(1,2,3-cd)pyrene	mg/kg	0.05	MCERTS	0.22	0.22	< 0.05	< 0.05	< 0.05
Dibenz(a,h)anthracene	mg/kg	0.05	MCERTS	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Benzo(ghi)perylene	mg/kg	0.05	MCERTS	0.23	0.26	< 0.05	< 0.05	< 0.05

#### Total PAH

Speciated Total EPA-16 PAHs	mg/kg	0.8	ISO 17025	3.03	3.17	< 0.80	< 0.80	< 0.80
-----------------------------	-------	-----	-----------	------	------	--------	--------	--------

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433730	433731	433732	433733	433734
Sample Reference				MWS101	MWS103	MWS104	MWS105	MWS106
Sample Number				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Water Matrix				N/A	N/A	N/A	N/A	N/A
Depth (m)				0.10	0.10	0.60	0.10	0.10
Date Sampled				21/01/2025	21/01/2025	21/01/2025	21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Analytical Parameter (Soil Analysis)				Units	Test Limit of detection	Test Accreditation Status		

#### Heavy Metals / Metalloids

Arsenic (aqua regia extractable)	mg/kg	1	MCERTS	8	9.3	6.5	7.9	8.4
Barium (aqua regia extractable)	mg/kg	1	MCERTS	44	55	43	31	32
Cadmium (aqua regia extractable)	mg/kg	0.2	MCERTS	< 0.2	0.2	< 0.2	< 0.2	< 0.2
Chromium (hexavalent)	mg/kg	1.8	MCERTS	< 1.8	< 1.8	< 1.8	< 1.8	< 1.8
Chromium (III)	mg/kg	1	NONE	21	25	20	17	17
Chromium (aqua regia extractable)	mg/kg	1	MCERTS	22	25	20	17	19
Copper (aqua regia extractable)	mg/kg	1	MCERTS	10	13	6.7	7.1	9
Lead (aqua regia extractable)	mg/kg	1	MCERTS	32	50	9.7	22	21
Mercury (aqua regia extractable)	mg/kg	0.3	MCERTS	< 0.3	< 0.3	< 0.3	< 0.3	< 0.3
Nickel (aqua regia extractable)	mg/kg	1	MCERTS	11	13	10	6.2	6.6
Selenium (aqua regia extractable)	mg/kg	1	MCERTS	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0
Vanadium (aqua regia extractable)	mg/kg	1	MCERTS	31	32	25	25	27
Zinc (aqua regia extractable)	mg/kg	1	MCERTS	49	55	34	30	34

#### Petroleum Hydrocarbons

TPHCWG - Aliphatic >EC5 - EC6 <sub>HS_1D_AL</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010
TPHCWG - Aliphatic >EC6 - EC8 <sub>HS_1D_AL</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010
TPHCWG - Aliphatic >EC8 - EC10 <sub>HS_1D_AL</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010
TPHCWG - Aliphatic >EC10 - EC12 <sub>EH_CU_1D_AL</sub>	mg/kg	1	MCERTS	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0
TPHCWG - Aliphatic >EC12 - EC16 <sub>EH_CU_1D_AL</sub>	mg/kg	2	MCERTS	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0
TPHCWG - Aliphatic >EC16 - EC21 <sub>EH_CU_1D_AL</sub>	mg/kg	8	MCERTS	< 8.0	< 8.0	< 8.0	< 8.0	< 8.0
TPHCWG - Aliphatic >EC21 - EC35 <sub>EH_CU_1D_AL</sub>	mg/kg	8	MCERTS	< 8.0	< 8.0	< 8.0	< 8.0	< 8.0
TPHCWG - Aliphatic >EC35 - EC40 <sub>EH_CU_1D_AL</sub>	mg/kg	10	NONE	< 10	< 10	< 10	< 10	< 10
TPHCWG - Aliphatic >EC5 - EC35 <sub>EH_CU+HS_1D_AL</sub>	mg/kg	10	NONE	< 10	< 10	< 10	< 10	< 10
TPHCWG - Aliphatic >EC5 - EC40 <sub>EH_CU+HS_1D_AL</sub>	mg/kg	10	NONE	< 10	< 10	< 10	< 10	< 10

TPHCWG - Aromatic >EC5 - EC7 <sub>HS_1D_AR</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010
TPHCWG - Aromatic >EC7 - EC8 <sub>HS_1D_AR</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010
TPHCWG - Aromatic >EC8 - EC10 <sub>HS_1D_AR</sub>	mg/kg	0.02	MCERTS	< 0.020	< 0.020	< 0.020	< 0.020	< 0.020
TPHCWG - Aromatic >EC10 - EC12 <sub>EH_CU_1D_AR</sub>	mg/kg	1	MCERTS	< 1.0	< 1.0	< 1.0	< 1.0	< 1.0
TPHCWG - Aromatic >EC12 - EC16 <sub>EH_CU_1D_AR</sub>	mg/kg	2	MCERTS	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0
TPHCWG - Aromatic >EC16 - EC21 <sub>EH_CU_1D_AR</sub>	mg/kg	10	MCERTS	< 10	< 10	< 10	< 10	< 10
TPHCWG - Aromatic >EC21 - EC35 <sub>EH_CU_1D_AR</sub>	mg/kg	10	MCERTS	< 10	< 10	< 10	< 10	< 10
TPHCWG - Aromatic >EC35 - EC40 <sub>EH_CU_1D_AR</sub>	mg/kg	10	NONE	< 10	< 10	< 10	< 10	< 10
TPHCWG - Aromatic >EC5 - EC35 <sub>EH_CU+HS_1D_AR</sub>	mg/kg	10	NONE	< 10	< 10	< 10	< 10	< 10
TPHCWG - Aromatic >EC5 - EC40 <sub>EH_CU+HS_1D_AR</sub>	mg/kg	10	NONE	< 10	< 10	< 10	< 10	< 10

TPH Total >EC5 - EC40 <sub>EH_CU+HS_1D_TOTAL</sub>	mg/kg	10	NONE	< 10	< 10	< 10	< 10	< 10
--	-------	----	------	------	------	------	------	------

#### VOCs

MTBE (Methyl Tertiary Butyl Ether)	µg/kg	5	MCERTS	< 5.0	< 5.0	< 5.0	< 5.0	< 5.0
Benzene	µg/kg	5	MCERTS	< 5.0	< 5.0	< 5.0	< 5.0	< 5.0
Toluene	µg/kg	5	MCERTS	< 5.0	< 5.0	< 5.0	< 5.0	< 5.0
Ethylbenzene	µg/kg	5	MCERTS	< 5.0	< 5.0	< 5.0	< 5.0	< 5.0
p & m-Xylene	µg/kg	8	MCERTS	< 8.0	< 8.0	< 8.0	< 8.0	< 8.0
o-Xylene	µg/kg	5	MCERTS	< 5.0	< 5.0	< 5.0	< 5.0	< 5.0



4041



Environmental Science

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433730	433731	433732	433733	433734
Sample Reference				MWS101	MWS103	MWS104	MWS105	MWS106
Sample Number				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Water Matrix				N/A	N/A	N/A	N/A	N/A
Depth (m)				0.10	0.10	0.60	0.10	0.10
Date Sampled				21/01/2025	21/01/2025	21/01/2025	21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Analytical Parameter (Soil Analysis)				Units	Test Limit of detection	Test Accreditation Status		

## Pesticides (GC-MS)

Alpha-BHC (Benzene Hexachloride)	µg/kg	10	NONE	-	-	-	< 10	-
Alachlor	µg/kg	10	NONE	-	-	-	< 10	-
Bifenthrin	µg/kg	10	NONE	-	-	-	< 10	-
Cyhalothrin (Lambda)	µg/kg	10	NONE	-	-	-	< 10	-
Gamma-BHC (Lindane, gamma HCH)	µg/kg	10	NONE	-	-	-	< 10	-
Ormethoate	µg/kg	10	NONE	-	-	-	< 10	-
1,2,3-Trichlorobenzene	µg/kg	10	NONE	-	-	-	< 10	-
1,3,5-Trichlorobenzene	µg/kg	10	NONE	-	-	-	< 10	-
2,6-Dichlorobenzonitrile	µg/kg	10	NONE	-	-	-	< 10	-
Dimethylvinphos	µg/kg	10	NONE	-	-	-	< 10	-
Demeton-O	µg/kg	10	NONE	-	-	-	< 10	-
Demeton-S	µg/kg	10	NONE	-	-	-	< 10	-
Endrin Aldehyde	µg/kg	10	NONE	-	-	-	< 10	-
Endrin Ketone	µg/kg	10	NONE	-	-	-	< 10	-
Hexachlorobutadiene	µg/kg	10	NONE	-	-	-	< 10	-
Phosphamidon (Sum)	µg/kg	10	NONE	-	-	-	< 10	-
1,2,4,5-Tetrachlorobenzene	µg/kg	10	NONE	-	-	-	< 10	-
Cis-Permethrin	µg/kg	10	NONE	-	-	-	< 10	-
Endosulfan sulfate	µg/kg	10	NONE	-	-	-	< 10	-
Etrinfos	µg/kg	10	NONE	-	-	-	< 10	-
Fenvalerate (Sum)	µg/kg	10	NONE	-	-	-	< 10	-
Hexachlorobenzene	µg/kg	10	NONE	-	-	-	< 10	-
Mevinphos, E+Z	µg/kg	10	NONE	-	-	-	< 10	-
Pentachlorobenzene	µg/kg	10	NONE	-	-	-	< 10	-
Pirimphos-ethyl	µg/kg	10	NONE	-	-	-	< 10	-
Propetamphos	µg/kg	10	NONE	-	-	-	< 10	-
Tecnazene	µg/kg	10	NONE	-	-	-	< 10	-
Triadimefon	µg/kg	10	NONE	-	-	-	< 10	-
Trans-Permethrin	µg/kg	10	NONE	-	-	-	< 10	-
Aldrin	µg/kg	10	NONE	-	-	-	< 10	-
Azinphos-methyl	µg/kg	10	NONE	-	-	-	< 10	-
Beta-BHC	µg/kg	10	NONE	-	-	-	< 10	-
Cis-Chlordane	µg/kg	10	NONE	-	-	-	< 10	-
Chlorfenvinphos	µg/kg	10	NONE	-	-	-	< 10	-
Chlorpyrifos	µg/kg	10	NONE	-	-	-	< 10	-
Chlorothalonil	µg/kg	10	NONE	-	-	-	< 10	-
Carbophenothion	µg/kg	10	NONE	-	-	-	< 10	-
Cyfluthrin (Sum)	µg/kg	10	NONE	-	-	-	< 10	-
Delta-BHC	µg/kg	10	NONE	-	-	-	< 10	-
Dieldrin	µg/kg	10	NONE	-	-	-	< 10	-
Deltamethrin	µg/kg	10	NONE	-	-	-	< 10	-
Heptachlor Exo-epoxide	µg/kg	10	NONE	-	-	-	< 10	-
Endrin	µg/kg	10	NONE	-	-	-	< 10	-
Endosulfan I (alpha isomer)	µg/kg	10	NONE	-	-	-	< 10	-
Endosulfan II (beta isomer)	µg/kg	10	NONE	-	-	-	< 10	-
Fenthion	µg/kg	10	NONE	-	-	-	< 10	-
Isodrin	µg/kg	10	NONE	-	-	-	< 10	-
Methacrifos	µg/kg	10	NONE	-	-	-	< 10	-
O,p'-DDD	µg/kg	10	NONE	-	-	-	< 10	-
O,p'-DDE	µg/kg	10	NONE	-	-	-	< 10	-



Environmental Science

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433730	433731	433732	433733	433734
Sample Reference				MWS101	MWS103	MWS104	MWS105	MWS106
Sample Number				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Water Matrix				N/A	N/A	N/A	N/A	N/A
Depth (m)				0.10	0.10	0.60	0.10	0.10
Date Sampled				21/01/2025	21/01/2025	21/01/2025	21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status					
O,p'-DDT	µg/kg	10	NONE	-	-	-	< 10	-
Parathion	µg/kg	10	NONE	-	-	-	< 10	-
Parathion-methyl	µg/kg	10	NONE	-	-	-	< 10	-
Pendimethalin	µg/kg	10	NONE	-	-	-	< 10	-
Phorate	µg/kg	10	NONE	-	-	-	< 10	-
Phosalone	µg/kg	10	NONE	-	-	-	< 10	-
P,p'-DDD	µg/kg	10	NONE	-	-	-	< 10	-
P,p'-DDE	µg/kg	10	NONE	-	-	-	< 10	-
P,p'-DDT	µg/kg	10	NONE	-	-	-	< 10	-
P,p'-Methoxychlor	µg/kg	10	NONE	-	-	-	< 10	-
Propyzamide	µg/kg	10	NONE	-	-	-	< 10	-
Triazophos	µg/kg	10	NONE	-	-	-	< 10	-
Trans-Chlordane	µg/kg	10	NONE	-	-	-	< 10	-
Cypermethrin (Sum)	µg/kg	10	NONE	-	-	-	< 10	-
Dichlorvos	µg/kg	10	NONE	-	-	-	< 10	-
Dimethoate	µg/kg	10	NONE	-	-	-	< 10	-
Diazinon	µg/kg	10	NONE	-	-	-	< 10	-
Ethion	µg/kg	10	NONE	-	-	-	< 10	-
Fenitrothion	µg/kg	10	NONE	-	-	-	< 10	-
Malathion	µg/kg	10	NONE	-	-	-	< 10	-
Pirimiphos-methyl	µg/kg	10	NONE	-	-	-	< 10	-
Trifluralin	µg/kg	10	NONE	-	-	-	< 10	-
Azinphos-ethyl	µg/kg	10	NONE	-	-	-	< 10	-

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433730	433731	433732	433733	433734
Sample Reference				MWS101	MWS103	MWS104	MWS105	MWS106
Sample Number				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Water Matrix				N/A	N/A	N/A	N/A	N/A
Depth (m)				0.10	0.10	0.60	0.10	0.10
Date Sampled				21/01/2025	21/01/2025	21/01/2025	21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status					

#### Pesticides (LC-MS)

Carbofuran, 3-OH	µg/kg	10	NONE	-	< 10	-	-	-
Tebuthiuron	µg/kg	10	NONE	-	< 10	-	-	-
Thiadiazuron	µg/kg	10	NONE	-	< 10	-	-	-
Aldicarb Sulfone	µg/kg	10	NONE	-	< 10	-	-	-
Aldicarb Sulfoxide	µg/kg	10	NONE	-	< 10	-	-	-
Aldicarb	µg/kg	10	NONE	-	< 10	-	-	-
Carbofuran	µg/kg	10	NONE	-	< 10	-	-	-
Fluometuron	µg/kg	10	NONE	-	< 10	-	-	-
Methomyl	µg/kg	10	NONE	-	< 10	-	-	-
Oxamyl	µg/kg	10	NONE	-	< 10	-	-	-
Propoxur	µg/kg	10	NONE	-	< 10	-	-	-
Siduron	µg/kg	10	NONE	-	< 10	-	-	-
Terbutryn	µg/kg	10	NONE	-	< 10	-	-	-
Carbaryl	µg/kg	10	NONE	-	< 10	-	-	-
Diiflubenuron	µg/kg	10	NONE	-	< 10	-	-	-
Isoproturon	µg/kg	10	NONE	-	< 10	-	-	-
Prometryn	µg/kg	10	NONE	-	< 10	-	-	-
Propazine	µg/kg	10	NONE	-	< 10	-	-	-
Trietazine	µg/kg	10	NONE	-	< 10	-	-	-
Atrazine	µg/kg	10	NONE	-	< 10	-	-	-
Chlorotoluron	µg/kg	10	NONE	-	< 10	-	-	-
Cyanazine	µg/kg	10	NONE	-	< 10	-	-	-
Diuron	µg/kg	10	NONE	-	< 10	-	-	-
Linuron	µg/kg	10	NONE	-	< 10	-	-	-
Methiocarb	µg/kg	10	NONE	-	< 10	-	-	-
Simazine	µg/kg	10	NONE	-	< 10	-	-	-
Terbutylazine	µg/kg	10	NONE	-	< 10	-	-	-

U/S = Unsuitable Sample I/S = Insufficient Sample ND = Not detected

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433735	433736
Sample Reference				MWS107	MWS108
Sample Number				None Supplied	None Supplied
Water Matrix				N/A	N/A
Depth (m)				0.10	0.10
Date Sampled				21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status		

Stone Content	%	0.1	NONE	< 0.1	< 0.1
Moisture Content	%	0.01	NONE	19	25
Total mass of sample received	kg	0.1	NONE	0.6	0.6

#### Asbestos

Asbestos in Soil Detected/Not Detected	Type	N/A	ISO 17025	Not-detected	-
Asbestos Analyst ID	N/A	N/A	N/A	SPU	-

#### General Inorganics

pH (L099)	pH Units	N/A	MCERTS	5.6	6.3
Water Soluble Sulphate as SO <sub>4</sub> 16hr extraction (2:1)	mg/kg	2.5	MCERTS	17	29
Water Soluble SO <sub>4</sub> 16hr extraction (2:1 Leachate Equivalent)	g/l	0.00125	MCERTS	0.0084	0.0143
Water Soluble SO <sub>4</sub> 16hr extraction (2:1 Leachate Equivalent)	mg/l	1.25	MCERTS	8.4	14.3
Organic Matter (automated)	%	0.1	MCERTS	4.7	4.4
Total Organic Carbon (TOC) - Automated	%	0.1	MCERTS	2.7	2.6

#### Total Phenols

Total Phenols (monohydric)	mg/kg	1	MCERTS	< 1.0	< 1.0
----------------------------	-------	---	--------	-------	-------

#### Speciated PAHs

Naphthalene	mg/kg	0.05	MCERTS	< 0.05	< 0.05
Acenaphthylene	mg/kg	0.05	MCERTS	< 0.05	< 0.05
Acenaphthene	mg/kg	0.05	MCERTS	< 0.05	< 0.05
Fluorene	mg/kg	0.05	MCERTS	< 0.05	< 0.05
Phenanthrene	mg/kg	0.05	MCERTS	0.14	< 0.05
Anthracene	mg/kg	0.05	MCERTS	< 0.05	< 0.05
Fluoranthene	mg/kg	0.05	MCERTS	0.2	0.11
Pyrene	mg/kg	0.05	MCERTS	0.15	0.09
Benzo(a)anthracene	mg/kg	0.05	MCERTS	0.08	< 0.05
Chrysene	mg/kg	0.05	MCERTS	0.08	0.06
Benzo(b)fluoranthene	mg/kg	0.05	ISO 17025	0.11	0.1
Benzo(k)fluoranthene	mg/kg	0.05	ISO 17025	0.07	< 0.05
Benzo(a)pyrene	mg/kg	0.05	MCERTS	0.08	< 0.05
Indeno(1,2,3-cd)pyrene	mg/kg	0.05	MCERTS	0.06	< 0.05
Dibenz(a,h)anthracene	mg/kg	0.05	MCERTS	< 0.05	< 0.05
Benzo(ghi)perylene	mg/kg	0.05	MCERTS	0.06	< 0.05

#### Total PAH

Speciated Total EPA-16 PAHs	mg/kg	0.8	ISO 17025	1.04	< 0.80
-----------------------------	-------	-----	-----------	------	--------

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433735	433736
Sample Reference				MWS107	MWS108
Sample Number				None Supplied	None Supplied
Water Matrix				N/A	N/A
Depth (m)				0.10	0.10
Date Sampled				21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status		

#### Heavy Metals / Metalloids

Arsenic (aqua regia extractable)	mg/kg	1	MCERTS	8.2	8
Barium (aqua regia extractable)	mg/kg	1	MCERTS	30	49
Cadmium (aqua regia extractable)	mg/kg	0.2	MCERTS	< 0.2	< 0.2
Chromium (hexavalent)	mg/kg	1.8	MCERTS	< 1.8	< 1.8
Chromium (III)	mg/kg	1	NONE	19	23
Chromium (aqua regia extractable)	mg/kg	1	MCERTS	19	24
Copper (aqua regia extractable)	mg/kg	1	MCERTS	8.2	11
Lead (aqua regia extractable)	mg/kg	1	MCERTS	24	34
Mercury (aqua regia extractable)	mg/kg	0.3	MCERTS	< 0.3	< 0.3
Nickel (aqua regia extractable)	mg/kg	1	MCERTS	6.5	11
Selenium (aqua regia extractable)	mg/kg	1	MCERTS	< 1.0	< 1.0
Vanadium (aqua regia extractable)	mg/kg	1	MCERTS	26	31
Zinc (aqua regia extractable)	mg/kg	1	MCERTS	35	52

#### Petroleum Hydrocarbons

TPHCWG - Aliphatic >EC5 - EC6 <sub>HS_1D_AL</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010
TPHCWG - Aliphatic >EC6 - EC8 <sub>HS_1D_AL</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010
TPHCWG - Aliphatic >EC8 - EC10 <sub>HS_1D_AL</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010
TPHCWG - Aliphatic >EC10 - EC12 <sub>EH_CU_1D_AL</sub>	mg/kg	1	MCERTS	< 1.0	< 1.0
TPHCWG - Aliphatic >EC12 - EC16 <sub>EH_CU_1D_AL</sub>	mg/kg	2	MCERTS	< 2.0	< 2.0
TPHCWG - Aliphatic >EC16 - EC21 <sub>EH_CU_1D_AL</sub>	mg/kg	8	MCERTS	< 8.0	< 8.0
TPHCWG - Aliphatic >EC21 - EC35 <sub>EH_CU_1D_AL</sub>	mg/kg	8	MCERTS	< 8.0	< 8.0
TPHCWG - Aliphatic >EC35 - EC40 <sub>EH_CU_1D_AL</sub>	mg/kg	10	NONE	< 10	< 10
TPHCWG - Aliphatic >EC5 - EC35 <sub>EH_CU+HS_1D_AL</sub>	mg/kg	10	NONE	< 10	< 10
TPHCWG - Aliphatic >EC5 - EC40 <sub>EH_CU+HS_1D_AL</sub>	mg/kg	10	NONE	< 10	< 10

TPHCWG - Aromatic >EC5 - EC7 <sub>HS_1D_AR</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010
TPHCWG - Aromatic >EC7 - EC8 <sub>HS_1D_AR</sub>	mg/kg	0.01	MCERTS	< 0.010	< 0.010
TPHCWG - Aromatic >EC8 - EC10 <sub>HS_1D_AR</sub>	mg/kg	0.02	MCERTS	< 0.020	< 0.020
TPHCWG - Aromatic >EC10 - EC12 <sub>EH_CU_1D_AR</sub>	mg/kg	1	MCERTS	< 1.0	< 1.0
TPHCWG - Aromatic >EC12 - EC16 <sub>EH_CU_1D_AR</sub>	mg/kg	2	MCERTS	< 2.0	< 2.0
TPHCWG - Aromatic >EC16 - EC21 <sub>EH_CU_1D_AR</sub>	mg/kg	10	MCERTS	< 10	< 10
TPHCWG - Aromatic >EC21 - EC35 <sub>EH_CU_1D_AR</sub>	mg/kg	10	MCERTS	< 10	< 10
TPHCWG - Aromatic >EC35 - EC40 <sub>EH_CU_1D_AR</sub>	mg/kg	10	NONE	< 10	< 10
TPHCWG - Aromatic >EC5 - EC35 <sub>EH_CU+HS_1D_AR</sub>	mg/kg	10	NONE	< 10	< 10
TPHCWG - Aromatic >EC5 - EC40 <sub>EH_CU+HS_1D_AR</sub>	mg/kg	10	NONE	< 10	< 10

TPH Total >EC5 - EC40 <sub>EH_CU+HS_1D_TOTAL</sub>	mg/kg	10	NONE	< 10	< 10
--	-------	----	------	------	------

#### VOCs

MTBE (Methyl Tertiary Butyl Ether)	µg/kg	5	MCERTS	< 5.0	< 5.0
Benzene	µg/kg	5	MCERTS	< 5.0	< 5.0
Toluene	µg/kg	5	MCERTS	< 5.0	< 5.0
Ethylbenzene	µg/kg	5	MCERTS	< 5.0	< 5.0
p & m-Xylene	µg/kg	8	MCERTS	< 8.0	< 8.0
o-Xylene	µg/kg	5	MCERTS	< 5.0	< 5.0

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433735	433736
Sample Reference				MWS107	MWS108
Sample Number				None Supplied	None Supplied
Water Matrix				N/A	N/A
Depth (m)				0.10	0.10
Date Sampled				21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status		

#### Pesticides (GC-MS)

Alpha-BHC (Benzene Hexachloride)	µg/kg	10	NONE	-	< 10
Alachlor	µg/kg	10	NONE	-	< 10
Bifenthrin	µg/kg	10	NONE	-	< 10
Cyhalothrin (Lambda)	µg/kg	10	NONE	-	< 10
Gamma-BHC (Lindane, gamma HCH)	µg/kg	10	NONE	-	< 10
Ormethoate	µg/kg	10	NONE	-	< 10
1,2,3-Trichlorobenzene	µg/kg	10	NONE	-	< 10
1,3,5-Trichlorobenzene	µg/kg	10	NONE	-	< 10
2,6-Dichlorobenzonitrile	µg/kg	10	NONE	-	< 10
Dimethylvinphos	µg/kg	10	NONE	-	< 10
Demeton-O	µg/kg	10	NONE	-	< 10
Demeton-S	µg/kg	10	NONE	-	< 10
Endrin Aldehyde	µg/kg	10	NONE	-	< 10
Endrin Ketone	µg/kg	10	NONE	-	< 10
Hexachlorobutadiene	µg/kg	10	NONE	-	< 10
Phosphamidon (Sum)	µg/kg	10	NONE	-	< 10
1,2,4,5-Tetrachlorobenzene	µg/kg	10	NONE	-	< 10
Cis-Permethrin	µg/kg	10	NONE	-	< 10
Endosulfan sulfate	µg/kg	10	NONE	-	< 10
Etrinfos	µg/kg	10	NONE	-	< 10
Fenvalerate (Sum)	µg/kg	10	NONE	-	< 10
Hexachlorobenzene	µg/kg	10	NONE	-	< 10
Mevinphos, E+Z	µg/kg	10	NONE	-	< 10
Pentachlorobenzene	µg/kg	10	NONE	-	< 10
Pirimphos-ethyl	µg/kg	10	NONE	-	< 10
Propetamphos	µg/kg	10	NONE	-	< 10
Tecnazene	µg/kg	10	NONE	-	< 10
Triadimefon	µg/kg	10	NONE	-	< 10
Trans-Permethrin	µg/kg	10	NONE	-	< 10
Aldrin	µg/kg	10	NONE	-	< 10
Azinphos-methyl	µg/kg	10	NONE	-	< 10
Beta-BHC	µg/kg	10	NONE	-	< 10
Cis-Chlordane	µg/kg	10	NONE	-	< 10
Chlorfenvinphos	µg/kg	10	NONE	-	< 10
Chlorpyrifos	µg/kg	10	NONE	-	< 10
Chlorothalonil	µg/kg	10	NONE	-	< 10
Carbophenothion	µg/kg	10	NONE	-	< 10
Cyfluthrin (Sum)	µg/kg	10	NONE	-	< 10
Delta-BHC	µg/kg	10	NONE	-	< 10
Dieldrin	µg/kg	10	NONE	-	< 10
Deltamethrin	µg/kg	10	NONE	-	< 10
Heptachlor Exo-epoxide	µg/kg	10	NONE	-	< 10
Endrin	µg/kg	10	NONE	-	< 10
Endosulfan I (alpha isomer)	µg/kg	10	NONE	-	< 10
Endosulfan II (beta isomer)	µg/kg	10	NONE	-	< 10
Fenthion	µg/kg	10	NONE	-	< 10
Isodrin	µg/kg	10	NONE	-	< 10
Methacrifos	µg/kg	10	NONE	-	< 10
O,p'-DDD	µg/kg	10	NONE	-	< 10
O,p'-DDE	µg/kg	10	NONE	-	< 10

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433735	433736
Sample Reference				MWS107	MWS108
Sample Number				None Supplied	None Supplied
Water Matrix				N/A	N/A
Depth (m)				0.10	0.10
Date Sampled				21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status		
O,p'-DDT	µg/kg	10	NONE	-	< 10
Parathion	µg/kg	10	NONE	-	< 10
Parathion-methyl	µg/kg	10	NONE	-	< 10
Pendimethalin	µg/kg	10	NONE	-	< 10
Phorate	µg/kg	10	NONE	-	< 10
Phosalone	µg/kg	10	NONE	-	< 10
P,p'-DDD	µg/kg	10	NONE	-	< 10
P,p'-DDE	µg/kg	10	NONE	-	< 10
P,p'-DDT	µg/kg	10	NONE	-	< 10
P,p'-Methoxychlor	µg/kg	10	NONE	-	< 10
Propyzamide	µg/kg	10	NONE	-	< 10
Triazophos	µg/kg	10	NONE	-	< 10
Trans-Chlordane	µg/kg	10	NONE	-	< 10
Cypermethrin (Sum)	µg/kg	10	NONE	-	< 10
Dichlorvos	µg/kg	10	NONE	-	< 10
Dimethoate	µg/kg	10	NONE	-	< 10
Diazinon	µg/kg	10	NONE	-	< 10
Ethion	µg/kg	10	NONE	-	< 10
Fenitrothion	µg/kg	10	NONE	-	< 10
Malathion	µg/kg	10	NONE	-	< 10
Pirimiphos-methyl	µg/kg	10	NONE	-	< 10
Trifluralin	µg/kg	10	NONE	-	< 10
Azinphos-ethyl	µg/kg	10	NONE	-	< 10

Analytical Report Number: 25-003326

Project / Site name: Grove

Your Order No: 25-2-FDO-LABS

Lab Sample Number				433735	433736
Sample Reference				MWS107	MWS108
Sample Number				None Supplied	None Supplied
Water Matrix				N/A	N/A
Depth (m)				0.10	0.10
Date Sampled				21/01/2025	21/01/2025
Time Taken				None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status		

#### Pesticides (LC-MS)

Carbofuran, 3-OH	µg/kg	10	NONE	< 10	-
Tebuthiuron	µg/kg	10	NONE	< 10	-
Thiadiazuron	µg/kg	10	NONE	< 10	-
Aldicarb Sulfone	µg/kg	10	NONE	< 10	-
Aldicarb Sulfoxide	µg/kg	10	NONE	< 10	-
Aldicarb	µg/kg	10	NONE	< 10	-
Carbofuran	µg/kg	10	NONE	< 10	-
Fluometuron	µg/kg	10	NONE	< 10	-
Methomyl	µg/kg	10	NONE	< 10	-
Oxamyl	µg/kg	10	NONE	< 10	-
Propoxur	µg/kg	10	NONE	< 10	-
Siduron	µg/kg	10	NONE	< 10	-
Terbutryn	µg/kg	10	NONE	< 10	-
Carbaryl	µg/kg	10	NONE	< 10	-
Diiflubenuron	µg/kg	10	NONE	< 10	-
Isoproturon	µg/kg	10	NONE	< 10	-
Prometryn	µg/kg	10	NONE	< 10	-
Propazine	µg/kg	10	NONE	< 10	-
Trietazine	µg/kg	10	NONE	< 10	-
Atrazine	µg/kg	10	NONE	< 10	-
Chlorotoluron	µg/kg	10	NONE	< 10	-
Cyanazine	µg/kg	10	NONE	< 10	-
Diuron	µg/kg	10	NONE	< 10	-
Linuron	µg/kg	10	NONE	< 10	-
Methiocarb	µg/kg	10	NONE	< 10	-
Simazine	µg/kg	10	NONE	< 10	-
Terbutylazine	µg/kg	10	NONE	< 10	-

U/S = Unsuitable Sample I/S = Insufficient Sample ND = Not detected

**Analytical Report Number : 25-003326**

**Project / Site name: Grove**

\* These descriptions are only intended to act as a cross check if sample identities are questioned. The major constituent of the sample is intended to act with respect to MCERTS validation. The laboratory is accredited for sand, clay and loam (MCERTS) soil types. Data for unaccredited types of solid should be interpreted with care.

Stone content of a sample is calculated as the % weight of the stones not passing a 10 mm sieve. Results are not corrected for stone content.

Lab Sample Number	Sample Reference	Sample Number	Depth (m)	Sample Description *
433730	MWS101	None Supplied	0.1	Brown loam and clay with gravel and vegetation
433731	MWS103	None Supplied	0.1	Brown loam and clay with gravel and vegetation
433732	MWS104	None Supplied	0.6	Brown loam and clay with gravel and vegetation
433733	MWS105	None Supplied	0.1	Brown loam and clay with gravel and vegetation
433734	MWS106	None Supplied	0.1	Brown loam and clay with gravel and vegetation
433735	MWS107	None Supplied	0.1	Brown loam and clay with gravel and vegetation
433736	MWS108	None Supplied	0.1	Brown loam and clay with gravel and vegetation

**Analytical Report Number : 25-003326**

**Project / Site name: Grove**

**Water matrix abbreviations:**

**Surface Water (SW) Potable Water (PW) Ground Water (GW) Process Waters Heating/Cooling (PrW) DI Process Water (DI PrW)**

**Final Sewage Effluent (FSE) Landfill Leachate (LL)**

Analytical Test Name	Analytical Method Description	Analytical Method Reference	Method number	Wet / Dry Analysis	Accreditation Status
Asbestos identification in Soil	Asbestos Identification with the use of polarised light microscopy in conjunction with dispersion staining techniques	In-house method based on HSG 248, 2021	A001B	D	ISO 17025
Organic matter (Automated) in soil	Determination of organic matter in soil by oxidising with potassium dichromate followed by titration with iron (II) sulphate (Walkley Black Method)	In-house method	L009B	D	MCERTS
Total organic carbon (Automated) in soil	Determination of organic matter in soil by oxidising with potassium dichromate followed by titration with iron (II) sulphate (Walkley Black Method)	In-house method	L009B	D	MCERTS
Moisture Content	Moisture content, determined gravimetrically (up to 30°C)	In-house method	L019B	W	NONE
Stones content of soil	Standard preparation for all samples unless otherwise detailed. Gravimetric determination of stone > 10 mm as % dry weight	In-house method based on British Standard Methods and MCERTS requirements.	L019B	D	NONE
Metals in soil by ICP-OES	Determination of metals in soil by aqua-regia digestion followed by ICP-OES	In-house method based on MEWAM 2006 Methods for the Determination of Metals in Soil	L038B	D	MCERTS
Sulphate, water soluble, in soil (16hr extraction)	Sulphate, water soluble, in soil (16hr extraction)	In-house method	L038B	D	MCERTS
Pesticides by GC-MS/MS	Determination of Pesticides in soil by GC MS/MS	In-house method	L055B	W	NONE
Pesticides by LC-MS	Determination of Pesticides in soil by LC-MS	In-house method	L056B	W	NONE
Speciated PAHs and/or Semi-volatile organic compounds in soil	Determination of semi-volatile organic compounds (including PAH) in soil by extraction in dichloromethane and hexane followed by GC-MS	In-house method based on USEPA 8270	L064B	D	MCERTS
BTEX and/or Volatile organic compounds in soil	Determination of volatile organic compounds in soil by headspace GC-MS	In-house method based on USEPA 8260	L073B	W	MCERTS
Total petroleum hydrocarbons with carbon banding by GC-FID/GC-MS HS in soil	Determination of total petroleum hydrocarbons in soil by GC-FID/GC-MS HS with carbon banding aliphatic and aromatic	In-house method	L076B/L088-PL	D/W	MCERTS
Chromium III in soil	In-house method by calculation from total Cr and Cr VI	In-house method by calculation	L080-PL/L130B	W	NONE
Hexavalent chromium in soil	Determination of hexavalent chromium in soil by extraction in NaOH and addition of 1,5 diphenylcarbazine followed by colorimetry	In-house method	L080-PL	W	MCERTS
Monohydric phenols in soil	Determination of phenols in soil by extraction with sodium hydroxide followed by distillation followed by colorimetry	In-house method based on Examination of Water and Wastewater 20th Edition: Clesceri, Greenberg & Eaton	L080-PL	W	MCERTS

**Analytical Report Number : 25-003326**

**Project / Site name: Grove**

**Water matrix abbreviations:**

**Surface Water (SW) Potable Water (PW) Ground Water (GW) Process Waters Heating/Cooling (PrW) DI Process Water (DI PrW)**

**Final Sewage Effluent (FSE) Landfill Leachate (LL)**

Analytical Test Name	Analytical Method Description	Analytical Method Reference	Method number	Wet / Dry Analysis	Accreditation Status
pH in soil (automated)	Determination of pH in soil by addition of water followed by automated electrometric measurement	In-house method	L099-PL	D	MCERTS

For method numbers ending in 'UK' or 'A' analysis have been carried out in our laboratory in the United Kingdom (Watford).

For method numbers ending in 'F' analysis have been carried out in our laboratory in the United Kingdom (East Kilbride).

For method numbers ending in 'PL' or 'B' analysis have been carried out in our laboratory in Poland.

Soil analytical results are expressed on a dry weight basis. Where analysis is carried out on as-received the results obtained are multiplied by a moisture correction factor that is determined gravimetrically using the moisture content which is carried out at a maximum of 30oC.

Unless otherwise indicated, site information, order number, project number, sampling date, time, sample reference and depth are provided by the client. The instructed on date indicates the date on which this information was provided to the laboratory.

Quality control parameter failure associated with individual result applies to calculated sum of individuals.

The result for sum should be interpreted with caution

Merebrook  
Cromford Mills  
Mill Lane  
Cromford  
Derbyshire  
DE4 3RQ

i2 Analytical Ltd.  
7 Woodshots Meadow,  
Croxley Green  
Business Park,  
Watford,  
Herts,  
WD18 8YS

e: balexander@idom.com  
coliveira@idom.com

t: 01923 225404  
f: 01923 237404  
e: reception@i2analytical.com

## **Analytical Report Number : 25-003327**

<b>Project / Site name:</b>	Grove	<b>Samples received on:</b>	23/01/2025
<b>Your job number:</b>	22653H	<b>Samples instructed on/ Analysis started on:</b>	27/01/2025
<b>Your order number:</b>	25-2-FDO-LABS	<b>Analysis completed by:</b>	03/02/2025
<b>Report Issue Number:</b>	1	<b>Report issued on:</b>	03/02/2025
<b>Samples Analysed:</b>	10:1 WAC sample		

**Signed:**



Dominika Liana  
Junior Reporting Specialist  
**For & on behalf of i2 Analytical Ltd.**

Standard Geotechnical, Asbestos and Chemical Testing Laboratory located at: ul. Pionierów 39, 41-711 Ruda Śląska, Poland.

Accredited tests are defined within the report, opinions and interpretations expressed herein are outside the scope of accreditation.

Standard sample disposal times, unless otherwise agreed with the laboratory, are :

soils	- 4 weeks from reporting
leachates	- 2 weeks from reporting
waters	- 2 weeks from reporting
asbestos	- 6 months from reporting
air	- once the analysis is complete

Excel copies of reports are only valid when accompanied by this PDF certificate.

Retention period for records and reports is minimum 6 years from the date of issue of the final report.  
Some records may be kept for longer according to other legal/best practice requirements.

Any assessments of compliance with specifications are based on actual analytical results with no contribution from uncertainty of measurement.  
Application of uncertainty of measurement would provide a range within which the true result lies.  
An estimate of measurement uncertainty can be provided on request.



Analytical Report Number: 25-003327  
Project / Site name: Grove  
Your Order No: 25-2-FDO-LABS

Lab Sample Number				433737
Sample Reference				MSW106
Sample Number				None Supplied
Water Matrix				N/A
Depth (m)				0.40
Date Sampled				21/01/2025
Time Taken				None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status	

Stone Content	%	0.1	NONE	< 0.1
Moisture Content	%	0.01	NONE	18
Total mass of sample received	kg	0.1	NONE	0.8

General Inorganics

pH (L005B)	pH Units	N/A	MCERTS	6.1
Total Organic Carbon (TOC) - Automated	%	0.1	MCERTS	0.8
Loss on Ignition @ 450°C	%	0.2	MCERTS	3
Acid Neutralisation Capacity	+/- mmol/kg	-9999	NONE	-4.5

Speciated PAHs

Naphthalene	mg/kg	0.05	MCERTS	< 0.05
Acenaphthylene	mg/kg	0.05	MCERTS	< 0.05
Acenaphthene	mg/kg	0.05	MCERTS	< 0.05
Fluorene	mg/kg	0.05	MCERTS	< 0.05
Phenanthrene	mg/kg	0.05	MCERTS	< 0.05
Anthracene	mg/kg	0.05	MCERTS	< 0.05
Fluoranthene	mg/kg	0.05	MCERTS	< 0.05
Pyrene	mg/kg	0.05	MCERTS	< 0.05
Benzo(a)anthracene	mg/kg	0.05	MCERTS	< 0.05
Chrysene	mg/kg	0.05	MCERTS	< 0.05
Benzo(b)fluoranthene	mg/kg	0.05	ISO 17025	< 0.05
Benzo(k)fluoranthene	mg/kg	0.05	ISO 17025	< 0.05
Benzo(a)pyrene	mg/kg	0.05	MCERTS	< 0.05
Indeno(1,2,3-cd)pyrene	mg/kg	0.05	MCERTS	< 0.05
Dibenz(a,h)anthracene	mg/kg	0.05	MCERTS	< 0.05
Benzo(ghi)perylene	mg/kg	0.05	MCERTS	< 0.05
Coronene	mg/kg	0.05	NONE	< 0.05

Total PAH

Total WAC-17 PAHs	mg/kg	0.85	NONE	< 0.85
-------------------	-------	------	------	--------

Petroleum Hydrocarbons

Mineral Oil (EC10 - EC40) <small>EH_CU_1D_AL</small>	mg/kg	10	NONE	< 10
--	-------	----	------	------

VOCs

Benzene	µg/kg	5	MCERTS	< 5.0
Toluene	µg/kg	5	MCERTS	< 5.0
Ethylbenzene	µg/kg	5	MCERTS	< 5.0
p & m-Xylene	µg/kg	8	MCERTS	< 8.0
o-Xylene	µg/kg	5	MCERTS	< 5.0

Total BTEX	µg/kg	10	MCERTS	< 10
------------	-------	----	--------	------



Analytical Report Number: 25-003327  
Project / Site name: Grove  
Your Order No: 25-2-FDO-LABS

Lab Sample Number				433737
Sample Reference				MSW106
Sample Number				None Supplied
Water Matrix				N/A
Depth (m)				0.40
Date Sampled				21/01/2025
Time Taken				None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status	

PCBs by GC-MS

PCB Congener 28	mg/kg	0.001	MCERTS	< 0.001
PCB Congener 52	mg/kg	0.001	MCERTS	< 0.001
PCB Congener 101	mg/kg	0.001	MCERTS	< 0.001
PCB Congener 118	mg/kg	0.001	MCERTS	< 0.001
PCB Congener 138	mg/kg	0.001	MCERTS	< 0.001
PCB Congener 153	mg/kg	0.001	MCERTS	< 0.001
PCB Congener 180	mg/kg	0.001	MCERTS	< 0.001
Total PCBs	mg/kg	0.007	MCERTS	< 0.007

U/S = Unsuitable Sample I/S = Insufficient Sample ND = Not detected



i2 Analytical

7 Woodshots Meadow  
Croxley Green Business Park  
Watford, WD18 8YS

Telephone: 01923 225404  
Fax: 01923 237404  
email:reception@i2analytical.com

Waste Acceptance Criteria Analytical Results							
Report No:	25-003327						
					Client: MEREBROOK		
Location	Grove						
Lab Reference (Sample Number)	433737				Landfill Waste Acceptance Criteria		
					Limits		
Sampling Date	21/01/2025				Inert Waste Landfill	Stable Non-reactive HAZARDOUS waste in non-hazardous Landfill	Hazardous Waste Landfill
Sample ID	MSW106						
Depth (m)	0.40						
Solid Waste Analysis							
TOC (%)**	0.8				3%	5%	6%
Loss on Ignition (%) **	3.0				--	--	10%
BTEX (µg/kg) **	< 10				6000	--	--
Sum of PCBs (mg/kg) **	< 0.007				1	--	--
Mineral Oil (mg/kg) <small>EH_1D_CU_AL</small>	< 10				500	--	--
Total PAH (WAC-17) (mg/kg)	< 0.85				100	--	--
pH (units)**	6.1				--	>6	--
Acid Neutralisation Capacity (mmol / kg)	-4.5				--	To be evaluated	To be evaluated
Eluate Analysis  (BS EN 12457 - 2 preparation utilising end over end leaching procedure)	10:1			10:1	Limit values for compliance leaching test		
	mg/l			mg/kg	using BS EN 12457-2 at L/S 10 l/kg (mg/kg)		
Arsenic *	0.00355			0.0355	0.5	2	25
Barium *	0.00436			0.0436	20	100	300
Cadmium *	< 0.000100			< 0.00100	0.04	1	5
Chromium *	0.0020			0.020	0.5	10	70
Copper *	0.0046			0.046	2	50	100
Mercury *	0.000815			0.00815	0.01	0.2	2
Molybdenum *	< 0.000400			< 0.00400	0.5	10	30
Nickel *	0.0017			0.017	0.4	10	40
Lead *	< 0.0010			< 0.010	0.5	10	50
Antimony *	< 0.0017			< 0.017	0.06	0.7	5
Selenium *	< 0.0040			< 0.040	0.1	0.5	7
Zinc *	0.0028			0.028	4	50	200
Chloride *	2.8			28	800	15000	25000
Fluoride*	0.18			1.8	10	150	500
Sulphate *	4.1			41	1000	20000	50000
TDS*	13			130	4000	60000	100000
Phenol Index (Monohydric Phenols) *	< 0.010			< 0.10	1	-	-
DOC	18.9			189	500	800	1000
Leach Test Information							
Stone Content (%)	< 0.1						
Sample Mass (kg)	0.8						
Dry Matter (%)	82						
Moisture (%)	18						
Results are expressed on a dry weight basis, after correction for moisture content where applicable.					*= UKAS accredited (liquid eluate analysis only)		
Stated limits are for guidance only and i2 cannot be held responsible for any discrepancies with current legislation					** = MCERTS accredited		

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes as defined by the Waste (England and Wales) Regulations 2011 (as amended) and EA Guidance WM3. This analysis is only applicable for landfill acceptance criteria (The Environmental Permitting (England and Wales) Regulations) and does not give any indication as to whether a waste may be hazardous or non-hazardous.

Where colour coding is used on this report, this is for guidance purposes only. This does not constitute a statement of conformity of pass or fail.

Application of uncertainty of measurement would provide a range within which the true result lies. An estimate of measurement uncertainty can be provided on request.



**Analytical Report Number : 25-003327**  
**Project / Site name: Grove**

\* These descriptions are only intended to act as a cross check if sample identities are questioned. The major constituent of the sample is intended to act with respect to MCERTS validation. The laboratory is accredited for sand, clay and loam (MCERTS) soil types. Data for unaccredited types of solid should be interpreted with care.

Stone content of a sample is calculated as the % weight of the stones not passing a 10 mm sieve. Results are not corrected for stone content.

Lab Sample Number	Sample Reference	Sample Number	Depth (m)	Sample Description *
433737	MSW106	None Supplied	0.4	Brown clay and loam with gravel and vegetation

**Analytical Report Number : 25-003327**

**Project / Site name: Grove**

**Water matrix abbreviations:**

**Surface Water (SW) Potable Water (PW) Ground Water (GW) Process Waters Heating/Cooling (PrW) DI Process Water (DI PrW)**

**Final Sewage Effluent (FSE) Landfill Leachate (LL)**

Analytical Test Name	Analytical Method Description	Analytical Method Reference	Method number	Wet / Dry Analysis	Accreditation Status
pH at 20°C in soil	Determination of pH in soil by addition of water followed by electrometric measurement	In-house method	L005B	W	MCERTS
Total organic carbon (Automated) in soil	Determination of organic matter in soil by oxidising with potassium dichromate followed by titration with iron (II) sulphate (Walkley Black Method)	In-house method	L009B	D	MCERTS
Moisture Content	Moisture content, determined gravimetrically (up to 30°C)	In-house method	L019B	W	NONE
Stones content of soil	Standard preparation for all samples unless otherwise detailed. Gravimetric determination of stone > 10 mm as % dry weight	In-house method based on British Standard Methods and MCERTS requirements.	L019B	D	NONE
PCB's By GC-MS in soil	Determination of PCB by extraction with hexane followed by GC-MS	In-house method based on USEPA 8082	L027B	D	MCERTS
Total dissolved solids 10:1 WAC	Determination of total dissolved solids in water by electrometric measurement	In-house method based on Examination of Water and Wastewater 20th Edition: Clesceri, Greenberg & Eaton	L031B	W	ISO 17025
Fluoride 10:1 WAC	Determination of fluoride in leachate by 1:1ratio with a buffer solution followed by Ion Selective Electrode	In-house method based on Use of Total Ionic Strength Adjustment Buffer for Electrode Determination	L033B	W	ISO 17025
Dissolved organic carbon 10:1 WAC	Determination of dissolved organic carbon in leachate by TOC/DOC NDIR Analyser	In-house method based on Examination of Water and Wastewater 20th Edition: Clesceri, Greenberg & Eaton	L037B	W	NONE
Metals in leachate by ICP-OES	Determination of metals in leachate by acidification followed by ICP-OES	In-house method based on MEWAM 2006 Methods for the Determination of Metals in Soil	L039B	W	ISO 17025
Sample Preparation		In-house method	L043B	W	NONE
Acid neutralisation capacity of soil	Determination of acid neutralisation capacity by addition of acid or alkali followed by electronic probe	In-house method based on Guidance an Sampling and Testing of Wastes to Meet Landfill Waste Acceptance	L046B	W	NONE
Loss on ignition of soil @ 450°C	Determination of loss on ignition in soil by gravimetrically with the sample being ignited in a muffle furnace	In-house method	L047-PL	D	MCERTS
Speciated PAHs and/or Semi-volatile organic compounds in soil	Determination of semi-volatile organic compounds (including PAH) in soil by extraction in dichloromethane and hexane followed by GC-MS	In-house method based on USEPA 8270	L064B	D	MCERTS
BTEX and/or Volatile organic compounds in soil	Determination of volatile organic compounds in soil by headspace GC-MS	In-house method based on USEPA 8260	L073B	W	MCERTS
Total petroleum hydrocarbons by GC-FID/GC-MS HS in soil	Determination of total petroleum hydrocarbons in soil by GC-FID/GC-MS HS	In-house method	L076B/L088-PL	D/W	NONE
Monohydric phenols 10:1 WAC	Determination of phenols in leachate by distillation followed by colorimetry	In-house method based on Examination of Water and Wastewater 20th Edition: Clesceri, Greenberg & Eaton	L080-PL	W	ISO 17025
Chloride 10:1 WAC	Determination of Chloride colorimetrically by discrete analyser	In-house based on MEWAM Method ISBN 0117516260	L082B	W	ISO 17025



Analytical Report Number : 25-003327  
Project / Site name: Grove

Water matrix abbreviations:  
Surface Water (SW) Potable Water (PW) Ground Water (GW) Process Waters Heating/Cooling (PrW) DI Process Water (DI PrW)  
Final Sewage Effluent (FSE) Landfill Leachate (LL)

Analytical Test Name	Analytical Method Description	Analytical Method Reference	Method number	Wet / Dry Analysis	Accreditation Status
----------------------	-------------------------------	-----------------------------	---------------	--------------------	----------------------

For method numbers ending in 'UK' or 'A' analysis have been carried out in our laboratory in the United Kingdom (Watford).  
For method numbers ending in 'F' analysis have been carried out in our laboratory in the United Kingdom (East Kilbride).  
For method numbers ending in 'PL' or 'B' analysis have been carried out in our laboratory in Poland.  
Soil analytical results are expressed on a dry weight basis. Where analysis is carried out on as-received the results obtained are multiplied by a moisture correction factor that is determined gravimetrically using the moisture content which is carried out at a maximum of 30oC.  
Unless otherwise indicated, site information, order number, project number, sampling date, time, sample reference and depth are provided by the client. The instructed on date indicates the date on which this information was provided to the laboratory.

Quality control parameter failure associated with individual result applies to calculated sum of individuals.  
The result for sum should be interpreted with caution

Site Name: <b>Stanton</b>										Accepted at site: Sampling period:			
Project Details										Number of tests			
Sample location										Mean			
Depth (m)										[mg kg <sup>-1</sup> ]			
Depth (m)										Standard deviation			
Depth (m)										Max			
Depth (m)										Min			
Depth (m)										Range			
Depth (m)										Coefficient of variation			
Depth (m)										Skewness			
Depth (m)										Kurtosis			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			
Depth (m)										Jarvis-Berry			

**APPENDIX 7**    ▪    Geotechnical Laboratory Certificates



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465867  
Hole No.: MWS101  
Sample Reference: Not Given  
Sample Description: Brown sandy CLAY

Depth Top [m]: 1.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
22.1	36	1.020	16	20	0.30	0.70	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt


Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test Results:

Laboratory Reference: 465868  
Hole No.: MWS102  
Sample Reference: Not Given  
Sample Description: Brown slightly gravelly sandy CLAY  
Sample Preparation: Tested after >0.425 mm removed by hand;  
Cone Type: 80g/30deg

Depth Top [m]: 2.50  
Depth Base [m]: Not Given  
Sample Type: D

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
21.7	40	1.039	19	21	0.14	0.86	97



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465869  
Hole No.: MWS103  
Sample Reference: Not Given  
Sample Description: Brown sandy CLAY

Depth Top [m]: 2.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
24.6	42	1.000	20	22	0.23	0.77	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465870  
Hole No.: MWS104  
Sample Reference: Not Given  
Sample Description: Brown sandy CLAY

Depth Top [m]: 2.00  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
22.5	37	1.000	18	19	0.26	0.74	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt


Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test Results:

Laboratory Reference: 465871  
Hole No.: MWS105  
Sample Reference: Not Given  
Sample Description: Brown slightly gravelly sandy CLAY  
Sample Preparation: Tested after >0.425 mm removed by hand;  
Cone Type: 80g/30deg

Depth Top [m]: 1.50  
Depth Base [m]: Not Given  
Sample Type: D

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
28.2	43	1.000	21	22	0.32	0.68	98



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L	Low
	M	Medium
	H	High
	V	Very high
	O	Organic
		append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465872  
Hole No.: MWS105  
Sample Reference: Not Given  
Sample Description: Greenish brown slightly sandy CLAY

Depth Top [m]: 3.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
20.0	47	1.058	21	26	-0.04	1.04	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L	Low
	M	Medium
	H	High
	V	Very high
	O	Organic
		append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465873  
Hole No.: MWS106  
Sample Reference: Not Given  
Sample Description: Brown slightly sandy CLAY

Depth Top [m]: 2.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
22.2	48	1.021	21	27	0.04	0.96	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465874  
Hole No.: MWS107  
Sample Reference: Not Given  
Sample Description: Yellowish brown slightly gravelly sandy CLAY

Depth Top [m]: 0.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested after >0.425 mm removed by hand;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
24.9	42	1.020	21	21	0.19	0.81	95



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L Low	50 to 70
	M Medium	exceeding 70
	H High	append to classification for organic material (eg ClHO)
	V Very high	
	O Organic	

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465875  
Hole No.: MWS108  
Sample Reference: Not Given  
Sample Description: Brownish grey slightly sandy CLAY

Depth Top [m]: 1.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
21.9	45	0.984	18	27	0.15	0.85	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L	Low
	M	Medium
	H	High
	V	Very high
	O	Organic
		append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 24/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465876  
Hole No.: MBH101  
Sample Reference: Not Given  
Sample Description: Brownish grey slightly sandy CLAY

Depth Top [m]: 0.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
29.5	48	1.058	20	28	0.36	0.64	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 24/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465877  
Hole No.: MBH101  
Sample Reference: Not Given  
Sample Description: Brown sandy CLAY

Depth Top [m]: 1.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
24.2	37	1.020	20	17	0.24	0.76	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 24/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465878  
Hole No.: MBH101  
Sample Reference: Not Given  
Sample Description: Brownish grey slightly gravelly very sandy CLAY

Depth Top [m]: 2.50  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested after >0.425 mm removed by hand;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
21.6	32	1.030	20	12	0.17	0.83	99



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L Low	50 to 70
	M Medium	exceeding 70
	H High	
	V Very high	
	O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465879  
Hole No.: MTP101  
Sample Reference: Not Given  
Sample Description: Yellowish brown sandy CLAY

Depth Top [m]: 1.00  
Depth Base [m]: Not Given  
Sample Type: B

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
26.9	40	1.020	21	19	0.32	0.68	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465881  
Hole No.: MTP101  
Sample Reference: Not Given  
Sample Description: Brownish grey silty SAND

Depth Top [m]: 2.90  
Depth Base [m]: Not Given  
Sample Type: B

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
26.4	31	1.030	NP	NP	N/A	N/A	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L	Low
	M	Medium
	H	High
	V	Very high
	O	Organic
		append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks: NP - non plastic.

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465883  
Hole No.: MTP103  
Sample Reference: Not Given  
Sample Description: Yellowish brown slightly gravelly sandy CLAY

Depth Top [m]: 1.00  
Depth Base [m]: Not Given  
Sample Type: B

Sample Preparation: Tested after washing to remove >0.425 mm;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
25.3	39	1.039	19	20	0.30	0.70	97



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L	Low
	M	Medium
	H	High
	V	Very high
	O	Organic
		append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465884  
Hole No.: MTP104  
Sample Reference: Not Given  
Sample Description: Greyish brown slightly sandy CLAY

Depth Top [m]: 1.20  
Depth Base [m]: Not Given  
Sample Type: B

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
24.3	53	1.020	20	33	0.12	0.88	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L	Low
	M	Medium
	H	High
	V	Very high
	O	Organic
		append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465885  
Hole No.: MTP105  
Sample Reference: Not Given  
Sample Description: Greyish brown sandy CLAY

Depth Top [m]: 1.30  
Depth Base [m]: Not Given  
Sample Type: B

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
22.5	44	1.058	20	24	0.13	0.88	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465886  
Hole No.: MTP105  
Sample Reference: Not Given  
Sample Description: Dark brown slightly gravelly very sandy silty CLAY

Depth Top [m]: 3.00  
Depth Base [m]: Not Given  
Sample Type: B

Sample Preparation: Tested after washing to remove >0.425 mm;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
17.4	34	0.984	22	12	-0.42	1.42	93



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

		Plasticity	Liquid Limit
Cl	Clay	L Low	below 35
Si	Silt	M Medium	35 to 50
		H High	50 to 70
		V Very high	exceeding 70
		O Organic	append to classification for organic material (eg CIHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## TEST CERTIFICATE

### DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


#### Test Results:

Laboratory Reference: 465887  
Hole No.: MTP106  
Sample Reference: Not Given  
Sample Description: Yellowish grey slightly sandy CLAY

Depth Top [m]: 2.40  
Depth Base [m]: Not Given  
Sample Type: B

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
28.1	49	1.039	20	29	0.28	0.72	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	below 35
Si	Silt	35 to 50
	L	Low
	M	Medium
	H	High
	V	Very high
	O	Organic
		append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF LIQUID AND PLASTIC LIMITS

Tested in Accordance with: BS EN ISO 17892-12:2018+A2:2022,  
cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022,  
cl 5.3, 6

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 24/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland


### Test Results:

Laboratory Reference: 465889  
Hole No.: MBH101  
Sample Reference: Not Given  
Sample Description: Greyish brown slightly sandy CLAY

Depth Top [m]: 9.00  
Depth Base [m]: Not Given  
Sample Type: D

Sample Preparation: Tested in natural condition;  
Cone Type: 80g/30deg

As Received Water Content [W] %	Corrected Liquid Limit [WL] %	Correlation Factor	Plastic Limit [Wp] %	Plasticity Index [Ip] %	Liquidity index [IL] % #	Consistency index [IC] % #	% Passing 425µm BS Test Sieve
25.5	59	1.036	25	34	0.03	0.97	100



Legend, based on BS EN ISO 14688 2:2018 Geotechnical investigation and testing – Identification and classification of soil

	Plasticity	Liquid Limit
Cl	Clay	
Si	Silt	
L	Low	below 35
M	Medium	35 to 50
H	High	50 to 70
V	Very high	exceeding 70
O	Organic	append to classification for organic material (eg ClHO)

Note: Water Content by BS EN 17892-1:2014+A1:2022, BS 1377-2:2022; Correlation Factor by Clayton C.R.I and Jukes A.W (1978); # Non accredited

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# SUMMARY REPORT

## SUMMARY OF CLASSIFICATION TEST RESULTS

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

Tested in Accordance with:

BS EN ISO 17892-12:2018+A2:2022, cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022, cl 5.3, 6. Correlation Factor by Clayton C.R.I and Jukes A.W (1978). W by BS EN ISO 17892-1:2014+A1:2022.

Client Reference: 22653H

Job Number: 25-009629-1

Date Sampled: 21/01 - 24/01/2025

Date Received: 04/02/2025

Date Tested: 04/03/2025

Sampled By: Client - Tim Stempt

4041

Client: Merebrook

Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ

Contact: Tim Stempt

Site Address: Grove

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test results

Laboratory Reference	Hole No.	Sample				Description	Remarks	W	Liquid & Plastic Limit							Density		
		Reference	Depth Top	Depth Base	Type				% Passing 425um	WL*	Correlation Factor	Wp	Ip	Cone type	Sample Preparation	bulk	dry	PD
465867	MWS101	Not Given	1.50	Not Given	D	Brown sandy CLAY	Atterberg 1 Point	22.1	100	36	1.020	16	20	80g/30 deg	N			
465868	MWS102	Not Given	2.50	Not Given	D	Brown slightly gravelly sandy CLAY	Atterberg 1 Point	21.7	97	40	1.039	19	21	80g/30 deg	R			
465869	MWS103	Not Given	2.50	Not Given	D	Brown sandy CLAY	Atterberg 1 Point	24.6	100	42	1.000	20	22	80g/30 deg	N			
465870	MWS104	Not Given	2.00	Not Given	D	Brown sandy CLAY	Atterberg 1 Point	22.5	100	37	1.000	18	19	80g/30 deg	N			
465871	MWS105	Not Given	1.50	Not Given	D	Brown slightly gravelly sandy CLAY	Atterberg 1 Point	28.2	98	43	1.000	21	22	80g/30 deg	R			
465872	MWS105	Not Given	3.50	Not Given	D	Greenish brown slightly sandy CLAY	Atterberg 1 Point	20.0	100	47	1.058	21	26	80g/30 deg	N			
465873	MWS106	Not Given	2.50	Not Given	D	Brown slightly sandy CLAY	Atterberg 1 Point	22.2	100	48	1.021	21	27	80g/30 deg	N			
465874	MWS107	Not Given	0.50	Not Given	D	Yellowish brown slightly gravelly sandy CLAY	Atterberg 1 Point	24.9	95	42	1.020	21	21	80g/30 deg	R			
465875	MWS108	Not Given	1.50	Not Given	D	Brownish grey slightly sandy CLAY	Atterberg 1 Point	21.9	100	45	0.984	18	27	80g/30 deg	N			
465876	MBH101	Not Given	0.50	Not Given	D	Brownish grey slightly sandy CLAY	Atterberg 1 Point	29.5	100	48	1.058	20	28	80g/30 deg	N			

Note: # Non accredited; NP - Non plastic; N - Tested in natural condition, R - Tested after >0.425mm removed by hand, WR - Tested after washing to remove >425mm; \* - One point liquid limit corrected as per the report Correlation Factor by Clayton C.R.I and Jukes A.W (1978)

Comments:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



## SUMMARY REPORT

### SUMMARY OF CLASSIFICATION TEST RESULTS

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

Tested in Accordance with:

BS EN ISO 17892-12:2018+A2:2022, cl 5.3.14, 5.5, Fall Cone Method, 1 Pt Test, BS 1377-2:2022, cl 5.3, 6. Correlation Factor by Clayton C.R.I and Jukes A.W (1978). W by BS EN ISO 17892-1:2014+A1:2022.

Client Reference: 22653H

Job Number: 25-009629-1

Date Sampled: 23/01 - 24/01/2025

Date Received: 04/02/2025

Date Tested: 04/03/2025

Sampled By: Client - Tim Stempt

4041

Client: Merebrook

Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ

Contact: Tim Stempt

Site Address: Grove

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test results

Laboratory Reference	Hole No.	Sample				Description	Remarks	W	Liquid & Plastic Limit							Density		
		Reference	Depth Top m	Depth Base m	Type				% Passing 425um %	WL* %	Correlation Factor	Wp %	Ip %	Cone type	Sample Preparation	bulk Mg/m3	dry Mg/m3	PD Mg/m3
465877	MBH101	Not Given	1.50	Not Given	D	Brown sandy CLAY	Atterberg 1 Point	24.2	100	37	1.020	20	17	80g/30 deg	N			
465878	MBH101	Not Given	2.50	Not Given	D	Brownish grey slightly gravelly very sandy CLAY	Atterberg 1 Point	21.6	99	32	1.030	20	12	80g/30 deg	R			
465879	MTP101	Not Given	1.00	Not Given	B	Yellowish brown sandy CLAY	Atterberg 1 Point	26.9	100	40	1.020	21	19	80g/30 deg	N			
465881	MTP101	Not Given	2.90	Not Given	B	Brownish grey silty SAND	Atterberg 1 Point	26.4	100	31	1.030	NP	NP	80g/30 deg	N			
465883	MTP103	Not Given	1.00	Not Given	B	Yellowish brown slightly gravelly sandy CLAY	Atterberg 1 Point	25.3	97	39	1.039	19	20	80g/30 deg	WR			
465884	MTP104	Not Given	1.20	Not Given	B	Greyish brown slightly sandy CLAY	Atterberg 1 Point	24.3	100	53	1.020	20	33	80g/30 deg	N			
465885	MTP105	Not Given	1.30	Not Given	B	Greyish brown sandy CLAY	Atterberg 1 Point	22.5	100	44	1.058	20	24	80g/30 deg	N			
465886	MTP105	Not Given	3.00	Not Given	B	Dark brown slightly gravelly very sandy silty CLAY	Atterberg 1 Point	17.4	93	34	0.984	22	12	80g/30 deg	WR			
465887	MTP106	Not Given	2.40	Not Given	B	Yellowish grey slightly sandy CLAY	Atterberg 1 Point	28.1	100	49	1.039	20	29	80g/30 deg	N			
465889	MBH101	Not Given	9.00	Not Given	D	Greyish brown slightly sandy CLAY	Atterberg 1 Point	25.5	100	59	1.036	25	34	80g/30 deg	N			

Note: # Non accredited; NP - Non plastic; N - Tested in natural condition, R - Tested after >0.425mm removed by hand, WR - Tested after washing to remove >425mm; \* - One point liquid limit corrected as per the report Correlation Factor by Clayton C.R.I and Jukes A.W (1978)

Comments:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# SUMMARY REPORT

## DETERMINATION OF WATER CONTENT

Tested in Accordance with: BS EN ISO 17892-1:2014+A1:2022, BS 1377-2: 2022, clause 4.1

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

**4041**  
Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 21/01 - 24/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test results

Laboratory Reference	Hole No.	Sample				Description	Remarks	WC											
		Reference	Depth Top m	Depth Base m	Type														
465867	MWS101	Not Given	1.50	Not Given	D	Brown sandy CLAY		22.1											
465868	MWS102	Not Given	2.50	Not Given	D	Brown slightly gravelly sandy CLAY		21.7											
465869	MWS103	Not Given	2.50	Not Given	D	Brown sandy CLAY		24.6											
465870	MWS104	Not Given	2.00	Not Given	D	Brown sandy CLAY		22.5											
465871	MWS105	Not Given	1.50	Not Given	D	Brown slightly gravelly sandy CLAY		28.2											
465872	MWS105	Not Given	3.50	Not Given	D	Greenish brown slightly sandy CLAY		20.0											
465873	MWS106	Not Given	2.50	Not Given	D	Brown slightly sandy CLAY		22.2											
465874	MWS107	Not Given	0.50	Not Given	D	Yellowish brown slightly gravelly sandy CLAY		24.9											
465875	MWS108	Not Given	1.50	Not Given	D	Brownish grey slightly sandy CLAY		21.9											
465876	MBH101	Not Given	0.50	Not Given	D	Brownish grey slightly sandy CLAY		29.5											

Comments:

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd



## SUMMARY REPORT

### DETERMINATION OF WATER CONTENT

Tested in Accordance with: BS EN ISO 17892-1:2014+A1:2022, BS 1377-2: 2022, clause 4.1

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01 - 24/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test results

Laboratory Reference	Hole No.	Sample				Description	Remarks	WC											
		Reference	Depth Top m	Depth Base m	Type														
465877	MBH101	Not Given	1.50	Not Given	D	Brown sandy CLAY		24.2											
465878	MBH101	Not Given	2.50	Not Given	D	Brownish grey slightly gravelly very sandy CLAY		21.6											
465879	MTP101	Not Given	1.00	Not Given	B	Yellowish brown sandy CLAY		26.9											
465881	MTP101	Not Given	2.90	Not Given	B	Brownish grey silty SAND		26.4											
465883	MTP103	Not Given	1.00	Not Given	B	Yellowish brown slightly gravelly sandy CLAY		25.3											
465884	MTP104	Not Given	1.20	Not Given	B	Greyish brown slightly sandy CLAY		24.3											
465885	MTP105	Not Given	1.30	Not Given	B	Greyish brown sandy CLAY		22.5											
465886	MTP105	Not Given	3.00	Not Given	B	Dark brown slightly gravelly very sandy silty CLAY		17.4											
465887	MTP106	Not Given	2.40	Not Given	B	Yellowish grey slightly sandy CLAY		28.1											
465889	MBH101	Not Given	9.00	Not Given	D	Greyish brown slightly sandy CLAY		25.5											

Comments:

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd



# TEST CERTIFICATE

## DETERMINATION OF PARTICLE SIZE DISTRIBUTION

Tested in Accordance with: BS EN ISO 17892-4:2016,  
BS 1377-2:2022 cl. 10

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove


Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test Results:

Laboratory Reference: 465880  
Hole No.: MTP101  
Sample Reference: Not Given  
Sample Description: Yellowish brown clayey SAND  
Sample Preparation: Sample was quartered, oven dried at 107.7 °C and broken down by hand.

Depth Top [m]: 2.00  
Depth Base [m]: Not Given  
Sample Type: B



Sieving		Sedimentation	
Particle Size mm	% Passing	Particle Size mm	% Passing
500	100	0.0500	12
300	100	0.0359	11
150	100	0.0255	11
125	100	0.0182	10
90	100	0.0096	9
75	100	0.0048	8
63	100	0.0034	7
50	100	0.0014	6
37.5	100		
28	100		
20	100		
14	100		
10	100		
6.3	100		
5	100		
3.35	100		
2	100		
1.18	100		
0.6	99	Particle density (assumed) 2.65 Mg/m3	
0.425	98		
0.3	98		
0.212	98		
0.15	94		
0.063	12		

Sample Proportions	% dry mass
Very coarse	0
Gravel	0
Sand	88
Silt	6
Clay	6

Grading Analysis	
D100	mm 3.35
D60	mm 0.104
D30	mm 0.076
D10	mm 0.0158
Uniformity Coefficient	6.6
Curvature Coefficient	3.5

Uniformity and Curvature Coefficient calculated in accordance with BS EN ISO 14688-2:2018

Note: Tested in Accordance with ISO 17892 -4, by sieving and hydrometer sedimentation

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF PARTICLE SIZE DISTRIBUTION

Tested in Accordance with: BS EN ISO 17892-4:2016,  
BS 1377-2:2022 cl. 10

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove


Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test Results:

Laboratory Reference: 465882  
Hole No.: MTP102  
Sample Reference: Not Given  
Sample Description: Brown clayey SAND  
Sample Preparation: Sample was quartered, oven dried at 107.7 °C and broken down by hand.

Depth Top [m]: 2.80  
Depth Base [m]: Not Given  
Sample Type: B



Sieving		Sedimentation	
Particle Size mm	% Passing	Particle Size mm	% Passing
500	100	0.0500	16
300	100	0.0356	16
150	100	0.0255	14
125	100	0.0181	14
90	100	0.0095	12
75	100	0.0048	10
63	100	0.0035	9
50	100	0.0014	6
37.5	100		
28	100		
20	100		
14	100		
10	100		
6.3	100		
5	100		
3.35	100		
2	100		
1.18	100		
0.6	98	Particle density (assumed) 2.65 Mg/m3	
0.425	97		
0.3	97		
0.212	93		
0.15	39		
0.063	17		

Sample Proportions	% dry mass
Very coarse	0
Gravel	0
Sand	83
Silt	9
Clay	8

Grading Analysis		
D100	mm	3.35
D60	mm	0.172
D30	mm	0.106
D10	mm	0.00435
Uniformity Coefficient		39
Curvature Coefficient		15

Uniformity and Curvature Coefficient calculated in accordance with BS EN ISO 14688-2:2018

Note: Tested in Accordance with ISO 17892 -4, by sieving and hydrometer sedimentation

Remarks:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# TEST CERTIFICATE

## DETERMINATION OF PARTICLE SIZE DISTRIBUTION

Tested in Accordance with: BS EN ISO 17892-4:2016,  
BS 1377-2:2022 cl. 10

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041

Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove


Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 23/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test Results:

Laboratory Reference: 465888  
Hole No.: MTP106  
Sample Reference: Not Given  
Sample Description: Yellowish brown very clayey SAND  
Sample Preparation: Sample was quartered, oven dried at 107.7 °C and broken down by hand.

Depth Top [m]: 3.40  
Depth Base [m]: Not Given  
Sample Type: B



Sieving		Sedimentation	
Particle Size mm	% Passing	Particle Size mm	% Passing
500	100	0.0427	22
300	100	0.0304	21
150	100	0.0218	20
125	100	0.0156	20
90	100	0.0084	17
75	100	0.0043	15
63	100	0.0031	14
50	100	0.0013	12
37.5	100		
28	100		
20	100		
14	100		
10	100		
6.3	100		
5	100		
3.35	100		
2	100		
1.18	100		
0.6	99	Particle density (assumed) 2.65 Mg/m3	
0.425	99		
0.3	98		
0.212	97		
0.15	58		
0.063	23		

Sample Proportions	% dry mass
Very coarse	0
Gravel	0
Sand	77
Silt	10
Clay	13

Grading Analysis	
D100	mm 3.35
D60	mm 0.153
D30	mm 0.0755
D10	mm
Uniformity Coefficient	
Curvature Coefficient	

Uniformity and Curvature Coefficient calculated in accordance with BS EN ISO 14688-2:2018

Note: Tested in Accordance with ISO 17892 -4, by sieving and hydrometer sedimentation

Remarks:

Signed:

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.



# SUMMARY REPORT

## DETERMINATION OF POINT LOAD STRENGTH

Tested in Accordance with: ISRM: 2007, pages 125-132

i2 Analytical Ltd  
Unit 8 Harrowden Road  
Brackmills Industrial Estate  
Northampton NN4 7EB



Environmental Science

4041  
Client: Merebrook  
Client Address: First Floor, 1 Leonard Place,  
Westerham Road, Keston,  
BR2 6HQ  
Contact: Tim Stempt  
Site Address: Grove

Client Reference: 22653H  
Job Number: 25-009629-1  
Date Sampled: 24/01/2025  
Date Received: 04/02/2025  
Date Tested: 04/03/2025  
Sampled By: Client - Tim Stempt

Testing carried out at i2 Analytical Limited, ul. Pionierow, 41-711 Ruda Slaska, Poland

### Test results

Laboratory Reference	Hole No.	Sample				Description	Remarks (including water content if measured)	Specimen Reference	Test Type see ISRM		Failure Valid (Y/N)	Dimensions				Force P	Equivalent diameter, De	Point Load Strength Index	
		Reference	Depth Top	Depth Base	Type				Type (D, A, I, B)	Direction (L, P or U)		Lne	W	Dps	Dps'			Is	Is(50)
			m	m															
465890	MBH101	Not Given	14.00	14.40	C	Grey LIMESTONE	WC = 1.4%	1	D	U	YES	217.1	88.9	89.0	84.0	16.7	86.4	2.24	2.86
465891	MBH101	Not Given	15.20	15.50	C	Grey LIMESTONE	WC = 3.4%	1	D	U	YES	141.1	88.4	88.0	85.0	17.3	86.7	2.30	2.94
465892	MBH101	Not Given	17.80	18.20	U	Grey LIMESTONE	WC = 1.8%	1	D	U	YES	186.2	88.9	89.0	67.0	29.7	77.2	4.98	6.06

Note: # non accredited; Test Type: D - Diametral, A - Axial, I - Irregular Lump, B - Block; Direction: L - parallel to planes of weakness, P - perpendicular to planes of weakness, U - unknown or random;  
Dimensions: Dps - Distance between platens ( platen separation ), Dps' - at failure ( see ISRM note 6), Lne - Length from platens to nearest free end W - Width of shortest dimension perpendicular to load, P;  
Detailed legend for test and dimensions, based on ISRM, is shown above; Size factor, F = (De/50)0.45 for all tests

Equipment No.: i2 4341 Calibration Date: 15/03/2024 - 15/03/2025

### Comments:

Signed:

Katarzyna Koziel

Katarzyna Koziel  
Geotechnical Reporting Team Leader  
for and on behalf of i2 Analytical Ltd

Opinions and interpretations expressed herein are outside of the scope of the UKAS Accreditation. This report may not be reproduced other than in full without the prior written approval of the issuing laboratory. The results included within the report relate only to the sample(s) submitted for testing.

Merebrook  
First Floor  
1 Leonard Place  
Westerham Road  
Keston  
BR2 6HQ

t: 01689 889980

e: ttempt@idom.com  
coliveira@idom.com

i2 Analytical Ltd.  
7 Woodshots Meadow,  
Croxley Green  
Business Park,  
Watford,  
Herts,  
WD18 8YS

t: 01923 225404  
f: 01923 237404  
e: reception@i2analytical.com

## **Analytical Report Number : 25-009630**

<b>Project / Site name:</b>	Grove	<b>Samples received on:</b>	04/02/2025
<b>Your job number:</b>	22653H	<b>Samples instructed on/ Analysis started on:</b>	27/02/2025
<b>Your order number:</b>	25-2-FDO-LABS	<b>Analysis completed by:</b>	05/03/2025
<b>Report Issue Number:</b>	1	<b>Report issued on:</b>	05/03/2025
<b>Samples Analysed:</b>	10 soil samples		

  
**Signed:**

Rachel Chappell  
Key Account Manager  
**For & on behalf of i2 Analytical Ltd.**

Standard Geotechnical, Asbestos and Chemical Testing Laboratory located at: ul. Pionierów 39, 41-711 Ruda Śląska, Poland.

Accredited tests are defined within the report, opinions and interpretations expressed herein are outside the scope of accreditation.

Standard sample disposal times, unless otherwise agreed with the laboratory, are :

soils	- 4 weeks from reporting
leachates	- 2 weeks from reporting
waters	- 2 weeks from reporting
asbestos	- 6 months from reporting
air	- once the analysis is complete

Excel copies of reports are only valid when accompanied by this PDF certificate.

Retention period for records and reports is minimum 6 years from the date of issue of the final report.  
Some records may be kept for longer according to other legal/best practice requirements.

Any assessments of compliance with specifications are based on actual analytical results with no contribution from uncertainty of measurement.  
Application of uncertainty of measurement would provide a range within which the true result lies.  
An estimate of measurement uncertainty can be provided on request.

Analytical Report Number: 25-009630  
Project / Site name: Grove  
Your Order No: 25-2-FDO-LABS

Lab Sample Number	465893	465894	465895	465896	465897
Sample Reference	MWS101	MWS102	MWS103	MWS103	MWS106
Sample Number	None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Water Matrix	N/A	N/A	N/A	N/A	N/A
Depth (m)	2.50	0.50	1.50	3.50	0.50
Date Sampled	21/01/2025	21/01/2025	21/01/2025	21/01/2025	21/01/2025
Time Taken	None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status		

Stone Content	%	0.1	NONE	< 0.1	< 0.1	< 0.1	< 0.1	< 0.1
Moisture Content	%	0.01	NONE	18	19	20	21	19
Total mass of sample received	kg	0.1	NONE	0.5	0.6	0.7	0.8	0.7

#### General Inorganics

pH (L099)	pH Units	N/A	MCERTS	7.9	8.2	8.5	6.1	6.3
Total Sulphate as SO <sub>4</sub>	%	0.005	MCERTS	0.011	0.027	0.011	0.094	0.011
Water Soluble Sulphate as SO <sub>4</sub> 16hr extraction (2:1)	mg/kg	2.5	MCERTS	8.3	13	13	33	31
Water Soluble SO <sub>4</sub> 16hr extraction (2:1 Leachate Equivalent)	mg/l	1.25	MCERTS	4.17	6.52	6.64	16.6	15.3
Water Soluble Chloride (2:1) (leachate equivalent)	mg/l	0.5	MCERTS	4.2	5.3	3.9	1.4	1.5
Total Sulphur	mg/kg	50	MCERTS	< 50	77	< 50	310	55
Total Sulphur	%	0.005	MCERTS	< 0.005	0.008	< 0.005	0.031	0.005
Water Soluble Nitrate (2:1) as N (leachate equivalent)	mg/l	2	NONE	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0

#### Heavy Metals / Metalloids

Magnesium (leachate equivalent)	mg/l	2.5	NONE	3	8.1	11	4.7	4.3
---------------------------------	------	-----	------	---	-----	----	-----	-----

U/S = Unsuitable Sample I/S = Insufficient Sample ND = Not detected

Analytical Report Number: 25-009630  
Project / Site name: Grove  
Your Order No: 25-2-FDO-LABS

Lab Sample Number	465898	465899	465900	465901	465902
Sample Reference	MBH101	MTP103	MTP106	MBH101	MBH101
Sample Number	None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Water Matrix	N/A	N/A	N/A	N/A	N/A
Depth (m)	4.00	2.00	1.20	10.00	17.50-18.50
Date Sampled	24/01/2025	23/01/2025	23/01/2025	24/01/2025	24/01/2025
Time Taken	None Supplied	None Supplied	None Supplied	None Supplied	None Supplied
Analytical Parameter (Soil Analysis)	Units	Test Limit of detection	Test Accreditation Status		

Stone Content	%	0.1	NONE	< 0.1	< 0.1	< 0.1	< 0.1	88.4
Moisture Content	%	0.01	NONE	22	16	18	14	5.8
Total mass of sample received	kg	0.1	NONE	0.6	0.8	0.6	0.7	0.8

#### General Inorganics

pH (L099)	pH Units	N/A	MCERTS	5.4	6.6	7.6	7.6	8.3
Total Sulphate as SO <sub>4</sub>	%	0.005	MCERTS	0.052	0.07	0.008	0.022	0.091
Water Soluble Sulphate as SO <sub>4</sub> 16hr extraction (2:1)	mg/kg	2.5	MCERTS	450	61	28	200	320
Water Soluble SO <sub>4</sub> 16hr extraction (2:1 Leachate Equivalent)	mg/l	1.25	MCERTS	227	30.4	14.2	102	160
Water Soluble Chloride (2:1) (leachate equivalent)	mg/l	0.5	MCERTS	4.1	3	0.8	3.9	4
Total Sulphur	mg/kg	50	MCERTS	290	1600	78	3700	3000
Total Sulphur	%	0.005	MCERTS	0.029	0.16	0.008	0.373	0.297
Water Soluble Nitrate (2:1) as N (leachate equivalent)	mg/l	2	NONE	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0

#### Heavy Metals / Metalloids

Magnesium (leachate equivalent)	mg/l	2.5	NONE	17	5.8	5.7	11	8
---------------------------------	------	-----	------	----	-----	-----	----	---

U/S = Unsuitable Sample I/S = Insufficient Sample ND = Not detected

**Analytical Report Number : 25-009630**

**Project / Site name: Grove**

\* These descriptions are only intended to act as a cross check if sample identities are questioned. The major constituent of the sample is intended to act with respect to MCERTS validation. The laboratory is accredited for sand, clay and loam (MCERTS) soil types. Data for unaccredited types of solid should be interpreted with care.

Stone content of a sample is calculated as the % weight of the stones not passing a 10 mm sieve. Results are not corrected for stone content.

Lab Sample Number	Sample Reference	Sample Number	Depth (m)	Sample Description *
465893	MWS101	None Supplied	2.5	Brown clay
465894	MWS102	None Supplied	0.5	Brown clay
465895	MWS103	None Supplied	1.5	Brown clay
465896	MWS103	None Supplied	3.5	Brown clay and sand
465897	MWS106	None Supplied	0.5	Brown clay
465898	MBH101	None Supplied	4	Brown sand with gravel
465899	MTP103	None Supplied	2	Brown clay with vegetation
465900	MTP106	None Supplied	1.2	Brown clay
465901	MBH101	None Supplied	10	Brown clay and sand
465902	MBH101	None Supplied	17.50-18.50	Non Soil. <sup>9</sup>

**Analytical Report Number : 25-009630**

**Project / Site name: Grove**

**Water matrix abbreviations:**

**Surface Water (SW) Potable Water (PW) Ground Water (GW) Process Waters Heating/Cooling (PrW) DI Process Water (DI PrW)**

**Final Sewage Effluent (FSE) Landfill Leachate (LL)**

Analytical Test Name	Analytical Method Description	Analytical Method Reference	Method number	Wet / Dry Analysis	Accreditation Status
Moisture Content	Moisture content, determined gravimetrically (up to 30°C)	In-house method	L019B	W	NONE
Stones content of soil	Standard preparation for all samples unless otherwise detailed. Gravimetric determination of stone > 10 mm as % dry weight	In-house method based on British Standard Methods and MCERTS requirements.	L019B	D	NONE
Magnesium, water soluble, in soil	Determination of water soluble magnesium by extraction with water followed by ICP-OES	In-house method based on TRL 447	L038B	D	NONE
Total sulphate (as SO <sub>4</sub> in soil)	Determination of total sulphate in soil by extraction with 10% HCl followed by ICP-OES	In-house method	L038B	D	MCERTS
Sulphate, water soluble, in soil (16hr extraction)	Sulphate, water soluble, in soil (16hr extraction)	In-house method	L038B	D	MCERTS
Total Sulphur in soil	Determination of total sulphur in soil by extraction with aqua-regia, potassium bromide/bromate followed by ICP-OES	In-house method	L038B	D	MCERTS
Water Soluble Nitrate (2:1) as N in soil	Determination of nitrate by reaction with sodium salicylate and colorimetry	In-house method based on Examination of Water and Wastewater & Polish Standard Method PN-82/C-04579.08, 2:1 extraction	L078-PL	W	NONE
Chloride, water soluble, in soil	Determination of Chloride colorimetrically by discrete analyser	In-house method	L082B	D	MCERTS
pH in soil (automated)	Determination of pH in soil by addition of water followed by automated electrometric measurement	In-house method	L099-PL	D	MCERTS

**For method numbers ending in 'UK' or 'A' analysis have been carried out in our laboratory in the United Kingdom (Watford).**

**For method numbers ending in 'F' analysis have been carried out in our laboratory in the United Kingdom (East Kilbride).**

**For method numbers ending in 'PL' or 'B' analysis have been carried out in our laboratory in Poland.**

**Soil analytical results are expressed on a dry weight basis. Where analysis is carried out on as-received the results obtained are multiplied by a moisture correction factor that is determined gravimetrically using the moisture content which is carried out at a maximum of 30°C.**

**Unless otherwise indicated, site information, order number, project number, sampling date, time, sample reference and depth are provided by the client. The instructed on date indicates the date on which this information was provided to the laboratory.**

Quality control parameter failure associated with individual result applies to calculated sum of individuals.

The result for sum should be interpreted with caution

\*g - Unaccredited sample matrix.

Analytical Report Number : 25-009630

Project / Site name: Grove

This deviation report indicates the sample and test deviations that apply to the samples submitted for analysis. Please note that the associated result(s) may be unreliable and should be interpreted with care.

Key: a - No sampling date b - Incorrect container c - Holding time d - Headspace e - Temperature

Sample ID	Other ID	Sample Type	Lab Sample Number	Sample Deviation	Test Name	Test Ref	Test Deviation
MBH101	N/A	S	465898	c	Chloride, water soluble, in soil	L082B	c
MBH101	N/A	S	465898	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MBH101	N/A	S	465898	c	Total Sulphur in soil	L038B	c
MBH101	N/A	S	465898	c	Total sulphate (as SO4 in soil)	L038B	c
MBH101	N/A	S	465898	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MBH101	N/A	S	465898	c	pH in soil (automated)	L099-PL	c
MBH101	N/A	S	465901	c	Chloride, water soluble, in soil	L082B	c
MBH101	N/A	S	465901	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MBH101	N/A	S	465901	c	Total Sulphur in soil	L038B	c
MBH101	N/A	S	465901	c	Total sulphate (as SO4 in soil)	L038B	c
MBH101	N/A	S	465901	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MBH101	N/A	S	465901	c	pH in soil (automated)	L099-PL	c
MBH101	N/A	S	465902	c	Chloride, water soluble, in soil	L082B	c
MBH101	N/A	S	465902	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MBH101	N/A	S	465902	c	Total Sulphur in soil	L038B	c
MBH101	N/A	S	465902	c	Total sulphate (as SO4 in soil)	L038B	c
MBH101	N/A	S	465902	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MBH101	N/A	S	465902	c	pH in soil (automated)	L099-PL	c
MTP103	N/A	S	465899	c	Chloride, water soluble, in soil	L082B	c
MTP103	N/A	S	465899	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MTP103	N/A	S	465899	c	Total Sulphur in soil	L038B	c
MTP103	N/A	S	465899	c	Total sulphate (as SO4 in soil)	L038B	c
MTP103	N/A	S	465899	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MTP103	N/A	S	465899	c	pH in soil (automated)	L099-PL	c
MTP106	N/A	S	465900	c	Chloride, water soluble, in soil	L082B	c
MTP106	N/A	S	465900	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MTP106	N/A	S	465900	c	Total Sulphur in soil	L038B	c
MTP106	N/A	S	465900	c	Total sulphate (as SO4 in soil)	L038B	c
MTP106	N/A	S	465900	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MTP106	N/A	S	465900	c	pH in soil (automated)	L099-PL	c
MWS101	N/A	S	465893	c	Chloride, water soluble, in soil	L082B	c
MWS101	N/A	S	465893	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MWS101	N/A	S	465893	c	Total Sulphur in soil	L038B	c
MWS101	N/A	S	465893	c	Total sulphate (as SO4 in soil)	L038B	c
MWS101	N/A	S	465893	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MWS101	N/A	S	465893	c	pH in soil (automated)	L099-PL	c
MWS102	N/A	S	465894	c	Chloride, water soluble, in soil	L082B	c
MWS102	N/A	S	465894	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MWS102	N/A	S	465894	c	Total Sulphur in soil	L038B	c
MWS102	N/A	S	465894	c	Total sulphate (as SO4 in soil)	L038B	c
MWS102	N/A	S	465894	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MWS102	N/A	S	465894	c	pH in soil (automated)	L099-PL	c
MWS103	N/A	S	465895	c	Chloride, water soluble, in soil	L082B	c
MWS103	N/A	S	465895	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MWS103	N/A	S	465895	c	Total Sulphur in soil	L038B	c
MWS103	N/A	S	465895	c	Total sulphate (as SO4 in soil)	L038B	c
MWS103	N/A	S	465895	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MWS103	N/A	S	465895	c	pH in soil (automated)	L099-PL	c
MWS103	N/A	S	465896	c	Chloride, water soluble, in soil	L082B	c
MWS103	N/A	S	465896	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MWS103	N/A	S	465896	c	Total Sulphur in soil	L038B	c
MWS103	N/A	S	465896	c	Total sulphate (as SO4 in soil)	L038B	c
MWS103	N/A	S	465896	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MWS103	N/A	S	465896	c	pH in soil (automated)	L099-PL	c
MWS106	N/A	S	465897	c	Chloride, water soluble, in soil	L082B	c
MWS106	N/A	S	465897	c	Sulphate, water soluble, in soil (16hr extraction)	L038B	c
MWS106	N/A	S	465897	c	Total Sulphur in soil	L038B	c
MWS106	N/A	S	465897	c	Total sulphate (as SO4 in soil)	L038B	c

**Analytical Report Number : 25-009630**

**Project / Site name: Grove**

This deviation report indicates the sample and test deviations that apply to the samples submitted for analysis. Please note that the associated result(s) may be unreliable and should be interpreted with care.

Key: a - No sampling date b - Incorrect container c - Holding time d - Headspace e - Temperature

Sample ID	Other ID	Sample Type	Lab Sample Number	Sample Deviation	Test Name	Test Ref	Test Deviation
MWS106	N/A	S	465897	c	Water Soluble Nitrate (2:1) as N in soil	L078-PL	c
MWS106	N/A	S	465897	c	pH in soil (automated)	L099-PL	c

**APPENDIX 8**

- Groundwater Chemistry
- Laboratory Analysis Certificates

Merebrook  
First Floor  
1 Leonard Place  
Westerham Road  
Keston  
BR2 6HQ

**t:** 01689 889980

**e:** coliveira@idom.com  
mbaylis@idom.com

i2 Analytical Ltd.  
7 Woodshots Meadow,  
Croxley Green  
Business Park,  
Watford,  
Herts,  
WD18 8YS

**t:** 01923 225404

**f:** 01923 237404

**e:** reception@i2analytical.com

## **Analytical Report Number : 25-007184**

<b>Project / Site name:</b>	Grove House, Sellindge	<b>Samples received on:</b>	14/02/2025
<b>Your job number:</b>	22653H	<b>Samples instructed on/ Analysis started on:</b>	14/02/2025
<b>Your order number:</b>	25-2-FDO-LABS	<b>Analysis completed by:</b>	20/02/2025
<b>Report Issue Number:</b>	1	<b>Report issued on:</b>	20/02/2025
<b>Samples Analysed:</b>	3 water samples		

**Signed:** 

Eric Bomfim Crociquia  
Customer Service Administrator  
**For & on behalf of i2 Analytical Ltd.**

Standard Geotechnical, Asbestos and Chemical Testing Laboratory located at: ul. Pionierów 39, 41-711 Ruda Śląska, Poland.

Accredited tests are defined within the report, opinions and interpretations expressed herein are outside the scope of accreditation.

Standard sample disposal times, unless otherwise agreed with the laboratory, are :

soils - 4 weeks from reporting  
leachates - 2 weeks from reporting  
waters - 2 weeks from reporting  
asbestos - 6 months from reporting  
air - once the analysis is complete

Excel copies of reports are only valid when accompanied by this PDF certificate.

Retention period for records and reports is minimum 6 years from the date of issue of the final report.  
Some records may be kept for longer according to other legal/best practice requirements.

Any assessments of compliance with specifications are based on actual analytical results with no contribution from uncertainty of measurement.  
Application of uncertainty of measurement would provide a range within which the true result lies.  
An estimate of measurement uncertainty can be provided on request.

Analytical Report Number: 25-007184  
Project / Site name: Grove House, Sellindge

Your Order No: 25-2-FDO-LABS

Lab Sample Number	453856	453857	453858
Sample Reference	MWS101	MWS104	MWS106
Sample Number	None Supplied	None Supplied	None Supplied
Water Matrix	Other water	Other water	Other water
Depth (m)	None Supplied	None Supplied	None Supplied
Date Sampled	13/02/2025	13/02/2025	13/02/2025
Time Taken	None Supplied	None Supplied	None Supplied
Analytical Parameter (Water Analysis)	Units	Test Limit of detection	Test Accreditation Status

#### General Inorganics

pH (L099)	pH Units	N/A	NONE	7	7.2	7.1
Total Cyanide	µg/l	10	NONE	< 10	< 10	< 10
Sulphate as SO <sub>4</sub>	µg/l	45	NONE	6050	5970	47500
Sulphide	µg/l	5	NONE	< 5.0	< 5.0	< 5.0
Dissolved Organic Carbon (DOC)	mg/l	0.1	NONE	2.41	2.04	3.3

#### Total Phenols

Total Phenols (monohydric)	µg/l	10	NONE	< 10	< 10	< 10
----------------------------	------	----	------	------	------	------

#### Speciated PAHs

Naphthalene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Acenaphthylene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Acenaphthene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Fluorene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Phenanthrene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Anthracene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Fluoranthene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Pyrene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Benzo(a)anthracene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Chrysene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Benzo(b)fluoranthene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Benzo(k)fluoranthene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Benzo(a)pyrene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Indeno(1,2,3-cd)pyrene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Dibenz(a,h)anthracene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01
Benzo(ghi)perylene	µg/l	0.01	NONE	< 0.01	< 0.01	< 0.01

#### Total PAH

Total EPA-16 PAHs	µg/l	0.16	NONE	< 0.16	< 0.16	< 0.16
-------------------	------	------	------	--------	--------	--------

#### Heavy Metals / Metalloids

Arsenic (dissolved)	µg/l	0.15	NONE	0.38	0.48	0.34
Cadmium (dissolved)	µg/l	0.02	NONE	< 0.02	0.02	0.02
Chromium (dissolved)	µg/l	0.2	NONE	0.4	1.6	0.3
Copper (dissolved)	µg/l	0.5	NONE	1.9	1.4	2.6
Lead (dissolved)	µg/l	0.2	NONE	< 0.2	0.7	< 0.2
Mercury (dissolved)	µg/l	0.05	NONE	< 0.05	< 0.05	< 0.05
Nickel (dissolved)	µg/l	0.5	NONE	2.6	1.6	9
Selenium (dissolved)	µg/l	0.6	NONE	0.7	1.3	2.3
Zinc (dissolved)	µg/l	0.5	NONE	14	2.3	4.3

Calcium (dissolved)	mg/l	0.012	NONE	51	48	76
Chromium (hexavalent)	µg/l	5	NONE	< 5.0	< 5.0	< 5.0

Analytical Report Number: 25-007184  
Project / Site name: Grove House, Sellindge

Your Order No: 25-2-FDO-LABS

Lab Sample Number	453856	453857	453858
Sample Reference	MWS101	MWS104	MWS106
Sample Number	None Supplied	None Supplied	None Supplied
Water Matrix	Other water	Other water	Other water
Depth (m)	None Supplied	None Supplied	None Supplied
Date Sampled	13/02/2025	13/02/2025	13/02/2025
Time Taken	None Supplied	None Supplied	None Supplied
Analytical Parameter (Water Analysis)	Units	Test Limit of detection	Test Accreditation Status

#### Petroleum Hydrocarbons

TPH - Aliphatic >EC5 - EC6 <sub>HS_1D_AL</sub>	µg/l	1	NONE	< 1.0	< 1.0	< 1.0
TPH - Aliphatic >EC6 - EC8 <sub>HS_1D_AL</sub>	µg/l	1	NONE	< 1.0	< 1.0	< 1.0
TPH - Aliphatic >EC8 - EC10 <sub>HS_1D_AL</sub>	µg/l	1	NONE	< 1.0	< 1.0	< 1.0
TPH - Aliphatic >EC10 - EC12 <sub>EH_1D_AL_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aliphatic >EC12 - EC16 <sub>EH_1D_AL_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aliphatic >EC16 - EC21 <sub>EH_1D_AL_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aliphatic >EC21 - EC35 <sub>EH_1D_AL_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aliphatic >EC5 - EC35 <sub>HS+EH_1D_AL_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10

TPH - Aromatic >EC5 - EC7 <sub>HS_1D_AR</sub>	µg/l	1	NONE	< 1.0	< 1.0	< 1.0
TPH - Aromatic >EC7 - EC8 <sub>HS_1D_AR</sub>	µg/l	1	NONE	< 1.0	< 1.0	< 1.0
TPH - Aromatic >EC8 - EC10 <sub>HS_1D_AR</sub>	µg/l	1	NONE	< 1.0	< 1.0	< 1.0
TPH - Aromatic >EC10 - EC12 <sub>EH_1D_AR_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aromatic >EC12 - EC16 <sub>EH_1D_AR_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aromatic >EC16 - EC21 <sub>EH_1D_AR_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aromatic >EC21 - EC35 <sub>EH_1D_AR_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10
TPH - Aromatic >EC5 - EC35 <sub>HS+EH_1D_AR_MS</sub>	µg/l	10	NONE	< 10	< 10	< 10

#### VOCs

MTBE (Methyl Tertiary Butyl Ether)	µg/l	3	NONE	< 3.0	< 3.0	< 3.0
Benzene	µg/l	3	NONE	< 3.0	< 3.0	< 3.0
Toluene	µg/l	3	NONE	< 3.0	< 3.0	< 3.0
Ethylbenzene	µg/l	3	NONE	< 3.0	< 3.0	< 3.0
p & m-xylene	µg/l	3	NONE	< 3.0	< 3.0	< 3.0
o-xylene	µg/l	3	NONE	< 3.0	< 3.0	< 3.0

U/S = Unsuitable Sample I/S = Insufficient Sample ND = Not detected

**Analytical Report Number : 25-007184**

**Project / Site name: Grove House, Sellindge**

**Water matrix abbreviations:**

**Surface Water (SW) Potable Water (PW) Ground Water (GW) Process Waters Heating/Cooling (PrW) DI Process Water (DI PrW)**

**Final Sewage Effluent (FSE) Landfill Leachate (LL)**

Analytical Test Name	Analytical Method Description	Analytical Method Reference	Method number	Wet / Dry Analysis	Accreditation Status
Metals in water by ICP-MS (dissolved)	Determination of metals in water by acidification followed by ICP-MS. Accredited matrices: SW, PW, GW, except B - SW, GW, Hg - SW, PW, Al - SW, PW	In-house method based on USEPA Method 6020 & 200.8 for the determination of trace elements in water by ICP-MS	L012B	W	NONE
Sulphide in water	Determination of sulphide in water by ion selective electrode	In-house method	L029-PL	W	NONE
Dissolved Organic Carbon in water	Determination of dissolved organic carbon in water by TOC/DOC NDIR Analyser. Accredited matrices: SW, PW, GW, FSE, LL	In-house method based on Examination of Water and Wastewater 20th Edition: Clesceri, Greenberg & Eaton	L037B	W	NONE
Sulphate in water	Determination of sulphate in water after filtration by acidification followed by ICP-OES. Accredited matrices: SW, PW, GW, PrW, DI PrW, FSE, LL	In-house method based on MEWAM 2006 Methods for the Determination of Metals in Soil	L039B	W	NONE
Total Petroleum Hydrocarbons with carbon banding in water by GC-MS	Determination of total petroleum hydrocarbons in water by GC-MS with carbon banding aliphatic and aromatic	In-house method	L070B	W	NONE
BTEX and/or Volatile Organic Compounds in water	Determination of volatile organic compounds in water by headspace GC-MS. Accredited matrices: SW, PW, GW	In-house method based on USEPA 8260	L073B	W	NONE
Hexavalent chromium in water	Determination of hexavalent chromium in water by acidification, addition of 1,5-diphenylcarbazide, followed by colorimetry. Accredited matrices: SW, PW, GW, FSE, LL	In-house method by continuous flow analyser	L080-PL	W	NONE
Monohydric phenols in water	Determination of phenols in water by continuous flow analyser. Accredited matrices: SW, PW, GW, FSE, LL	In-house method based on Examination of Water and Wastewater 20th Edition: Clesceri, Greenberg & Eaton	L080-PL	W	NONE
Total cyanide in water	Determination of total cyanide in water by distillation followed by colorimetry. Accredited matrices: SW, PW, GW, FSE, LL	In-house method based on Examination of Water and Wastewater 20th Edition: Clesceri, Greenberg & Eaton	L080-PL	W	NONE
Total Petroleum Hydrocarbons in water by HS-GC-MS	Determination of total petroleum hydrocarbons in water by headspace GC-MS. Accredited matrices: SW, PW, GW	In-house method	L088-PL	W	NONE
pH of water at 20°C (automated)	Determination of pH of water by electrochemical measurement. Accredited matrices: SW, PW, GW, FSE, LL	In-house method	L099-PL	W	NONE
Speciated PAHs and/or Semi-volatile organic compounds in water	Determination of semi-volatile organic compounds (including PAHs) in water by extraction in dichloromethane followed by GC-MS. Accredited matrices (PAHs): SW, PW, GW	In-house method based on USEPA 8270	L102B	W	NONE
Metals in water by ICP-OES (dissolved)	Determination of metals in water by acidification followed by ICP-OES. Accredited matrices: SW, PW, GW, FSE, LL; PrW, DI PrW (Al, Cu, Fe, Zn)	In-house method based on MEWAM 2006 Methods for the Determination of Metals in Soil	L039B	W	NONE

**For method numbers ending in 'UK' or 'A' analysis have been carried out in our laboratory in the United Kingdom (Watford).**

**For method numbers ending in 'F' analysis have been carried out in our laboratory in the United Kingdom (East Kilbride).**

**For method numbers ending in 'PL' or 'B' analysis have been carried out in our laboratory in Poland.**

**Soil analytical results are expressed on a dry weight basis. Where analysis is carried out on as-received the results obtained are multiplied by a moisture correction factor that is determined gravimetrically using the moisture content which is carried out at a maximum of 30°C.**

**Unless otherwise indicated, site information, order number, project number, sampling date, time, sample reference and depth are provided by the client. The instructed on date indicates the date on which this information was provided to the laboratory.**

Analytical Report Number : 25-007184

Project / Site name: Grove House, Sellindge

Water matrix abbreviations:

Surface Water (SW) Potable Water (PW) Ground Water (GW) Process Waters Heating/Cooling (PrW) DI Process Water (DI PrW)

Final Sewage Effluent (FSE) Landfill Leachate (LL)

Analytical Test Name	Analytical Method Description	Analytical Method Reference	Method number	Wet / Dry Analysis	Accreditation Status
----------------------	-------------------------------	-----------------------------	---------------	--------------------	----------------------

#### Information in Support of Analytical Results

##### List of HWOL Acronyms and Operators

Acronym	Descriptions
HS	Headspace Analysis
MS	Mass spectrometry
FID	Flame Ionisation Detector
GC	Gas Chromatography
EH	Extractable Hydrocarbons (i.e. everything extracted by the solvent(s))
CU	Clean-up - e.g. by Florisil®, silica gel
1D	GC - Single coil/column gas chromatography
2D	GC-GC - Double coil/column gas chromatography
Total	Aliphatics & Aromatics
AL	Aliphatics
AR	Aromatics
#1	EH_2D_Total but with humics mathematically subtracted
#2	EH_2D_Total but with fatty acids mathematically subtracted
-	Operator - underscore to separate acronyms (exception for +)
+	Operator to indicate cumulative e.g. EH+HS_Total or EH_CU+HS_Total

Quality control parameter failure associated with individual result applies to calculated sum of individuals.

The result for sum should be interpreted with caution

**APPENDIX 9**

- Field Monitoring Records
- Groundwater Level Data
- Hazardous Soil Gas Data

GAS MONITORING RECORD ROUND 1

Location Reference	Time	Flow and Pressure Measurements				Gas Measurements								VOC Measurements		Dip Measurements		Comments	
		Flow		Atmospheric Pressure	Differential Pressure	Methane Max	Methane Steady	Methane LEL	Carbon Dioxide Max	Carbon Dioxide Steady	Oxygen	Carbon Monoxide	Hydrogen Sulphide	Time Taken to Reach Steady State	Hexane	PID	Depth to Water		Depth to Base
		max	steady																
		l hr <sup>-1</sup>																	
MWS101	14:28	0	0	1018	0	0	0	0	0.9	0.9	19.6	0	0	20.000	0.000	0	0.84	2.66	-
MWS104	14:47	0	0	1018	0	0	0	0	0.5	0	20.7	0	60	60.000	0.000	0	1.42	3.08	-
MWS106	10:59	0	0	1017	0	0	0	0	0.8	0.8	19	0	0	30.000	0.000	0	1.30	3.10	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0.00	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Weather:		Overcast and dry. Atmospheric pressure remains steady for the past 12 hours.				nr = not recorded				Gas Analyser		PID		Site:				Grove House, Sellindge	
						Model:				-		-		Project Number:				22653H	
						Serial Number:				-		-		Monitored By:				Ben Alexander	
						Date of Last Calibration:				-		-		Date:				03/02/2025	

GAS MONITORING RECORD ROUND 2

Location Reference	Time	Flow and Pressure Measurements				Gas Measurements									VOC Measurements		Dip Measurements		Comments
		Flow		Atmospheric Pressure	Differential Pressure	Methane Max	Methane Steady	Methane LEL	Carbon Dioxide Max	Carbon Dioxide Steady	Oxygen	Carbon Monoxide	Hydrogen Sulphide	Time Taken to Reach Steady State	Hexane	PID	Depth to Water	Depth to Base	
		max	steady																
		l hr <sup>-1</sup>																	
MWS101	14:30	0	0	1016	0	0	0	0	1.9	1.9	17.9	0	0		0.000	1	0.85	2.60	Groundwater sample taken
MWS104	14:40	0	0	1015	0	0	0	0	0.9	0.9	19.9	0	0		0.000	0	0.92	3.00	Groundwater sample taken
MWS106	14:50	0	0	1014	0	0	0	0	1.6	1.6	17.5	0	0		0.000	0	1.20	2.95	Groundwater sample taken
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
Weather:		Overcast and dry. Atmospheric pressure rising for the past 12 hours.				nr = not recorded					Gas Analyser		PID		Site:			Grove House, Sellindge	
						Model:					-		-		Project Number:			22653H	
						Serial Number:					-		-		Monitored By:			Matt Baylis	
						Date of Last Calibration:					-		-		Date:			13/02/2025	

GAS MONITORING RECORD ROUND 3

Location Reference	Time	Flow and Pressure Measurements				Gas Measurements								VOC Measurements		Dip Measurements		Comments	
		Flow		Atmospheric Pressure	Differential Pressure	Methane Max	Methane Steady	Methane LEL	Carbon Dioxide Max	Carbon Dioxide Steady	Oxygen	Carbon Monoxide	Hydrogen Sulphide	Time Taken to Reach Steady State	Hexane	PID	Depth to Water		Depth to Base
		max	steady																
		l hr <sup>-1</sup>																	
MWS101	15:05	0	0	1006	0	0	0	0	1.3	1.3	18.1	0	0		0.009	0	1.68	2.38	Hole fitted with piezometer - unable to measure base depth
MWS104	15:25	0	0	1005	0	0	0	0	0.7	0.7	19.6	0	0		0.002	0	1.77	3.08	Hole fitted with piezometer - unable to measure base depth
MWS106	15:40	0	0	1004	0	0	0	0	1.1	1.1	17.9	1	0		0.002	0	2.17	2.60	Hole fitted with piezometer - unable to measure base depth
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
Weather:		Overcast and dry, pressure steady for last 6 hours				nr = not recorded					Gas Analyser		PID		Site:		Grove House, Sellindge		
						Model:					GFM 436		MiniRae Lite		Project Number:		22653H		
						Serial Number:					13702		590-904749		Monitored By:		Thea James		
						Date of Last Calibration:					26/07/2024		27/11/2024		Date:		25/02/2025		

Location Reference	Time	Flow and Pressure Measurements				Gas Measurements									VOC Measurements		Dip Measurements		Comments
		Flow		Atmospheric Pressure	Differential Pressure	Methane Max	Methane Steady	Methane LEL	Carbon Dioxide Max	Carbon Dioxide Steady	Oxygen	Carbon Monoxide	Hydrogen Sulphide	Time Taken to Reach Steady State	Hexane	PID	Depth to Water	Depth to Base	
		max	steady																
		l hr <sup>-1</sup>		mb	Pa	%	%	%	%	%	%	ppm	ppm	s	%	ppm	m	m	
MWS101	-	-	-	-	-	-	-	-	-	-	-	-	nr		-	nr	-	-	-
MWS104	-	-	-	-	-	-	-	-	-	-	-	-	nr		-	nr	-	-	-
MWS106	-	-	-	-	-	-	-	-	-	-	-	-	nr		-	nr	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
Weather:		0.0				nr = not recorded				Gas Analyser		PID		Site:			Grove House, Sellindge		
						Model:				-		-		Project Number:			22653H		
						Serial Number:				-		-		Monitored By:			0		
						Date of Last Calibration:				-		-		Date:			00/01/1900		

GAS MONITORING RECORD ROUND 5

Location Reference	Time	Flow and Pressure Measurements				Gas Measurements								VOC Measurements		Dip Measurements		Comments		
		Flow		Atmospheric Pressure	Differential Pressure	Methane Max	Methane Steady	Methane LEL	Carbon Dioxide Max	Carbon Dioxide Steady	Oxygen	Carbon Monoxide	Hydrogen Sulphide	Time Taken to Reach Steady State	Hexane	PID	Depth to Water		Depth to Base	
		max	steady																	
		l hr <sup>-1</sup>																		
MWS101	-	-	-	-	-	-		-	-		-	-	nr		-	nr	-	-	-	
MWS104	-	-	-	-	-	-		-	-		-	-	nr		-	nr	-	-	-	
MWS106	-	-	-	-	-	-		-	-		-	-	nr		-	nr	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
-	-	-	-	-	-	-		-	-		-	-	-		-	-	-	-	-	
Weather:		0.0				nr = not recorded					Gas Analyser		PID		Site:				Grove House, Sellindge	
						Model:					-		-		Project Number:				22653H	
						Serial Number:					-		-		Monitored By:				0	
						Date of Last Calibration:					-		-		Date:				00/01/1900	

Location Reference	Time	Flow and Pressure Measurements				Gas Measurements								VOC Measurements		Dip Measurements		Comments	
		Flow		Atmospheric Pressure	Differential Pressure	Methane Max	Methane Steady	Methane LEL	Carbon Dioxide Max	Carbon Dioxide Steady	Oxygen	Carbon Monoxide	Hydrogen Sulphide	Time Taken to Reach Steady State	Hexane	PID	Depth to Water		Depth to Base
		max	steady																
		l hr <sup>-1</sup>		mb	Pa	%	%	%	%	%	%	ppm	ppm	s	%	ppm	m		m
MWS101	-	-	-	-	-	-	-	-	-	-	-	-	nr		-	nr	-	-	-
MWS104	-	-	-	-	-	-	-	-	-	-	-	-	nr		-	nr	-	-	-
MWS106	-	-	-	-	-	-	-	-	-	-	-	-	nr		-	nr	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-
Weather:		0.0				nr = not recorded				Gas Analyser		PID		Site:			Grove House, Sellindge		
						Model:				-		-		Project Number:			22653H		
						Serial Number:				-		-		Monitored By:			0		
						Date of Last Calibration:				-		-		Date:			00/01/1900		

**APPENDIX 10**   ■   Gas Risk Assessment

Industrial style building having large volume internal space(s) that are well ventilated. Corporate ownership with building management controls on alterations to the ground floor and basement areas of the building and on maintenance of ground gas protective measures. Probably civil engineering construction. Examples are retail park sales buildings, factory shop floor areas, warehouses. (Small rooms within these style buildings should be separately categorized as Type B or Type C).

# IDOM

IDOM Cromford Mills, Mill Lane, Matlock, Derbyshire DE4 3RQ  
t +44 (0)1773 829 988 e [info.derbyshire@idom.com](mailto:info.derbyshire@idom.com) **idom.com**  
Registered in England No. 02740216 Registered office: as above